



Conductive Neoprene Bench/Floor Mat

Extra tough conductive matting



- Heavy-duty neoprene rubber for demanding environments.
- Suitable as an ESD work surface mat or hardwearing anti-static floor mat.
- Solder iron resistant and low reflecting, ideal for electrical component manufacturing and refurbishment.
- Hardwearing Neoprene is heat, chemical, oil, fire and ozone resistant.
- Grounded via a 10 mm male stud fitted to the mat.
- Conforms to IEC 61340-5-1.
- Point to point resistance (Rp-p): $1.8 \times 10^8 \Omega$
- Resistance to a groundable point (Rgp): $4.3 \times 10^6 \Omega$

Parts

Part Number	Size	Colour	Weight
CBF010004	0.6 m x 1.2 m x 2 mm	Black	2.45 kg

Technical Specification

Material	NBR
Surface Finish	Smooth
Product Height	2 mm
Operating Temperature	-30°C to +70°C
Environmental Resistance	Suitable for dry indoor environments
Accessories	ESD accessories available
Country of Origin	China

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Antistatic Control Products](#) category:

Click to view products by [COBA](#) manufacturer:

Other Similar products are found below :

[14404](#) [2202SP](#) [37061](#) [42470](#) [09813](#) [09857](#) [09037](#) [09813](#) [68101](#) [68103](#) [73741](#) [13457](#) [13245](#) [13420](#) [13205](#) [91070](#) [66085](#) [13080](#) [010-0115](#)
[013-0010](#) [13390](#) [09121](#) [07501](#) [09204](#) [66086](#) [66121](#) [16316](#) [ZJ-SD100](#) [1900-8X12](#) [1910-10X12](#) [82A3](#) [1900-6X8](#) [1900-7-15](#) [19866](#) [20-082-](#)
[1012](#) [STS1327](#) [STW404111](#) [20-871-1418](#) [20-871-1624](#) [20-871-1818](#) [20-871-1824](#) [20-872-1418](#) [53707](#) [ELSEC 5/10](#) [52889](#) [52867](#) [52865](#)
[52849](#) [52870](#) [52843](#)