



Deckplate Anti Fatigue Mat

Fatigue relief in demanding environments



- Reduce standing fatigue for workers in industry.
- Dual layer mat provides balance of comfort and wear resistance.
- Hardwearing top surface ensures a long life in normal use.
- Checker plate style design suits industrial environments.
- Self-extinguishing top surface (tested to BS EN 13501-1) provides resilience to many industrial chemicals.
- High visibility version available with bright yellow borders.
- Bevelled edges help avoid creating a trip risk.



Styles Available



Standard

Safety

Parts

Part Number	Size	Colour	Weight
DP010609	0.6 m x 0.9 m	Black	3.54 kg
DP010004	0.6 m x 18.3 m	Black	71.92 kg
DP010004C	0.6 m x per linear metre	Black	3.93 kg
DP010915	0.9 m x 1.5 m	Black	8.86 kg
DP010903	0.9 m x 3 m	Black	17.71 kg
DP010906	0.9 m x 6 m	Black	35.42 kg

Technical Specification

Material	Vinyl top surface with PVC foam backing (fusion bonded, not glued)
Surface Finish	Diamond pattern
Product Height	15 mm
Roll Length	18.3 m
Operating Temperature	0°C to +60°C
Resistance to	The PVC top surface provides limited resistance to

DP010005	0.9 m x 18.3 m	Black	108.00 kg
DP010005C	0.9 m x per linear metre	Black	8.00 kg
DP010007	1.2 m x 18.3 m	Black	166.00 kg
DP010007C	1.2 m x per linear metre	Black	9.00 kg
SD010701	0.6 m x 0.9 m	Black/Yellow	4.00 kg
SD010702	0.9 m x 1.5 m	Black/Yellow	11.00 kg
SD010703	0.9 m x 3 m	Black/Yellow	22.00 kg
SD010704	0.9 m x 6 m	Black/Yellow	44.00 kg
SD010706	0.6 m x 18.3 m	Black/Yellow	93.00 kg
SD010706C	0.6 m x per linear metre	Black/Yellow	8.00 kg
SD010707	0.9 m x 18.3 m	Black/Yellow	166.00 kg
SD010707C	0.9 m x per linear metre	Black/Yellow	6.00 kg
SD010708	1.2 m x 18.3 m	Black/Yellow	9.70 kg
SD010708C	1.2 m x per linear metre	Black/Yellow	178.00 kg
DP010011C	1.5 m x per linear metre	Black	9.7 kg
DP010011	1.5 m x 15 m	Black	178.00 kg
SD010709C	1.5 m x per linear metre	Black/Yellow	9.7 kg
SD010709	1.5 m x 15 m	Black/Yellow	178.00 kg

Chemicals	chemicals and oils
Environmental Resistance	Suitable for dry indoor environments
Typical Applications	Packing stations, Assembly areas, Production lines where regular turning occurs
Installation Method	Loose lay
Cleaning Method	Brush/mop the top surface
Fire Tested to	BS EN 13501-1 Class Cfl - s1
Country of Origin	China
Guarantee	3 years when used in a dry environment

Get in touch | To order FREE samples or arrange a site visit please call +44 (0)116 240 1088 or email sales@cobaeurope.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [PPE Safety Equipment / Lockout Tagout](#) category:

Click to view products by [COBA](#) manufacturer:

Other Similar products are found below :

[AB12-SF1260](#) [GPSL-6KA](#) [GPSL-8MKEY](#) [35035](#) [702201756](#) [PSL-PC38-33](#) [7100078986](#) [132231](#) [44-809](#) [G3000NUV-VI-R](#) [STC1165](#)
[STC5951](#) [WC000003](#) [509-0015](#) [509-0017](#) [509-0019](#) [509-0020](#) [509-0021](#) [509-0022](#) [509-0002](#) [509-0003](#) [509-0004](#) [509-0006](#) [109-0920](#)
[109-0917](#) [109-0918](#) [109-0919](#) [DYC200-01-01-9-DYCLEAN-S](#) [109-0027](#) [X2A](#) [26702](#) [28774](#) [SFTY PADLOCK NYLON 38MM SHA](#)
[YELLOW 6/PAC](#) [FMFR 12](#) [FMFR 12-AUT](#) [FMFR 14](#) [FMFR 14 MIDI](#) [FMFR 18](#) [FMFR 38](#) [FML 12](#) [FML 14](#) [FML 14 MIDI](#) [FML 18](#)
[FMR 12](#) [FMR 18](#) [FMR 38](#) [603](#) [30-551-3040](#) [30-552-0010](#) [30-552-6012](#)