



## Fatigue-Step Anti Slip Comfort Mat

Fatigue relief for large, wet and oily shop floors



- Tiles link together to provide an anti-fatigue surface for particularly wet or oily areas.
- Soft, yet resilient rubber floor tiles.
- Open holes allow efficient drainage of spilt liquids.
- Effective anti-fatigue properties for prolonged standing.
- Main tiles available in two options:
  - Standard
  - Nitrile
- Nitrile option has excellent resistance to oils, chemicals and grease.
- Slip tested to DIN 51130.
- Optional ramped edging in yellow or black.



### Parts

Part Number	Size	Colour	Weight
SS010001	0.9 m x 0.9 m	Black	9.95 kg
SS020001	0.9 m x 0.9 m	Blue	10.00 kg
SS010007	0.9 m x 0.9 m	Nitrile	10.00 kg
SS010002F	Female Corner Edge	Black	1.00 kg
SS070002F	Female Corner Edge	Yellow	1.00 kg
SS010002M	Male Corner Edge	Black	1.30 kg
SS070002F	Female Corner Edge	Yellow	1.00 kg
SS010002FN	Female Corner Edge Nitrile	Black	1.00 kg
SS070002FN	Female Corner Edge Nitrile	Yellow	1.00 kg
SS010002MN	Male Corner Edge Nitrile	Black	1.00 kg
SS070002MN	Male Corner Edge Nitrile	Yellow	1.30 kg
SS070002B1F	Female Corner Edge B1	Yellow	1.00 kg
SS070002B1M	Male Corner Edge B1	Yellow	1.30 kg

### Technical Specification

<b>Material</b>	Rubber mix, including >50% recycled material
<b>Surface Finish</b>	Textured with holes to allow drainage
<b>Product Height</b>	18 mm
<b>Hole Size</b>	22 mm
<b>Operating Temperature</b>	-20°C to +130°C
<b>Resistance to Chemicals</b>	Natural rubber offers limited resistance to chemicals and oils
<b>Environmental Resistance</b>	Suitable for wet and dry environments. Will withstand welding splatter and spillages of other hot materials.
<b>UV Resistance</b>	Yes
<b>Typical Applications</b>	All industrial environments, Bars, Catering environments, Areas where swarf is prevalent
<b>Installation Method</b>	Loose lay interlocking tiles

SS010002B1F	Female Corner Edge B1	Black	1.00 kg
SS010002B1M	Male Corner Edge B1	Black	1.30 kg

<b>Accessories</b>	Bevelled corner edges
<b>Cleaning Method</b>	Wash with cold water, use vacuum cleaner or use pressure pump to remove dirt
<b>Country of Origin</b>	India
<b>Storage and application</b>	Store at room temperature, free from deformations.
<b>Tensile Strength</b>	3 to 3.5 MPa
<b>Notes</b>	Silicone is used in the production process of the mats and a residue will possibly be left on the mat
<b>Slip Tested to</b>	DIN 51130 - R10

Get in touch | To order FREE samples or arrange a site visit please call +44 (0)116 240 1088 or email [sales@cobaeurope.com](mailto:sales@cobaeurope.com)

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [PPE Safety Equipment / Lockout Tagout](#) category:*

*Click to view products by [COBA](#) manufacturer:*

Other Similar products are found below :

[AB12-SF1260](#) [GPSL-6KA](#) [GPSL-8MKEY](#) [35035](#) [702201756](#) [PSL-PC38-33](#) [7100078986](#) [132231](#) [44-809](#) [G3000NUV-VI-R](#) [STC1165](#)  
[STC5951](#) [DAF010701](#) [WC000003](#) [509-0015](#) [509-0017](#) [509-0019](#) [509-0020](#) [509-0021](#) [509-0022](#) [509-0002](#) [509-0003](#) [509-0004](#) [509-0006](#)  
[109-0920](#) [109-0917](#) [109-0918](#) [109-0919](#) [DYC200-01-01-9-DYCLEAN-S](#) [109-0027](#) [X2A](#) [26702](#) [28774](#) [SFTY PADLOCK NYLON 38MM](#)  
[SHA YELLOW 6/PAC](#) [FMB12](#) [FMB14](#) [FMB14 MIDI](#) [FMB18](#) [FMB38](#) [FMFR 12](#) [FMFR 12-AUT](#) [FMFR 14](#) [FMFR 14 MIDI](#) [FMFR 18](#)  
[FMFR 38](#) [FML 12](#) [FML 14](#) [FML 14 MIDI](#) [FML 18](#) [FMR 12](#)