


# Shielded Power Inductors – SLR1050



- Tight DCR tolerance for inductor-DCR-based current sensing circuits
- Three versions for optimal efficiency and accuracy
- Excellent current handling
- 10.2 × 7.0 × 4.95 mm surface mount package
- Designed for use in multi-phase VRM/VRD/EVRD regulators

**Designer's Kit C467** contains 3 each of select values.

**Core material** Ferrite

**Weight** 1.2 – 1.4 g

**Environmental** RoHS compliant, halogen free

**Terminations** RoHS compliant matte tin over nickel over copper.

**Ambient temperature** –40°C to +85°C with Irms current

**Maximum part temperature** +125°C (ambient + temp rise). [Derating](#).

**Storage temperature** Component: –40°C to +125°C.

Tape and reel packaging: –40°C to +80°C




**Resistance to soldering heat** Max three 40 second reflows at +260°C, parts cooled to room temperature between cycles

**Moisture Sensitivity Level (MSL)** 1 (unlimited floor life at <30°C / 85% relative humidity)


**Failures in Time (FIT) / Mean Time Between Failures (MTBF)**

38 per billion hours / 26,315,789 hours, calculated per Telcordia SR-332

**PCB washing** Tested to MIL-STD-202 Method 215 plus an additional aqueous wash. See [Doc787 PCB Washing.pdf](#).




### Recommended Land Pattern



Dimensions are in  $\frac{\text{inches}}{\text{mm}}$

### Typical Temperature Rise (from 25°C)



**Packaging** 250/7" reel; 1000/13" reel; Plastic tape: 24 mm wide, 0.4 mm thick, 12 mm pocket spacing, 5.03 mm pocket depth

**NEW!**

# SLR1050 Shielded Power Inductors



Part number <sup>1</sup>	Inductance <sup>2</sup> ±10% (nH)	DCR <sup>3</sup> (mOhms)	SRF typ (MHz)	Isat (A) <sup>4</sup>			Irms (A) <sup>5</sup>	
				at 25°C	at 100°C	at 125°C	20°C rise	40°C rise
<b>Lowest DCR</b>								
SLR1050A-850KE_	85	0.39 ±7.7%	210	86	68.0	60.5	56.7	77.1
SLR1050A-101KE_	100	0.39 ±7.7%	200	78	61.5	55.0	56.7	77.1
SLR1050A-121KE_	120	0.39 ±7.7%	180	65	51.0	48.0	56.7	77.1
SLR1050A-151KE_	150	0.39 ±7.7%	90	51	38.0	36.0	56.7	77.1
SLR1050A-221KE_	220	0.39 ±7.7%	65	35	25.5	23.5	56.7	77.1
<b>Balanced DCR/tolerance</b>								
SLR1050B-850KE_	85	0.47 ±6.7%	210	86	68.0	60.5	48.8	67.2
SLR1050B-101KE_	100	0.47 ±6.7%	200	78	61.5	55.0	48.8	67.2
SLR1050B-121KE_	120	0.47 ±6.7%	180	65	51.0	48.0	48.8	67.2
SLR1050B-151KE_	150	0.47 ±6.7%	90	51	38.0	36.0	48.8	67.2
SLR1050B-221KE_	220	0.47 ±6.7%	65	35	25.5	23.5	48.8	67.2
<b>Tightest DCR tolerance</b>								
SLR1050C-850KE_	85	0.55 ±5.4%	210	86	68.0	60.5	46.7	65.0
SLR1050C-101KE_	100	0.55 ±5.4%	200	78	61.5	55.0	46.7	65.0
SLR1050C-121KE_	120	0.55 ±5.4%	180	65	51.0	48.0	46.7	65.0
SLR1050C-151KE_	150	0.55 ±5.4%	90	51	38.0	36.0	46.7	65.0
SLR1050C-221KE_	220	0.55 ±5.4%	65	35	25.5	23.5	46.7	65.0

1. When ordering, please specify **version** and **packaging** codes:

SLR1050C-221KEC

- Version**    **A** = Lowest DCR; **B** = Balanced DCR/DCR tol;  
                   **C** = Tightest DCR tolerance
- Packaging:** **C** = 7" machine-ready reel. EIA-481 embossed plastic tape (250 parts per full reel).
- B** = Less than full reel. In tape, but not machine ready. To have a leader and trailer added (\$25 charge), use code letter C instead.
- D** = 13" machine-ready reel. EIA-481 embossed plastic tape. Factory order only, not stocked (1000 parts per full reel).

2. Inductance at 100 kHz, 0.1 Vrms, 0 Adc.  
 3. DCR is measured on a micro-ohmmeter at points indicated in the diagram



4. DC current at 25°C that causes an inductance drop of 20% (typ) from its value without current. [Click for temperature derating information.](#)  
 5. Current that causes the specified temperature rise from 25°C ambient. This information is for reference only and does not represent absolute maximum ratings. [Click for temperature derating information.](#)  
 6. Electrical specifications at 25°C.

Refer to Doc 362 "Soldering Surface Mount Components" before soldering.

## Irms Testing

Irms testing was performed on 0.75 inch wide × 0.25 inch thick copper traces in still air.


Temperature rise is highly dependent on many factors including pcb land pattern, trace size, and proximity to other components. Therefore temperature rise should be verified in application conditions.

**NEW!**






# SLR1050 Shielded Power Inductors



## L vs Current



## L vs Frequency



**US** +1-847-639-6400 sales@coilcraft.com  
**UK** +44-1236-730595 sales@coilcraft-europe.com  
**Taiwan** +886-2-2264 3646 sales@coilcraft.com.tw  
**China** +86-21-6218 8074 sales@coilcraft.com.cn  
**Singapore** + 65-6484 8412 sales@coilcraft.com.sg

Document 1255-3 Revised 06/01/16

© Coilcraft Inc. 2017

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check web site for latest information.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Fixed Inductors](#) category:*

*Click to view products by [Coilcraft](#) manufacturer:*

Other Similar products are found below :

[CR32NP-100KC](#) [CR54NP-470LC](#) [70F224AI](#) [MGDQ4-00004-P](#) [MHQ1005P10NJ](#) [MHQ1005P1N0S](#) [MHQ1005P2N4S](#) [MHQ1005P3N6S](#)  
[MHQ1005P5N1S](#) [MHQ1005P8N2J](#) [PE-53601NL](#) [PE-53602NL](#) [PG0936.113NLT](#) [9220-20](#) [9310-16](#) [PM06-2N7](#) [PM06-39NJ](#) [A01TK](#)  
[1206CS-471XJ](#) [HC8-1R2-R](#) [HCF1305-3R3-R](#) [1206CS-151XG](#) [RCH664NP-140L](#) [RCP1317NP-391L](#) [RCR110DNP-331L](#) [DH2280-4R7M](#)  
[DS1608C-106](#) [B10TJ](#) [B82498B3101J000](#) [ELJ-RE27NJF2](#) [1812CS-153XJ](#) [1812CS-183XJ](#) [1812CS-223XJ](#) [1812LS-104XJ](#) [1812LS-105XJ](#)  
[1812LS-124XJ](#) [1812LS-154XJ](#) [1812LS-223XJ](#) [1812LS-224XJ](#) [1812LS-563XJ](#) [1812LS-683XJ](#) [1812LS-824XJ](#) [NIN-FA4R7JTR220F](#) [NIN-](#)  
[FB101JTR110F](#) [NIN-FB471JTR62F](#) [NIN-FC1R5JTR220F](#) [NIN-HCR15JTRF](#) [NIN-HCR33JTRF](#) [NIN-HDR22JTRF](#) [NIN-HDR82JTRF](#)