



SPECIFICATION FOR APPROVAL

产品规格承认书

Multilayer Ferrite Bead

贴片共模绕线电感

CUSTOMER.

MODEL NO.

MACM1211-102

CUSTOMER'S PART NO.

LILE NO.

DATE.

2021/9/24

REVISION.

A/0

CUSTOMER APPROVE		
DATE:		
DRAWING		
DRAWN BY	CHECK BY	APPROVAL BY
DATE:		



深圳市迈翔科技有限公司
SHENZHEN MOTTO TECHNOLOGY Co., Ltd

香港瑞德科技有限公司 黄冈市迈翔电子有限公司
Motto Technology park, niu e ling village no#214 xintian,nghua Town,
Guanlan Street, Longhua District, Shenzhen

TEL: +86 0755-8948751~2 89487610 Fax: +86 0755-61624574

[Http://www.coilmx.com](http://www.coilmx.com) E-mail: sales@mottotech.com

CUSTOMER		MODEL NO.	MACM1211-102	A/0
FILE NO.		PART NO.		2021/9/24

1.PRODUCT DIMENSION		UNIT:mm	
	A	12.0±0.5	
	A1	12.0±0.5	
	B	10.8±0.5	
	C	6.4Max	
	D	7.0Typ	
	E	2.7±0.2	
	F	2.5±0.2	
	G	2.5±0.2	

2.ELECTRICAL REQUIREMENTS							
Part Number 型号	Impedance At 100MHZ 阻抗 Z (Ω)		Insulation resistance 绝缘阻抗 IR(MΩ)Min	DC Resistance 直 流电阻抗 RDC (mΩ)Max	Rated Current 额 定电流 Ir(A)Max	Rated Voltage 额 定电压 VDC(V) max	印字
MACM1211-102	750	1000	10	14	6.0	125	102

3.CHARACTERISTICS
(1). All test data is based on 25°C ambient.
(2). DC current(A)that will cause L0 to drop approximately 30%Typ
(3). Operating temperature range: -55°C~+125°C
(4).The part temperature (ambient + temp rise)should not exceed 125°C under worst case operating conditions. circuit design, component.PWB trace size and thickness,airflow and other cooling provision all affect the part temperature. Part temperature should be verified in the den application



深圳市迈翔科技有限公司

CUSTOMER		MODEL NO.	MACM1211-102		A/0
FILE NO.		PART NO.			2021/9/24

4.PRODUCT IDENTIFICATION

XXX XXXX X X XXX X

① ② ③ ④ ⑤ ⑥

①.Coilmx Series Name ②.Dimensions

③.General characteristics ④.Tapde in reel 2000pcs/reel

⑤.Typical impedance at 100MHz ⑥.Tolerance: J:±5%,K:±10%,M±20%, S±25%, N±30%.

5.APPLICATION

- (1)High frequency circuits of telecommunication.
- (2)Mobile phones such as GSM,CDMA,PDC,etc.
- (3)Bluetooth.
- (4)Other High frequency circuits in general.

6.FEATURES

- (1)Monlithic construction yields high reliability.
- (2)High self-resonant frequency.
- (3)Excellent solderability and heat resistance for either flow or reflow soldering.

CUSTOMER		MODEL NO.	MACM1211-102		A/0
FILE NO.		PART NO.			2021/9/24

7.可靠性Reliability


项目Item	规格与需求 Specification and Requirement	测试方法Test Method
可焊性 Solderability test	沾锡面积不得小于95%上锡面 Terminals area must have 95% min solder coverage	上锡升温曲线Solder heat proof: (1) 预热: 160±10℃持续90s Preheating: 160±10℃ for 90 seconds (2) 恒温时段: 245±5℃持续2±0.5s Retention time: 245±5℃ for 2±0.5 seconds
振动测试 Vibration test	感值变化: 不超过±5% 且无破裂等机械损伤产生 Inductance change: Within±5% Without mechanical damage such as break	(1) 振动频率(10Hz 55Hz 10Hz)60s为一个周期 Vibration frequency: (10Hz to 55Hz to 10Hz) in 60 seconds as a period (2) 振动时间 Vibration time: 三维正交坐标系每个方向振动(周期)循环2小时 Period cycled for 2 hours in each of 3 mutual perpendicular directions (3) 振幅 Amplitude: 1.5 mm Max
冲击测试 Shock test	感值变化: 不超过±5% 且无破裂等机械损伤产生 Inductance change: Within±5% Without mechanical damage such as break	(1) 最大振幅 Peak value: 100G (2) 脉冲波长 Duration of pulse: 11ms (3) 三维正交坐标系每个方向正负方向冲击3次 Times in each positive and negative direction of 3 mutual perpendicular directions
冷热冲击 Thermal shock	感值变化: 不超过±5% 且无破裂等机械损伤产生 Inductance change: Within±5% Without mechanical damage such as break	(1)重复以上100个循环Repeat 100 cycle as follow (-55±2℃,30±3分钟) 室温5分钟 (-55±2℃,30±3 minutes) Room temperature,5 minutes (+125±2℃,30±3分钟) 室温5分钟 (+125±2℃,30±3 minutes) Room temperature,5 minutes (2)恢复: 测试于标准条件下恢复48+4/-0小时(参考注释1) Recovery:48+4/-0 hours of recovery under the standard condition after the test. (see Note1)
耐高温测试 High temperature life test	感值变化: 不超过±5% 且无破裂等机械损伤产生 Inductance change: Within±5% Without mechanical damage such as break	(1)环境条件: 85±2℃ Environment condition : 85±2℃ 应用电流: 额定电流 Applied current: Rated current (2)持续时间: 1000+4/-0 小时(参考注释1) Duration:1000+4/-0 hours (see Note1)
耐湿测试 Humidity Resistance	感值变化: 不超过±5% 且无破裂等机械损伤产生 Inductance change: Within±5% Without mechanical damage such as break	(1)环境条件: 60±2℃ Environment condition : 60±2℃ 湿度: 90~95% Humidity:90~95% 应用电流: 额定电流 Applied current: Rated current (2)持续时间: 1000+4/-0 小时(参考注释1) Duration:1000+4/-0 hours (see Note1)
低温存放测试 Low temperature life test	感值变化: 不超过±5% 且无破裂等机械损伤产生 Inductance change: Within±5% Without mechanical damage such as break	(1)存储温度 Store temperature -55±2℃下存放 1000+4/-0 小时 -55±2℃for total 1000+4/-0 hours
高温存放测试 High temperature life test	感值变化: 不超过±5% 且无破裂等机械损伤产生 Inductance change: Within±5% Without mechanical damage such as break	(1)存储温度 Store temperature +125±2℃下存放 1000+4/-0 小时 +125±2℃for total 1000+4/-0 hours

CUSTOMER		MODEL NO.	MACM1211-102		A/0
FILE NO.		PART NO.			2021/9/24

8、包装 Packaging


8.1、尺寸 Dimensions

8.1.1 包装料带尺寸 Tape packaging dimensions




W	A0	B0	K0	P	P2	F	E	D0	P0	T
12.00 ±0.20	3.45 ±0.10	4.90 ±0.10	3.05 ±0.10	8.00 ±0.10	2.00 ±0.10	5.50 ±0.05	1.75 ±0.10	1.50 +0.1/-0	4.00 ±0.05	0.35 ±0.05

8.1.2 卷轴尺寸 Reel dimensions



项目 7"x8	尺寸(mm)	项目 7"x12	尺寸(mm)
A	9.0±0.5	A	13.5±0.5
B	60.0±2.0	B	60.0±2.0
C	13.5±0.5	C	13.5±0.5
D	178.0±2.0	D	178.0±2.0

8.1.3 外箱尺寸 Carton dimensions




项目	数量 (K)
1卷轴	0.5
1内箱	
1外箱	

CUSTOMER		MODEL NO.	MACM1211-102		A/0
FILE NO.		PART NO.			2021/9/24

Reflow curve

※ Reflow Profile

Power Choke Coil Type



1. Reflow Soldering Method

Reflow Soldering	Tp:255~260°C	Max.30 seconds (tp)
	217°C	60~150 seconds
Pre-Heat	150 ~ 200°C	60~120 seconds
Time 25°C to peak temperature	8 minutes max.	

2. Soldering iron method : 350±5°C Max.3 seconds.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Common Mode Chokes / Filters](#) category:

Click to view products by [COILMX](#) manufacturer:

Other Similar products are found below :

[PE-64683](#) [RD5122-6-9M6](#) [RD6137-6-7M5](#) [RD8147-16-3M0](#) [ST6118T-R](#) [FE3X025-10-7NL](#) [RD7147-25-0M7](#) [TCM0806G-350-2P-T](#)
[TCM0806G-650-2P-T](#) [IND-0110](#) [UAL21VR0802000](#) [UALSC023000000](#) [UALSC1020JH000](#) [UALSU10VD20010](#) [UALSU9VD070100](#) [36-00037](#) [UALW21HS072450](#) [UALSU9H0208000](#) [UAL24VK06450CH](#) [PLT10HH501100PNB](#) [PLT10HH401100PNB](#) [PLT10HH1026R0PNB](#)
[36-00029-01](#) [PE-67531](#) [TLH10UB](#) [113 0R5](#) [2752045447](#) [7351V](#) [CMF16-153131](#) [RD7147-6-6M0](#) [T8116NLT](#) [FE2X10-4-2NL](#) [36-00029-07](#)
[T8003NLT](#) [CTX01-13663](#) [CTX66-19521-R](#) [RC212-0.5-10M](#) [RC112-0.4-15M](#) [RC212-0.6-6M8](#) [RC212-0.4-15M](#) [RC112-0.3-30M](#)
[WTCF2012Z0M751PB](#) [PH9408.814NLT](#) [PAC6006.364NLT](#) [PAC6006.444NLT](#) [PAC6006.204NLT](#) [PH9407.204NLT](#) [PAC6006.264NLT](#)
[PH9408.105NLT](#) [PH9408.494NLT](#) [PAC6006.104NLT](#)