



SPECIFICATION FOR APPROVAL
产品规格承认书
CHIP COMMON MODE INDUCTOR
贴片共模电感

CUSTOMER.

MODEL NO.

MACM1211-701

CUSTOMER'S PART NO.

LILE NO.

DATE.

2019.12.03

REVISION.

A/0

NUMBER.

CUSTOMER APPROVE		
DATE:		
DRAWING		
DRAWN BY	CHECK BY	APPROVAL BY
林思思	陈健波	曾伟
DATE: 2019.12.03		



深圳市迈翔科技有限公司
惠州市迈翔电子有限公司

黄冈市迈翔电子有限公司 英德市迈翔电子有限公司
5-6F, Building B, Jinhao Smart Park, No. 207 Sihuan South Road, Zhongkai High tech
Zone, Huizhou City, Guangdong Province, China
TEL: +86 0752-3398115 3398116 3398117
Http: //www.coilcrafts.com www.coilmx.com E-mail: pxr@coilmx.com

CUSTOMER		MODEL NO.	MACM1211-701	REVISION	A/0
FILE NO.		PART NO.		DATE	2019.12.03

1.PRODUCT DIMENSION		UNIT:mm	
	A	12.0±0.5	
	A1	12.5±0.5	
	B	10.8±0.5	
	C	6.4Max	
	D	7.0Typ	
	E	2.7±0.2	
	F	2.5±0.2	


2.ELECTRICAL REQUIREMENTS							
Part Number	Impedance(Ω) @100MHZ /0.1V		DC Resistance (mΩ) Max	Rated current (A) Max	Rated Voltage (V) Max	Insulation Resistance (MΩ)Min	Marking
	MIN	TYP					
MACM1211-701	500	700	6	8	125	10	701

3.MATERIAL LIST			
NO.	ITEM	DESCRIPTION	SUPPLIER
1	CORE	FERRITE	SINCORES OR EQ
2	WIRE	2UEW P180	ELEKTRISOLA OR EQ
3	BASE	LCP	LIANGCHENG OR EQ
4	SOLDER	Sn Cu	SHENMAO OR EQ
5	INK	白色	BON MARK

4.CHARACTERISTICS
(1). All test data is based on 25°C ambient.
(2). DC current(A)that will cause an approximate ΔT40°C
(3). Operating temperature range: -40°C~+125°C
(4).Storage condition: Temperature 5 to 40°C, RH≤70%
(5).The part temperature (ambient + temp rise)should not exceed 125°C under worst case operating conditions. circuit design, component.PWB trace size and thickness,airflow and other cooling provision all affect the part temperature. Part temperature should be verified in the den application

CUSTOMER		MODEL NO.	MACM1211-701	REVISION	A/0
FILE NO.		PART NO.		DATE	2019.12.03

5.CIRCUIT DIAGRAM





6.APPLIATION

- (1)EMI/RFI chokes.
- (2)SCR and triac controls.
- (3)Power amplifiers.


7.FEATURES

- (1)Cost effective design.
- (2)ultra high current rating.

8、PACKAGING



Tape width	Distance	Pull-of force
24mm	16mm	10-120g



轮盘：24（直径330mm）数量：500PCS/盘

PE袋
数量：500PCS/袋

内盒
数量：1000PCS/盒

外箱，数量;5000PCS/箱
不足整箱用内盒或填充物装满

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Common Mode Chokes / Filters](#) category:

Click to view products by [COILMX](#) manufacturer:

Other Similar products are found below :

[PE-64683](#) [RD5122-6-9M6](#) [RD6137-6-7M5](#) [RD8147-16-3M0](#) [ST6118T-R](#) [FE3X025-10-7NL](#) [RD7147-25-0M7](#) [TCM0806G-350-2P-T](#)
[TCM0806G-650-2P-T](#) [IND-0110](#) [UAL21VR0802000](#) [UALSC023000000](#) [UALSC1020JH000](#) [UALSU10VD20010](#) [UALSU9VD070100](#) [36-00037](#) [UALW21HS072450](#) [UALSU9H0208000](#) [UAL24VK06450CH](#) [PLT10HH501100PNB](#) [PLT10HH401100PNB](#) [PLT10HH1026R0PNB](#)
[36-00029-01](#) [PE-67531](#) [TLH10UB](#) [113 0R5](#) [2752045447](#) [7351V](#) [CMF16-153131](#) [RD7147-6-6M0](#) [T8116NLT](#) [FE2X10-4-2NL](#) [36-00029-07](#)
[T8003NLT](#) [CTX01-13663](#) [CTX66-19521-R](#) [RC212-0.5-10M](#) [RC112-0.4-15M](#) [RC212-0.6-6M8](#) [RC212-0.4-15M](#) [RC112-0.3-30M](#)
[WTCF2012Z0M751PB](#) [PH9408.814NLT](#) [PAC6006.364NLT](#) [PAC6006.444NLT](#) [PAC6006.204NLT](#) [PH9407.204NLT](#) [PAC6006.264NLT](#)
[PH9408.105NLT](#) [PH9408.494NLT](#) [PAC6006.104NLT](#)