



SPECIFICATION FOR APPROVAL

产品规格承认书

SMD POWER INDUCTOR

贴片共模电感

CUSTOMER.

MODEL NO.

MACM9070系列

CUSTOMER'S PART NO.

LILE NO.

DATE.

2020.03.07

REVISION.

A/0

CUSTOMER APPROVE

DATE:

DRAWING

DRAWN BY

CHECK BY

APPROVAL BY

DATE:



sira
CERTIFICATION



IATF16949 / ISO9001 / ISO14000

深圳市迈翔科技有限公司

SHENZHEN MOTTO TECHNOLOGY Co., Ltd

香港瑞德科技有限公司 黄冈市迈翔电子有限公司

Motto Technology park, niu e ling village no#214 xintian, nghua Town,

Guanlan Street, Longhua District, Shenzhen

TEL: +86 0755-8948751~2 89487610 Fax: +86 0755-61624574

[Http://www.coilmx.com](http://www.coilmx.com) E-mail: sales@mottotech.com

| | | | | | |
|----------|--|-----------|------------|----------|------------|
| CUSTOMER | | MODEL NO. | MACM9070系列 | REVISION | A/0 |
| FILE NO. | | PART NO. | | DATE | 2020.03.07 |

| 1.PRODUCT DIMENSION | | UNIT:mm | |
|---------------------|----|---------|--|
| | A | 9.0±0.5 | |
| | A1 | 9.5±0.5 | |
| | B | 7.0±0.5 | |
| | C | 4.8Max | |
| | D | 5.6Typ | |
| | E | 1.5Typ | |
| | F | 1.7Typ | |
| | | | |
| | | | |
| | | | |

| 2.ELECTRICAL REQUIREMENTS | | | | | | | |
|---------------------------|---------------|------|-------------|----------------------|------------|---------------------|---------|
| Product NO | Z(Ω)100MHZ/1V | | DCR (mΩ)Max | Rated Current(A) Max | IR (MΩ)Min | Rated Voltag(V) Max | MARKING |
| | MIN | TYP | | | | | |
| MACM9070-301 | 225 | 300 | 6 | 6 | 10 | 80 | 301 |
| MACM9070-501 | 450 | 600 | 8 | 5.5 | 10 | 80 | 501 |
| MACM9070-701 | 500 | 700 | 10 | 5 | 10 | 80 | 701 |
| MACM9070-102 | 750 | 1000 | 13 | 4 | 10 | 80 | 102 |
| MACM9070-222 | 1700 | 2200 | 50 | 3 | 10 | 80 | 222 |
| MACM9070-272 | 2000 | 2700 | 80 | 2 | 10 | 80 | 272 |

3.CHARACTERISTICS

- All test data is based on 25°C ambient.
- DC current(A)that will cause an approximate $\Delta T40^{\circ}\text{C}$
- DC current(A)that will cause L0 to drop approximately 10%Typ
- Operating temperature range: -55°C~+125°C
- The part temperature (ambient + temp rise)should not exceed 125°C under worst case operating conditions. circuit design, component.PWB trace size and thickness,airflow and other cooling provision all affect the part temperature. Part temperature should be verified in the den application

4.SPECIAL REQUEST

- Lettering on top of the body.

| | | | | | |
|----------|--|-----------|------------|----------|------------|
| CUSTOMER | | MODEL NO. | MACM9070系列 | REVISION | A/0 |
| FILE NO. | | PART NO. | | DATE | 2020.03.07 |

5.PRODUCT IDENTIFICATION


XX XXXX - XXX X X

① ② ③ ④ ⑤

①、 Product Symbol ②、 Dimensions ③、 Inductance

④、 Tolerance: M±20%, N±30%. ⑤、 Material

6.ELECTRICAL SCHEMATICS




7.APPLICATION

- (1)Low profile,high current power supplies.
- (2)Battery powered devices.
- (3)DC/DC converters in distributed power systems.
- (5)DC/DC converters for field programmable gate array.

8.FEATURES

- (1)ROHS compliant.
- (2)Super low resistance,ultra high current rating.
- (3)high performance(I sat)realized by metal dust core.
- (4)Frequency Range:up to 1MHZ.

9.RECOMMENDED PCB LAYOUT



| | |
|---|---------|
| G | 5.5Typ |
| H | 1.5Typ |
| I | 10.5Typ |
| J | 5.0Typ |
| | |
| | |
| | |


| CUSTOMER | | MODEL NO. | MACM9070系列 | REVISION | A/0 |
|-------------------------------------|---|---|------------|----------|------------|
| FILE NO. | | PART NO. | | DATE | 2020.03.07 |
| 项目Item | 规格与需求 Specification and Requirement | 测试方法Test Method | | | |
| 可焊性 Solderability test | 沾锡面积不得小于95%上锡面 Terminals area must have 95% min solder coverage | 上锡升温曲线Solder heat proof: (1) 预热: 160±10℃持续90s Preheating: 160±10℃ for 90 seconds (2) 恒温时段: 245±5℃持续2±0.5s Retention time: 245±5℃ for 2±0.5 seconds | | | |
| 振动测试 Vibration test | 感值变化: 不超过±5% 且无破裂等机械损伤产生 Inductance change: Within±5% Without mechanical damage such as break | (1) 振动频率(10Hz 55Hz 10Hz)60s为一个周期 Vibration frequency: (10Hz to 55Hz to 10Hz) in 60 seconds as a period (2) 振动时间 Vibration time: 三维正交坐标系每个方向振动(周期)循环2小时 Period cycled for 2 hours in each of 3 mutual perpendicular directions (3) 振幅 Amplitude: 1.5 mm Max | | | |
| 冲击测试 Shock test | 感值变化: 不超过±5% 且无破裂等机械损伤产生 Inductance change: Within±5% Without mechanical damage such as break | (1) 最大振幅 Peak value: 100G (2) 脉冲波长 Duration of pulse: 11ms (3) 三维正交坐标系每个方向正负方向冲击3次 Times in each positive and negative direction of 3 mutual perpendicular directions | | | |
| 冷热冲击 Thermal shock | 感值变化: 不超过±5% 且无破裂等机械损伤产生 Inductance change: Within±5% Without mechanical damage such as break | (1)重复以上100个循环Repeat 100 cycle as follow (-55±2℃,30±3分钟) 室温5分钟 (-55±2℃,30±3 minutes) Room temperature,5 minutes (+125±2℃,30±3分钟) 室温5分钟 (+125±2℃,30±3 minutes) Room temperature,5 minutes (2)恢复: 测试于标准条件下恢复48+4/-0小时(参考注释1) Recovery:48+4/-0 hours of recovery under the standard condition after the test. (see Note1) | | | |
| 耐高温测试 High temperature life test | 感值变化: 不超过±5% 且无破裂等机械损伤产生 Inductance change: Within±5% Without mechanical damage such as break | (1)环境条件: 85±2℃ Environment condition : 85±2℃ 应用电流: 额定电流 Applied current: Rated current (2)持续时间: 1000+4/-0 小时(参考注释1) Duration:1000+4/-0 hours (see Note1) | | | |
| 耐湿测试 Humidity Resistance | 感值变化: 不超过±5% 且无破裂等机械损伤产生 Inductance change: Within±5% Without mechanical damage such as break | (1)环境条件: 60±2℃ Environment condition : 60±2℃ 湿度: 90~95% Humidity:90~95% 应用电流: 额定电流 Applied current: Rated current (2)持续时间: 1000+4/-0 小时(参考注释1) Duration:1000+4/-0 hours (see Note1) | | | |
| 低温存放测试Low temperature life test | 感值变化: 不超过±5% 且无破裂等机械损伤产生 Inductance change: Within±5% Without mechanical damage such as break | (1)存储温度 Store temperature -55±2℃下存放 1000+4/-0 小时 -55±2℃ for total 1000+4/-0 hours | | | |
| 高温存放测试High temperature life test | 感值变化: 不超过±5% 且无破裂等机械损伤产生 Inductance change: Within±5% Without mechanical damage such as break | (1)存储温度 Store temperature +125±2℃下存放 1000+4/-0 小时 +125±2℃ for total 1000+4/-0 hours | | | |

| | | | | | |
|-----------------|--|------------------|-------------------|-----------------|-------------------|
| CUSTOMER | | MODEL NO. | MACM9070系列 | REVISION | A/0 |
| FILE NO. | | PART NO. | | DATE | 2020.03.07 |


11、包装 Packaging

11.1、尺寸 Dimensions

11.1.1 包装料带尺寸 Tape packaging dimensions




11.1.2 卷轴尺寸 Reel dimensions



| 项目 | 尺寸(mm) |
|----------|-------------|
| A | 330 |
| B | 100 |
| C | 13 |
| D | 16.5 |
| | |
| | |

11.1.3 外箱尺寸 Carton dimensions




| 项目 | 数量 (PCS) |
|------------|-------------|
| 1卷轴 | 700 |
| 1内箱 | 1400 |
| 1外箱 | 7000 |

| | | | | | |
|----------|--|-----------|------------|----------|------------|
| CUSTOMER | | MODEL NO. | MACM9070系列 | REVISION | A/0 |
| FILE NO. | | PART NO. | | DATE | 2020.03.07 |

Reflow curve

※ Reflow Profile

Power Choke Coil Type



1. Reflow Soldering Method

| | | |
|-------------------------------|----------------|-----------------------|
| Reflow Soldering | Tp:255~260°C | Max.30 seconds (tp) |
| | 217°C | 60~150 seconds |
| Pre-Heat | 150 ~ 200°C | 60~120 seconds |
| Time 25°C to peak temperature | 8 minutes max. | |

2. Soldering iron method : 350±5°C Max.3 seconds.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Common Mode Chokes / Filters](#) category:

Click to view products by [COILMX](#) manufacturer:

Other Similar products are found below :

[74279408](#) [PE-62911NL](#) [PE-64683](#) [RD5122-6-9M6](#) [RGCMF1210900H3T](#) [ST6118T-R](#) [FE3X025-10-7NL](#) [T8114NLT](#) [RD5122-10-6M0](#)
[TCM0806G-350-2P-T](#) [TCM0806G-650-2P-T](#) [IND-0110](#) [UAL21VR0802000](#) [UALSC023000000](#) [UALSC1020JH000](#) [UALSC1520JH000](#)
[UALSU10VR15019](#) [UALSU9VD070100](#) [36-00037](#) [5701610000](#) [UALW21HS200290](#) [UALW21HS072450](#) [UALSU9HF050500](#)
[UALSU9H0208000](#) [UAL24VK06450CH](#) [PLT10HH501100PNB](#) [PLT10HH401100PNB](#) [PLT10HH1026R0PNB](#) [PE-67531](#) [TLH10UB 113](#)
[OR5](#) [2752045447](#) [CMS3-11-R](#) [7351V](#) [7408-RC](#) [CMF16-153131](#) [744252510](#) [T8116NLT](#) [CMS2-10-R](#) [DLW44SN101SK2L](#) [FE2X10-4-2NL](#)
[744253200](#) [744253101](#) [744252220](#) [TX8111NLT](#) [UAL30VR3500470](#) [CTX01-19077-R](#) [T8003NLT](#) [CTX01-13663](#) [CTX66-19521-R](#)
[7446630047](#)