

A1N4007G-G

Voltage: 1000 V

Current: 1.0 A

RoHS Device




Features

- Low drop down voltage
- High current capability
- Low reverse leakage.
- High forward surge current capability.
- Glass passivated chip junction.
- Comply with AEC-Q101

Mechanical data

- Case: JEDEC DO-41 molded plastic
- Epoxy: UL 94V-0 rate flame retardant
- Terminals: Solderable per MIL-STD-750 method 2026.
- Polarity: Color band denotes cathode end
- Mounting position: Any
- Weight: 0.34 grams(approx.)



Circuit diagram



Maximum Ratings and Electrical Characteristics (at Ta=25°C unless otherwise noted)

Ratings at 25°C ambient temperature unless otherwise specified.
Single phase, half wave, 60Hz, resistive or inductive load.
For capacitive load derate current by 20%.

Parameter	Conditions	Symbol	Value	Unit
Maximum recurrent peak reverse voltage		V_{RRM}	1000	V
Maximum RMS voltage		V_{RMS}	700	V
Maximum DC blocking voltage		V_{DC}	1000	V
Maximum average forward rectified current	see figure 1	$I_{(AV)}$	1	A
Peak forward surge current	8.3ms single half sine-wave superimposed on rated load (JEDEC Method) TL=110°C	I_{FSM}	30	A
Maximum instantaneous forward voltage	@ $I_F = 1A$	V_F	1.1	V
Maximum DC reverse current at rated DC blocking voltage	$T_A = 25^\circ C$	I_R	5	μA
	$T_A = 125^\circ C$		50	
Typical junction Capacitance	$V_R = 4V, f = 1MHz$	C_J	10	pF
Typical thermal resistance	Junction to ambient	$R_{\theta JA}$	45	°C/W
Operating junction temperature range		T_J	-55 ~ +125	°C
Storage temperature range		T_{STG}	-55 ~ +150	°C

Rating and Characteristic Curves (A1N4007G-G)

Fig.1 - Forward Current Derating Curve




Fig.2 - Maximum Non-Repetitive Peak Forward Surge Current




Fig.3 - Typical Instantaneous Forward Characteristics




Fig.4 - Typical Reverse Characteristics






Fig.5 - Typical Junction Capacitance



Taping Specification For Axial Lead Diodes



DO-41	SYMBOL	A	B	Z	T	L1	L2
	(mm)	5.00 ± 0.50	52.00 ± 0.50	1.20 (max)	6.00 ± 0.40	1.00 (max)	1.00 (max)
	(inch)	0.197 ± 0.020	2.047 ± 0.020	0.047 (max)	0.236 ± 0.016	0.039 (max)	0.039 (max)

DO-41	SYMBOL	L	W	H			
	(mm)	260.00 ± 10.00	75.00 ± 10.00	140.00 ± 10.00			
	(inch)	10.236 ± 0.394	2.953 ± 0.394	5.512 ± 0.394			

Marking Code

Part Number	Marking Code
A1N4007G-G	1N4007G



1N4007G = Product type marking code

Standard Packaging

Case Type	AMMO PACK	
	BOX (pcs)	CARTON (pcs)
DO-41	5,000	50,000

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Rectifiers](#) category:

Click to view products by [Comchip](#) manufacturer:

Other Similar products are found below :

[70HFR40](#) [RL252-TP](#) [150KR30A](#) [1N5397](#) [NTE5841](#) [NTE6038](#) [SCF5000](#) [1N4002G](#) [1N4005-TR](#) [JANS1N6640US](#) [481235F](#)

[RRE02VS6SGTR](#) [067907F](#) [MS306](#) [70HF40](#) [T110HF60](#) [T85HFL60S02](#) [US2JFL-TP](#) [A1N5404G-G](#) [CRS04\(T5L,TEMQ\)](#) [ACGRA4007-HF](#)

[ACGRB207-HF](#) [CLH03\(TE16L,Q\)](#) [ACGRC307-HF](#) [ACEFC304-HF](#) [NTE6356](#) [NTE6359](#) [NTE6002](#) [NTE6023](#) [NTE6039](#) [NTE6077](#)

[85HFR60](#) [40HFR60](#) [1N1186RA](#) [70HF120](#) [85HFR80](#) [D126A45C](#) [SCF7500](#) [D251N08B](#) [SCHJ22.5K](#) [SM100](#) [SCPA2](#) [SCH10000](#) [SDHD5K](#)

[VS-12FL100S10](#) [ACGRA4001-HF](#) [D1821SH45T PR](#) [D1251S45T](#) [NTE5990](#) [NTE6358](#)