

## SS14-HF Thru. SS120-HF

**Reverse Voltage: 40 to 200 Volts**

**Forward Current: 1.0 Amp**

**RoHS Device**

**Halogen Free**




### Features

- Metal silicon junction, majority carrier conduction
- For surface mounted applications
- Low power loss, high efficiency
- High forward surge current capability
- For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications

### Mechanical data

- Case: SMA
- Terminals: Solderable per MIL-STD-750, Method 2026
- Approx. Weight: 70mg / 0.0025oz



### Maximum Ratings and Electrical Characteristics

Ratings at 25 °C ambient temperature unless otherwise specified.

Single phase, half wave, 60Hz resistive or inductive load, for capacitive load, derate by 20 %

Parameter	Symbols	SS14	SS16	SS110	SS115	SS120	Units
Maximum repetitive peak reverse voltage	V <sub>RRM</sub>	40	60	100	150	200	V
Maximum RMS voltage	V <sub>RMS</sub>	28	42	70	105	140	V
Maximum DC blocking voltage	V <sub>DC</sub>	40	60	100	150	200	V
Maximum average forward rectified current	I <sub>F(AV)</sub>			1.0			A
Peak forward surge current, 8.3ms single half sine-wave superimposed on rated load (JEDEC method)	I <sub>FSM</sub>			25			A
Max instantaneous forward voltage at 1 A	V <sub>F</sub>	0.55	0.70	0.85	0.90		V
Maximum DC reverse current T <sub>j</sub> = 25°C at rated DC reverse voltage T <sub>j</sub> = 100°C	I <sub>R</sub>	0.3 10		0.2 5	0.1 2		mA
Typical junction capacitance (Note 1)	C <sub>j</sub>	110		80			pF
Typical thermal resistance (Note 2)	R <sub>θJA</sub>			90			°C/W
Operating junction temperature range	T <sub>j</sub>			-55 ~ +125			°C
Storage temperature range	T <sub>stg</sub>			-55 ~ +150			°C

Notes: 1. Measured at 1 MHz and applied reverse voltage of 4 V D.C

2. P.C.B. mounted with 2.0" X 2.0" (5 X 5 cm) copper pad areas.

# SMD Schottky Barrier Rectifiers

**Comchip**  
SMD Diode Specialist

## Rating and Characteristic Curves (SS14-HF Thru. SS120-HF)

Fig.1 - Forward Current Derating Curve




Fig.2 - Typical Reverse Characteristics




Fig.3 - Typical Forward Characteristic




Fig.4 - Typical Junction Capacitance




Fig.5 - Maximum Non-Repetitive Peak Forward Surge Current






Fig.6 - Typical Transient Thermal Impedance



# SMD Schottky Barrier Rectifiers

**Comchip**  
SMD Diode Specialist

## Reel Taping Specification



DO-214AC (SMA)	SYMBOL	A	B	C	d	D	D1	D2
	(mm)	$2.70 \pm 0.10$	$5.30 \pm 0.10$	$2.66 \pm 0.10$	$1.50 \pm 0.10$	$330 \pm 2.00$	50.0 MIN.	$13.50 \pm 0.50$
	(inch)	$0.106 \pm 0.004$	$0.209 \pm 0.004$	$0.105 \pm 0.004$	$0.059 \pm 0.004$	$12.99 \pm 0.079$	1.969 MIN.	$0.531 \pm 0.020$


DO-214AC (SMA)	SYMBOL	E	F	P	P0	P1	T	W	W1
	(mm)	$1.75 \pm 0.10$	$5.50 \pm 0.10$	$4.00 \pm 0.10$	$4.00 \pm 0.10$	$2.00 \pm 0.10$	$0.60 \pm 0.10$	$12.0 \pm 0.30$	$18.4 \pm 1.00$
	(inch)	$0.069 \pm 0.004$	$0.217 \pm 0.004$	$0.157 \pm 0.004$	$0.157 \pm 0.004$	$0.079 \pm 0.004$	$0.024 \pm 0.004$	$0.472 \pm 0.012$	$0.724 \pm 0.040$

Company reserves the right to improve product design , functions and reliability without notice.

REV:B

## Marking Code


Part Number	Marking Code
SS14-HF	SS14
SS16-HF	SS16
SS110-HF	SS110
SS115-HF	SS115
SS120-HF	SS120



xxxxx = Product type marking code

## Suggested PAD Layout

SIZE	DO-214AC (SMA)	
	(mm)	(inch)
A	4.00	0.157
B	2.50	0.100
C	1.80	0.071
D	6.50	0.256
E	1.50	0.060



## Standard Packaging

Case Type	REEL PACK	
	REEL ( pcs )	Reel Size (inch)
DO-214AC (SMA)	5,000	13

# X-ON Electronics

Largest Supplier of Electrical and Electronic Components

***Click to view similar products for Schottky Diodes & Rectifiers category:***

***Click to view products by Comchip manufacturer:***

Other Similar products are found below :

[MA4E2039](#) [D1FH3-5063](#) [MBR10100CT-BP](#) [MBR1545CT](#) [MMBD301M3T5G](#) [RB160M-50TR](#) [RB551V-30](#) [BAS16E6433HTMA1](#) [BAT54-02LRH](#) [E6327](#) [NSR05F40QNXT5G](#) [NTE555](#) [JANS1N6640](#) [SB07-03C-TB-H](#) [SK310-T](#) [SK32A-LTP](#) [SK33A-TP](#) [SK34B-TP](#) [SS3003CH-TL-E](#) [GA01SHT18](#) [CRS10I30A\(TE85L,QM](#) [MA4E2501L-1290](#) [MBRA140TRPBF](#) [MBRB30H30CT-1G](#) [SB007-03C-TB-E](#) [SK32A-TP](#) [SK33B-TP](#) [SK35A-TP](#) [SK38B-TP](#) [NRVBM120LT1G](#) [NTE505](#) [NTSB30U100CT-1G](#) [SS15E-TP](#) [VS-6CWQ10FNHM3](#) [ACDBA1100LR-HF](#) [ACDBA1200-HF](#) [ACDBA140-HF](#) [ACDBA2100-HF](#) [ACDBA3100-HF](#) [CDBQC0530L-HF](#) [CDBQC0240LR-HF](#) [BAT6202VH6327XTSA1](#) [ACDBA340-HF](#) [ACDBA260LR-HF](#) [ACDBA1100-HF](#) [SK310B-TP](#) [MA4E2502L-1246](#) [MA4E2502H-1246](#) [NRVBM120ET1G](#) [NSR01L30MXT5G](#) [NTE573](#)