


POLARITY PROTECTION DEVICE
DETAIL "A" S=2

SPECIFICATION

- (1) ITEM NO. : BH-341-2A
- (2) WIRE: UL1007 AWG 26,
BLACK & RED: 150MM±5MM
STRIP & TIN: 5MM±1MM
- (3) HOLDER MATERIAL: PP RESIN, BLACK COLOR
- (4) SPRING MATERIAL: Ø0.7MM SPRING STEEL NICKEL PLATED
- (5) RIVET MATERIAL: BRASS NICKEL PLATED
- (6) RoHS COMPLIANT

③	Polarity protection device 2.3mm changed to 1.6mm	JUL/26/14
②	Added the polarity protection device	NOV/30 /2011
①	Add MODEL NO. : "BH-341-2"	JUL/24/08
NO.	MODIFICATION	DATE
General Tolerances		
0 ~ >3	± 0.10	30 ~ >120 ± 0.30
3 ~ >6	± 0.10	120 ~ >400 ± 0.50
6 ~ >30	± 0.20	Angle: ± 3°



COMF COMFORTABLE ELECTRONIC CO.LTD.			
NAME	BATTERY HOLDER: BH-341-2A		
SCALE	1:1	APPD	游原正
UNIT	MM	CHKD	黄永连
MAT'L	SEE SPEC.	DWN	RAOXIANHUI
DATE	AUG. 09. 2014	DR NO	3412A-0814

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Comf manufacturer](#):

Other Similar products are found below :

[201D](#) [BC-0301](#) [BC-0401](#) [BC-0403](#) [BH-111A](#) [BH-111D](#) [BH-121-1A](#) [BH-121-1B](#) [BH-1/2AA-2A](#) [BH-131A](#) [BH-211-1A](#) [BH-221A](#) [BH-232A](#) [BH-243B](#) [BH-3103B](#) [BH-311-1A](#) [BH-311-1D](#) [BH-311-1P](#) [BH-321-1A](#) [BH-321-1B](#) [BH-321-1D](#) [BH-321-1P](#) [BH-321-2A](#) [BH-321-2P](#) [BH-322-1A](#) [BH-325-1A](#) [BH-331-3D](#) [BH-331A-3A](#) [BH-331D](#) [BH-332A](#) [BH-333A](#) [BH-341-1A](#) [BH-341-1B](#) [BH-341-1D](#) [BH-341-1P](#) [BH-341-2A](#) [BH-342-1A](#) [BH-343-1A](#) [BH-343-2B](#) [BH-351A](#) [BH-362B](#) [BH363-1B](#) [BH-383A](#) [BH-383B](#) [BH-422A](#) [BH-425A](#) [BH-431-1A](#) [BH-431-1B](#) [BH-441P](#) [BH-443A](#)