
Comus Group of Companies

PRODUCT DATA SHEET







Drawings not to scale All dimensions in mm (inches)

SPECIFICATION

Magnet material	Alcomax/Alnico
Gauss reading at 6.5mm	1000
Maximum operating temperature	550°C

Alnico/Alcomax is a good general purpose material that can be machined or cast to the required shape before magnatizing. The material has the best temperate co-efficient of all permanent magnets. The high nickel content results in good corrosion and oxidisation resistance

MAGNET

PART NUMBER **PRM**

Rev. No.Revision NoteDateSignatureBWeb Site 20011-4-01RG

As part of the company policy of continued product improvement, specifications may change without notice. Our sales office will be pleased to help you with the latest information on this product range and details of our full design and manufacturing service. All products are supplied to our standard conditions of sale otherwise agreed in writing.

The Comus Group of Companies consist of:
Assemtech Europe Limited
E. Bachem GmbH
Comus International
W. Gunther GmbH
Gunther Belgium
Gunther France
S.I.G.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Racks & Rack Cabinet Accessories category:

Click to view products by Comus manufacturer:

Other Similar products are found below:

CR-1727 M00-PLN F2420 F2424 8310-1032-SS 9104 PLFF2000 PLFF6000 GP216 PTFA60000LG H-9163-B AC220-84-1 HEH050BA

1427C3 BAS-5104 N-700-2 190-002 HTL10 HTS10 PC-118 PC-780L PC-79 PC-800 SC4-28 F3024 AKWAMT PLFF1000 GRPB12PG

CG3-340S/12 2CWDP36 2CWDP48 2SSHINGE CP-001BK CPL19431LG1 R570-004-107 M6123-4007-SS TS170 531300535 BRX
12290 C4BD3077SBK1 UPS 7-17-14 PLAIN LP40 5261304-07 CCA26-44-01 706-102 CG3-160G 7112C-PLN ALUM CM10 TS81 7142