



**NOTES:**

**1. Electrical Specifications:**

- Meets USB 2.0 specifications
- Low level Contact Resistance: 30 mOhm max.
- Insulation Resistance 1000 MOhm min.
- Current Rating: 1.5 A max. @ 25°C
- DWV: 500 VAC/60s at sea level

Ⓒ Connector Operating Temperature: -40°C to +80°C

**2. Material and Finish:**

- Coupling Ring: Polyester (Black); Metallized ABS, UL94 V-0
- Ⓒ or Zinc Die-Cast, Powercron 590-534 (PPG), Black
- Plug Housing: Polyester (Black) or Metallized ABS, UL94 V-0,
- Interfacial Seal: Silicone, Color: White
- Cable Gland: PA (Black); UL94 V-0 or Brass, Nickel Plated
- Cable Gland Seal: NBR, Color: Black
- Cable Gland Insert (Metal Version): Nylon, Color: White
- USB Insulator: PBT, UL 94V-0, Color: White
- USB Overmold: PVC, UL94 V-0, Color: Black
- USB Metal Shell: SPCC. Nickel plated
- USB Contact: Copper Alloy, 30 u" min. Au over 40 u" min. Nickel Plated

**3. Shielded USB Cable Configuration**

**AWM 2725 AWG28/1p + AWG24/2c, OD: 4.5 mm Color: black**

Directive 2002/95/EC RoHS Compliant

Cable Length	Part Number		
	Plastic Version	Metallized Plastic Version	Powercron Finished Zinc Die-Cast Version
L			
0.25 ± 0.01 m	17-230071	17-230081	17-230141
1 ± 0.02 m	17-200221	17-230091	17-230151
1.5 ± 0.03 m	17-230471		
2 ± 0.03 m	17-200231	17-230101	17-230161
3 ± 0.04 m	17-200241	17-230111	17-230171
4 ± 0.05 m	17-200251	17-230121	17-230181
4.5 ± 0.05 m	17-200261	17-230131	17-230191

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY MANNER AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC CORPORATION  DO NOT ALTER CAD DRAWING BY HAND	Customer:			Tolerance Unless otherwise specified			Scale:	Dim. in m	
	Name		Title	Approval Date	0 PLC ±0.30 1 PLC ±0.20 2 PLC ±0.10 3 PLC ±0.05 ANGLES ±1°		Autodesk Inventor	Material: See Notes	
	f	1 x f	Aug/15/2017	Vincent Ke	Draw.	Sept. 23	Vincent Ke	Title: USB Patch Cord USB 2.0 Type A Plug (Industrial) to USB 2.0 Type A Plug (Standard)	
	e	2 x e	Mar/27/2013	Vincent Ke	Appd.	Sept. 23	J. chaudry		
d	2 x d	Oct/24/2012	Vincent Ke	Norm			Drawing No.: 17K1A106 Part No.: SEE P/N ABOVE		
c	1 x c	Sep/13/2012	Vincent ke	D-old					
b	1 x b	Jan/19/2009	Vincent ke				DIN A3 Sheet 1/1		
a	original								
Rev.	Changes	Date	Name	<b>CONEC</b>					

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [USB Cables / IEEE 1394 Cables](#) category:*

*Click to view products by [CONEC](#) manufacturer:*

Other Similar products are found below :

[68768-0173](#) [FNY-W6003-01](#) [88764-0800](#) [148700-1](#) [17-200621](#) [17-250051P](#) [954](#) [17-200261](#) [AC102012-1](#) [AC102012-2](#) [FTP-629Y601](#) [45-1345-15](#) [45-1358-15](#) [45-1363-15](#) [IP-USB1\(C10\)S-RW](#) [CABLE/RTP/USB/DT](#) [45-1351-15](#) [45-1357-15](#) [45-1433-1](#) [687680278](#)  
[USBFTVX2SA2N03A](#) [USBFTV2SA2N03A](#) [USBFTV2SA2N05A](#) [MDM9PH004B](#) [MDM9PH004P](#) [FTP-629Y401](#) [FTP-628Y302](#) [FTP-628Y402](#) [CSMNB9MF-5](#) [FNY-W6022](#) [UA-30AMF-SD7B03](#) [UA-30AMFM-SL7B03](#) [USBAPSCC7202A](#) [17-200641](#) [UES-1001A160](#) [UES-1003A160](#) [USBFTVX7SA2N20A](#) [FTP-629Y602](#) [USBCAMCM100](#) [USB A/F\\*2 to 2.54 2\\*5P-SH L=400mm](#) [68784-0075](#) [MINI-SCREW-USB-DATACABLE](#) [19800-010500-200-RS](#) [103-1092-BL-F0050](#) [103-1020-BL-00100](#) [103-1092-BL-F0200](#) [103-1092-BL-F0100](#) [105-1092-BL-00300](#) [105-1092-BL-00200](#) [105-1031-BL-00200](#)