



USB 2.0 Type A Plug  
Industrial IP67,  
Plastic Version  
Bayonet Locking Type

USB 2.0 Type A Plug  
Industrial IP67,  
Plastic Version  
Bayonet Locking Type

**NOTES:**

**1. Electrical Specifications:**

- Meets USB 2.0 specifications
- Low level Contact Resistance: 30 mOhm max.
- Insulation Resistance 1000 MOhm min.
- Current Rating: 1.5 A max. @ 25°C
- DWV: 500 VAC/60s at sea level
- Operating Temperature: -40°C to +80°C

**2. Material and Finish:**

- Coupling Ring: Polyester (Black); UL94 V-0
- Plug Housing: Polyester (Black); UL94 V-0
- Interfacial Seal: Silicone, Color: White
- Cable Gland: PA (Black); UL94 V-0
- Cable Gland Seal: NBR, Color: Black
- USB Insulator: PBT, UL 94V-0, Color: White
- USB Metal Shell: SPCC. Nickel plated
- USB Contact: Copper Alloy, 30 u" min. Au over 40 u" min. Nickel Plated

**3. Shielded USB Cable Configuration**

AWM 2725 AWG28/1p + AWG24/2c, OD: 4.5 mm Color: black Directive 2002/95/EC RoHS Compliant

ⓑ	Cable Length L	Part Number
Ⓒ	0.46 m +/- 0.01m	17-230361
Ⓓ	1 m +/- 0.03m	17-200271
	2 m +/- 0.05m	17-200281
	3 m +/- 0.05m	17-200291
	4 m +/-0.08m	17-200301
	4.5 m +/-0.08m	17-200311

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY MANNER AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC CORPORATION  DOT NOT ALTER CAD DRAWING BY HAND	Customer:			Tolerance Unless otherwise specified			Scale: 1.7:1	Dim. in
	Name	Title	Approval Date	0 PLC ±0.30	1 PLC ±0.20		Autodesk Inventor Title: <b>USB Patch Cord</b> USB 2.0 Type A Plug (Industrial) to USB 2.0 Type A Plug (Industrial)	Material: See Notes
				2 PLC ±0.10	3 PLC ±0.05			
				ANGLES ±1°				
	d	1 x d	Feb/26/2014	Vincent Ke	2008	Date	Name	Drawing No.: 17K1A107
c	1 x c	May/08/2013	Vincent Ke		Draw.	Sept. 23	Vincent Ke	DIN A3
b	1 x b	Jan/19/2009	Vincent ke		Appd.	Sept. 23	J. chaudry	Sheet 1/1
a	original							
Rev.	Changes	Date	Name			Part No.: SEE P/N ABOVE		

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [USB Cables / IEEE 1394 Cables category](#):*

*Click to view products by [CONEC manufacturer](#):*

Other Similar products are found below :

[68768-0173](#) [FNY-W6003-01](#) [88764-0800](#) [148700-1](#) [17-200621](#) [17-250051P](#) [954](#) [17-200261](#) [AC102012-1](#) [AC102012-2](#) [FTP-629Y601](#) [45-1345-15](#) [45-1358-15](#) [45-1363-15](#) [IP-USB1\(C10\)S-RW](#) [CABLE/RTP/USB/DT](#) [45-1351-15](#) [45-1357-15](#) [45-1433-1](#) [687680278](#)  
[USBFTVX2SA2N03A](#) [USBFTV2SA2N03A](#) [USBFTV2SA2N05A](#) [MDM9PH004B](#) [MDM9PH004P](#) [FTP-629Y401](#) [FTP-628Y302](#) [FTP-628Y402](#) [CSMNB9MF-5](#) [FNY-W6022](#) [UA-30AMF-SD7B03](#) [UA-30AMFM-SL7B03](#) [USBAPSCC7202A](#) [17-200641](#) [UES-1001A160](#) [UES-1003A160](#) [USBFTVX7SA2N20A](#) [FTP-629Y602](#) [USBCAMCM100](#) [USB A/F\\*2 to 2.54 2\\*5P-SH L=400mm](#) [68784-0075](#) [MINI-SCREW-USB-DATACABLE](#) [19800-010500-200-RS](#) [103-1092-BL-F0050](#) [103-1020-BL-00100](#) [103-1092-BL-F0200](#) [103-1092-BL-F0100](#) [105-1092-BL-00300](#) [105-1092-BL-00200](#) [105-1031-BL-00200](#)