



Notes:

1. Electrical Specifications:

- Meets USB 2.0 Specification
- Contact Resistance: 30 mOhm max.
- Insulation Resistance: 1000 MOhm min. @ 100 VDC
- Current Rating: 1.5 A max. at 25°C
- Working Voltage: 30 V (RMS) max.
- DWV: 500 VAC/60s at sea Level
- Operating Temperature: -40°C to +85°C

2. Material and Finish:

- Metal Coupling Ring: Brass, Nickel Plated
- Plug Housing: ABS, Nickel Plated, UL94 V-0
- Interfacial Seal: Silicon, Color: White
- Cable Fitting: PA (Black), UL94 V-0
- Cable Fitting Rubber Ring: NBR, Color: Black
- USB Metal Shell: SPCC, Nickel Plated
- USB Insulator: PBT UL94 V-0
- USB Contacts: Copper Alloy,
- USB Contact Finish: 30 u" Gold min. over Nickel for mating area, Tin over Nickel for solder cup

3. USB Type A Plug accepts AWG28 to AWG24 wires, Cable OD of 4.0 mm to 5.5 mm

4. IP67 rated when fully mated with the appropriate mating connector

RoHS Compliant

<small>THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY MANNER AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC CORPORATION</small> DO NOT ALTER CAD DRAWING BY HAND				Customer:			Tolerance Unless otherwise specified 0 PLC ±0.50 1 PLC ±0.38 2 PLC ±0.25 3 PLC ±0.10 ANGLES ±.7		Scale: 1.5:1	Dim. in mm
				Name	Title	Approval Date			Material: See Notes	
g	1 x g	Apr/21/2017	Vincent Ke	2008	Date	Name	Title: IP67 USB 2.0			
f	1 x f	Apr/21/2017	Vincent Ke	Draw.	Oct. 31	Vincent Ke	Type A Plug (Solder Cup) Assembly Kit			
e	1 x e	Feb/23/2017	Vincent Ke	Appd.	Oct. 31	J. Chaudry	Metal Version			
d	1 x d	Jun/23/2014	Vincent Ke	Norm			Drawing No.: 17K1A115			
c	1 x c	Nov/26/2009	Vincent Ke	D-old			Part No.: 17-200331			
b	1 x b	Jun/01/2009	Vincent Ke				DIN A3			
a	original						Sheet 1/1			
Rev.	Changes	Date	Name							

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [USB Connectors](#) category:

Click to view products by [CONEC](#) manufacturer:

Other Similar products are found below :

[65-647-8-BK-BU](#) [950](#) [952](#) [E8144-B01021-L](#) [A-USB B-TOP-C](#) [MUSBA511N5](#) [MUSBD11135](#) [217450-1](#) [KMBVX-TH-5S-B30](#) [896-30-004-00-000000](#) [KUSBVX-BS1N-W30](#) [KUSBX-AP-KIT-SCBLK](#) [KUSBX-AS2N-W](#) [KUSBX-SMT2AP1S-W](#) [KUSBX-SMT2AP1S-W30](#) [935](#) [957](#) [30-498-6](#) [SK-60A-2](#) [17-210051](#) [1734082-1](#) [30-1574](#) [30-470](#) [30-489](#) [30-541](#) [30-572-3](#) [A-USB A-2P-C](#) [MIKROE-1451](#) [USBFTV2PEM2G](#) [USBFTVC6ZN](#) [KUSBX-AS2N-W30](#) [KUSBX-SLAS1N-W](#) [KUSBX-SMT-AS1N-W30](#) [4689-1](#) [1-1734084-2](#) [E8110-001-01](#) [33UBARS1-04SW11](#) [33UBAR-04SW11](#) [USBF21ZNSCC](#) [USBBFTV6ZC](#) [10135326-001LF](#) [M9177/3-1](#) [USB-A-S-F-B-VT](#) [925](#) [4198](#) [690-024-633-031](#) [KUSBEX-BSFS1N-W](#) [USBFTVC6MRG](#) [UA-20BMFA-SL8001](#) [17-250101](#)