



NOTES:

1. Electrical Specifications:

- Meets USB 3.0 specifications
- Low level Contact Resistance:
- 30 mOhm max for VBUS and GND Contacts
- 50 mOhm max for all other contacts
- Insulation Resistance 1000 MOhm min.
- Current Rating: 2A max. @ 25°C
- DWV: 500V AC/60s Pin to Pin; 1000V AC/60s Pin to shell
- Connector Operating Temperature: -40°C to +85°C

2. Material and Finish:

- Coupling Ring: Polyester (Black); or ABS, Nickel Plated, UL94 V-0
 - Plug Housing: Polyester (Black); or ABS, Nickel Plated, UL94 V-0
 - Interfacial Seal: Silicone, Color: White
 - Cable Gland: PA (Black) or Brass, Nickel Plated
 - Cable Gland Seal: NBR, Color: Black
 - Cable Gland Insert (Metal Version): Nylon, Color: White
 - USB Insulator: PBT, UL 94V-0, Color: Blue
 - USB Metal Shell: SPCC, Nickel plated
 - USB Contact: Copper Alloy, 30 u" min. Au over 40 u" min. Nickel Plated
 - USB Insulator: PBT +GF, UL94 V-0, Color: Blue
3. Cable: UL AWM 2725, 2 x (Shielded Twist Pair AWG28 + Drain Wire)
+ 2 x Unshielded AWG28 + 2 x AWG24 + Drain Wire, Overall Braid Shield;
Outer Jack PVC, OD: 6.0 mm Color: Blue

⑥ Pin Assignment

Plug 1	Wire Map	Plug 2
p1	----- Red -----	p1
p2	----- White -----	p2
P3	----- Green -----	P3
P4	----- Black -----	P4
P5	----- Blue -----	P8
P6	----- Yellow -----	P9
P7	---- Drain Wire --	P7
P8	----- Purple -----	P5
P9	----- Orange -----	P6
Shell	----- Braid -----	Shell

L	Part Number	
	Plastic Version	Metallized Plastic Version
0.3 ± 0.03 m	17-241271	17-241351
0.5 ± 0.05 m	17-241281	17-241361
0.75 ± 0.05 m	17-241291	17-241371
1 ± 0.10 m	17-241301	17-241381
2 ± 0.10 m	17-241311	17-241391
3 ± 0.10 m	17-241321	17-241401

RoHS Compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY MANNER AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC CORPORATION DO NOT ALTER CAD DRAWING BY HAND	Customer:			Tolerance Unless otherwise specified 0 PLC ±0.50 1 PLC ±0.38 2 PLC ±0.25 3 PLC ±0.10 ANGLES ±3°		Scale: N/A	Dim. in
	Name	Title	Approval Date			Material: See Notes	
						Title: USB Patch Cord to USB 3.0 Type A Plug (Strain Relief) to USB 3.0 Type A Plug (IP20)	
						Drawing No.: 17K1A587	
	2 x b	Aug/16/2017	Vincent Ke		Part No.: SEE P/N ABOVE		DIN A3
Rev.	Changes	Date	Name		Sheet 1/1		

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [USB Cables / IEEE 1394 Cables category](#):

Click to view products by [CONEC manufacturer](#):

Other Similar products are found below :

[68768-0173](#) [FNY-W6003-01](#) [88764-0800](#) [148700-1](#) [17-200621](#) [17-250051P](#) [954](#) [17-200261](#) [AC102012-1](#) [AC102012-2](#) [FTP-629Y601](#) [45-1345-15](#) [45-1358-15](#) [45-1363-15](#) [IP-USB1\(C10\)S-RW](#) [CABLE/RTP/USB/DT](#) [45-1351-15](#) [45-1357-15](#) [45-1433-1](#) [687680278](#)
[USBFTVX2SA2N03A](#) [USBFTV2SA2N03A](#) [USBFTV2SA2N05A](#) [MDM9PH004B](#) [MDM9PH004P](#) [FTP-629Y401](#) [FTP-628Y302](#) [FTP-628Y402](#) [CSMNB9MF-5](#) [FNY-W6022](#) [UA-30AMF-SD7B03](#) [UA-30AMFM-SL7B03](#) [USBAPSCC7202A](#) [17-200641](#) [UES-1001A160](#) [UES-1003A160](#) [USBFTVX7SA2N20A](#) [FTP-629Y602](#) [USBCAMCM100](#) [USB A/F*2 to 2.54 2*5P-SH L=400mm](#) [68784-0075](#) [MINI-SCREW-USB-DATACABLE](#) [19800-010500-200-RS](#) [103-1092-BL-F0050](#) [103-1020-BL-00100](#) [103-1092-BL-F0200](#) [103-1092-BL-F0100](#) [105-1092-BL-00300](#) [105-1092-BL-00200](#) [105-1031-BL-00200](#)