



NOTES:

1. Electrical Specifications:

- Meets USB 2.0 Specifications
- Low level Contact Resistance:
 - 50 mOhm max. for mini USB
 - 30 mOhm max. for USB
- Insulation Resistance 100 MOhm min.
- Current Rating: 1.0 A max. @ 25°C
- DWV: 100 VAC/60s at sea level
- Connector Operating Temperature: -40°C to +80°C

2. Material and Finish:

- mini USB Coupling Ring: PBT (Black); UL94 V-0
- mini USB Overmold: PVC (Black); UL94 V-0
- mini USB Insulator: PBT, UL 94V-0, Black
- Gasket: Silicone, Transparent
- USB Insulator: PBT, UL 94V-0, Color: White
- USB Overmold: PVC, UL94 V-0, Color: Black
- mini USB & USB Metal Shell: Steel, Nickel plated
- mini USB & USB Contact: Copper Alloy, 30 u" min. Au over 40 u" min. Ni Plated

3. Shielded USB Cable Configuration

AWM 2725 AWG28/1p + AWG28/2c, OD: 3.5 mm Color: black

4. IP67 rated when fully mated with appropriate mating connector

Pin-Assignments

mini-B USB Plug	USB Cable	USB Type A Plug
Pin1 -----	Red -----	Pin1
Pin2 -----	White -----	Pin2
Pin3 -----	Green -----	Pin3
Pin4 -----	Not Connected	
Pin5 -----	Black -----	Pin4
Shell -----	Braid + Drain -----	Shell

ⓑ	Cable Length L	Part Number
Ⓒ	2 m +/-0.1m	17-250031
	3 m +/-0.1m	17-250041
	5 m +/-0.1m	17-250051

RoHS Compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY MANNER AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC CORPORATION. DO NOT ALTER CAD DRAWING BY HAND	Customer:			Tolerance Unless otherwise specified 0 PLC ±0.30 1 PLC ±0.20 2 PLC ±0.10 3 PLC ±0.05 ANGLES ±1°		Scale: 2	Dim. in m	
	Name	Title	Approval Date			Material: See Notes		
				2011	Date	Name	Title: USB Patch Cords IP67 mini-B USB Plug to Standard USB Type A Plug	
				Draw.	May 05	Vincent Ke		
				Appd.	May 05	J. Cahudry		
				Norm		Drawing No.: 17K1A140 Part No.: SEE P/N ABOVE		
c	1 x c	Mar/27/2015	Vincent Ke	D-old				DIN A3
b	1 x b	Feb/09/2015	Vincent Ke			Sheet 1/1		
a	original							
Rev.	Changes	Date	Name	CONEC®				

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [USB Connectors](#) category:

Click to view products by [CONEC](#) manufacturer:

Other Similar products are found below :

[65-647-8-BK-BU](#) [950](#) [952](#) [E8144-B01021-L](#) [A-USB B-TOP-C](#) [MUSBA511N5](#) [MUSBD11135](#) [217450-1](#) [KMBVX-TH-5S-B30](#) [896-30-004-00-000000](#) [KUSBVX-BS1N-W30](#) [KUSBX-AP-KIT-SCBLK](#) [KUSBX-AS2N-W](#) [KUSBX-SMT2AP1S-W](#) [KUSBX-SMT2AP1S-W30](#) [935](#) [957](#) [30-498-6](#) [SK-60A-2](#) [17-210051](#) [1734082-1](#) [30-1574](#) [30-470](#) [30-489](#) [30-541](#) [30-572-3](#) [A-USB A-2P-C](#) [MIKROE-1451](#) [USBFTV2PEM2G](#) [USBFTVC6ZN](#) [KUSBX-AS2N-W30](#) [KUSBX-SLAS1N-W](#) [KUSBX-SMT-AS1N-W30](#) [4689-1](#) [1-1734084-2](#) [E8110-001-01](#) [33UBARS1-04SW11](#) [33UBAR-04SW11](#) [USBF21ZNSCC](#) [USBBFTV6ZC](#) [10135326-001LF](#) [M9177/3-1](#) [USB-A-S-F-B-VT](#) [925](#) [4198](#) [690-024-633-031](#) [KUSBEX-BSFS1N-W](#) [USBFTVC6MRG](#) [UA-20BMFA-SL8001](#) [17-250101](#)