

## **Technical specification:**

Rated voltage: IEC 61076-2-104

3pos 60 V 4pos 30 V

Current rating: IEC 61076-2-104 3 A bei 40℃

Insulation resistance:

>=100 MΩ

IEC 60512

Pollution degree: IEC 60664-1

3/2

Degree of protection: IEC 60529

IP 67, in mated condition

Temperature range:

IEC 60664-1

-30℃ ... +85℃

Mating cycles: IEC 60512-9a >=100

Materials:

CuZn Contact:

Contact plating:


Nickel, gold plated


Contact carrier:


PA, UL 94


Socket housing:

CuZn, Nickel plated









Part no:	Description:	Pos	
42-01002	SAL - 8 - ESTM3 - L	3	
42-01003	SAL - 8 - ESTM4 - L	4	

OO NOT ALTER CAD DRAWING BY HAND Directive 2002/95/EC RoHS compliant

Index: a 02.03.11 fro Ä3914 Data sheet revised

dim. in mm

name date drawn 15.10.08 Fromm 15.10.08 Mankopf title:

Male socket M8x1 with soldering version

dwg no:

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH

42K1A111

part no:



## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Circular Metric Connectors category:

Click to view products by CONEC manufacturer:

Other Similar products are found below:

600X518037X 6STD15PCR99B70A 8R4000A16M020 8R5000A16M005 1200910002 1203580030 1200910008 1200910011 1300140094 130203-0054 1300140026 1300150099 RF-12S1N8A90DU 1-3637-600-5205 1612618 21036836414 8R4006A16M010 8R5006A18A120 1604232 1R3006A20M005 RF-12P1N8A80DU RF-12P1N8A90DU 41-40011 42-01015 4-22279-4 4-22281-1 4-22284-9 43-01088 43-01203 41-40013 42-00008 43-00343 43-01032 43-01162 43-10000 600X518050X SACC-DSI-FS-5P-PG9-L180 SC 8R5006A16M020 8R5006A16M005 8R4000A16M010 6-22279-3 1605332 N03FA03144 1300140077 43-01338 XS2RD4265 RSC 4/9 XS2R-D426-1 XS8A-0441 859RD04-103R004