





Rated voltage: IEC 61076-2-101 30 V

Current rating: IEC 61076-2-101 2 A at 40℃

Insulation resistance:

IEC 60512-2

>=100 MΩ

Pollution degree: IEC 60664-1

3/2

Degree of protection: IEC 60529

IP 67, in mated

condition

Temperature range:

-30℃ ... +85℃

Mating cycles: IEC 60512-9a

>=100

Wire cross section:

AWG20 / max. 0,5 mm²

Materials:

Contact:

CuZn

Contact plating:

Nickel, gold plated

Contact carrier:

PA6, UL 94

Contact screw:

Steel, zinc plated

Cable sealing:

Elastomere

O-Ring:

NBR

Coupling screw:

GD-Zn, nickel plated

Housing:

PA6 GF, UL 94

Installation specification:

Recommended

torque:

0,6 Nm

Conec

installation tooling:

Torque wrench: 36-000200

Insert across flats 18:

36-000240



Part no:	Description:	Cable-Ø:
43-00132	SAL - 12 - RSC8 - S	4 - 8 mm

OO NOT ALTER CAD DRAWING BY HAND Directive 2002/95/EC RoHS compliant

± 0,50mm 0 general tolerance: 0,0 ± 0,25mm 0,00 ± 0,10mm

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSIO OWNERSHIP AND COPYRIGHT OF CONEC GmbH

dim. in mm date name 16.10.13 Mankopf drawn appd. 16.10.13 Franz

title: Male connector M12x1, 8pos, field attachable, axial, with screw connection

dwg no:

43K1A2194

part no: see table

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Circular Metric Connectors category:

Click to view products by CONEC manufacturer:

Other Similar products are found below:

600X518037X 6STD15PCR99B70A 8R4000A16M020 8R5000A16M005 1200910002 1203580030 1200910008 1200910011 1300140094 130203-0054 1300140026 1300150099 RF-12S1N8A90DU 1-3637-600-5205 1612618 21036836414 8R4006A16M010 8R5006A18A120 1604232 1R3006A20M005 RF-12P1N8A80DU RF-12P1N8A90DU 41-40011 42-01015 4-22279-4 4-22281-1 4-22284-9 43-01088 43-01203 41-40013 42-00008 43-00343 43-01032 43-01162 43-10000 600X518050X SACC-DSI-FS-5P-PG9-L180 SC 8R5006A16M020 8R5006A16M005 8R4000A16M010 6-22279-3 1605332 N03FA03144 1300140077 43-01338 XS2RD4265 RSC 4/9 XS2R-D426-1 XS8A-0441 859RD04-103R004