

Technical specification:

Rated voltage: 4pos 5pos IEC 61076-2-101 250 V 60 V

Current rating: 4 A at 40℃

IEC 61076-2-101

Insulation resistance: >=100 MΩ

IEC 60512

Pollution degree: IEC 60664-1

3/2

Degree of protection: IP 67, in mated

IEC 60529 condition

Temperature range: IEC 60664-1

-30℃ ... +85℃

Mating cycles: IEC 60512-9a

>=100

Materials:

Contact: CuZn

Nickel, gold plated Contact plating:

Contact carrier: PA 6.6, UL 94

FPM Sealing:

Socket housing: CuZn, nickel plated

Shroud: Spring steel Tin plated -plating:

Installation specification:

recommended

0,8-1 Nm


torque:

Torque wrench:

Conec installation tool: 36-000200

Insert across flats 15:

36-000320







DO NOT ALTER CAD DRAWING BY HAND Directive 2002/95/EC RoHS compliant

Index: a 06.01.11 fro Ä3759 Installation specification added

THIS DRAWING MAY NOT BE COPIED OR

WRITTEN PERMISSION.

REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT

OWNERSHIP AND COPYRIGHT OF CONEC GmbH

name date

dim. in mm

drawn 15.10.07 Fromm 18.10.07 W. Schmidt

title:

Male Socket M12x1 axial, frontmounting, dip solder, X5,5

dwg no:

43K1A502

part no:

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Circular Metric Connectors category:

Click to view products by CONEC manufacturer:

Other Similar products are found below:

600X518037X 6STD15PCR99B70A 8R4000A16M020 8R5000A16M005 1200910002 1203580030 1200910008 1200910011 1300140094 130203-0054 1300140026 1300150099 RF-12S1N8A90DU 1-3637-600-5205 1612618 21036836414 8R4006A16M010 8R5006A18A120 1604232 1R3006A20M005 RF-12P1N8A80DU RF-12P1N8A90DU 41-40011 42-01015 4-22279-4 4-22281-1 4-22284-9 43-00113 43-01088 43-01203 41-40013 42-00008 43-00343 43-01032 43-01162 43-10000 600X518050X SACC-DSI-FS-5P-PG9-L180 SC 8R5006A16M020 8R5006A16M005 8R4000A16M010 6-22279-3 1605332 N03FA03144 1300140077 43-01338 XS2RD4265 RSC 4/9 XS2R-D426-1 XS8A-0441