

# ULTRA LOW POWER NXP i.MX 8X SERIES

## conga-SMX8-X



- NXP i.MX 8X processor series with ARM Cortex-A35 / M4F core complex
- Ultra low power architecture with 2-5W
- Highest reliability and improved virtualization
- Support for up to 2 independent HD displays
- Extended longevity up to 15 years
- Temperature range up to -40°C .. +85°C



<b>Form factor</b>	SMARC Specification 2.1			
<b>CPU</b>	<b>NXP i.MX 8X ARM Processor Cores</b>			
	<b>i.MX 8QuadXPlus</b>	<b>ARM Cortex-A35</b> 4x Cortex-A35 @ 1.2GHz	<b>ARM Cortex-M4F</b> 1x Cortex-M4F @ 264MHz	<b>GPU</b> 1x GC7000Lite
<b>DRAM</b>	Up to 4 GByte onboard LPDDR4 memory   2400 MT/s			
<b>Ethernet</b>	Up to 2x Gbit Ethernet with IEEE 1588 support			
<b>I/O Interfaces</b>	Up to 5x USB 2.0 (1x shared with USB OTG client)   up to 2x USB 3.0   1x SDIO 3.0   1x PCIe 3.0   I <sup>2</sup> C Bus   1x SPI   1x QSPI up to 4x UART (2x with Handshake (1x shared with FlexCAN))   2x FlexCAN   GPIOs   optional soldered M.2 1216 WiFi/BT			
<b>Mass Storage</b>	eMMC 5.1 up to 128 GByte			
<b>Sound</b>	Up to 2x I <sup>2</sup> S   optional processor with Tensilica <sup>®</sup> HiFi 4 DSP			
<b>Graphics</b>	Integrated in NXP i.MX 8X Series GT7000Lite multimedia GPU VPU up to 4K h.265 dec / 1080p h.264 enc/dec   3D Graphics with up to 4 high performance vec4 shaders and 16 execution units   up to 2 independent displays   OpenGL ES 3.1   Vulkan VX extensions   OpenCL 1.2 EP   OpenVG 1.1			
<b>Video Interfaces</b>	1x dual channel or 2x single channel LVDS 24 bit   2x MIPI-DSI with 4-lanes shared with LVDS   1x MIPI-CSI 4-lanes			
<b>Features</b>	Watchdog Timer   I <sup>2</sup> C bus 400 kHz   Cortex-A35 Console   optional JTAG debug interface   High Precision Real Time Clock			
<b>Virtualization</b>	Hardware Virtualization with Domain Separation   Multiple Operating System Support			
<b>Security</b>	High Assurance Boot support, SHE   Inline Encryption Engine (AES-128)   TRNG, AES-128, AES-256, 3DES, ARC4, RSA4096, SHA-1, SHA-2, SHA-256, MD-5   RSA-1024, 2048, 3072, 4096 and secure key storage			
<b>Boot Loader</b>	U-Boot boot loader			
<b>Operating Systems</b>	Linux   Yocto Linux   Android			
<b>Power Consumption</b>	Ultra low power Cortex-A35   typ. application 2-5W @ 5V			
<b>Temperature Range</b>	Operating Temperature Range:		-40 to +85°C industrial grade	
	Storage Temperature Range:		-40 to +85°C	
<b>Humidity</b>	Operating: 10 - 90% r. H. non cond.		Storage: 5 - 95% r. H. non-condensing	
<b>Size</b>	82 x 50 mm (3,23" x 1,97")			

# conga-SMX8-X | Block Diagram



\* Assembly Option

# conga-SMX8-X | Order Information

Article	PN	Description
conga-SMX8-X/i-QXP-4G eMMC16	051110	SMARC 2.1 module with ultra low power NXP i.MX 8QuadXPlus processor with 4x ARM Cortex-A35 and 1x ARM Cortex-M4F, 4GB onboard LPDDR4 memory and 16GB onboard eMMC. Industrial temperature range.
conga-SMX8-X/i-QXP-2G eMMC16	051113	SMARC 2.1 module with ultra low-power NXP i.MX 8QuadXPlus processor with 4x ARM Cortex-A35 and 1x ARM Cortex-M4F, 2GB onboard LPDDR4 memory and 16GB onboard eMMC. Industrial temperature range.
conga-SMX8-X/i-CSP-B	051150	Passive cooling solution for SMARC module conga-SMX8-X with lidded NXP i.MX 8X ARM processor. All standoffs are with 2.7mm bore hole.
conga-SMX8-X/i-HSP-B	051151	Heat spreader solution for SMARC module conga-SMX8-X with lidded NXP i.MX 8X ARM processor. All standoffs are with 2.7mm bore hole.
conga-SEVAL	007010	Evaluation carrier board for SMARC modules.
conga-SMC1/SMARC-ARM	020750	3.5" carrier board for congatec SMARC modules based on NXP i.MX ARM architecture.

© 2022 congatec GmbH. All rights reserved.

All data is for information purposes only. Although all the information contained within this document is carefully checked, no guarantee of correctness is implied or expressed. Product names, logos, brands, and other trademarks featured or referred are the property of their respective trademark holders. These trademark holders are not affiliated with congatec GmbH.  
Rev. 1.5, March 16, 2022

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Heat Sinks](#) category:*

*Click to view products by [Congatec](#) manufacturer:*

Other Similar products are found below :

[657-20ABPNE](#) [73452PPBA](#) [A22-4026](#) [120-1873-007](#) [218-40CTE3](#) [231-69PAB-15V](#) [231-75PAB-13V](#) [231-75PAB-15V](#) [253-122ABE-22](#)  
[PSC22CB](#) [295-2](#) [CLP212SG](#) [D10100-28](#) [BDN183CBA01](#) [3-21053-4](#) [TX0506-1B](#) [LAE66A3CB](#) [511-3U](#) [73381PPBA](#) [73403PPBA](#) [8191-](#)  
[E40](#) [510-12M](#) [529802B00000](#) [D10650-40T5](#) [6225B-MT6G](#) [ATS-54310K-C2-R0](#) [648-51AB](#) [657-20ABPESC](#) [679-25AG](#) [FK 212 CB SA](#)  
[FK225 SA L1](#) [241404B91203G](#) [6801G](#) [680-5K](#) [7106DG/TR](#) [SK145 37 5STSTO220](#) [7109DG/TR](#) [TS-11042-CY](#) [S14K35G3S5](#) [8924G](#)  
[7717-133DAP](#) [7717-26DAP](#) [4509](#) [SW25-4G](#) [CLP-215](#) [CLP-207](#) [D20850-40-T2](#) [APF30-30-10CB/A01](#) [V8508E](#) [268-85CTE](#)