

# ADA/APA-A

6.3Ø x 32 mm

Time-Lag Fuse



### Agency Approvals

Agency	Ampere Rating
UL Listed	ADA: 100mA - 20A APA-A: 100mA - 15A
UL Recognized	APA-A only: 15.1A - 20A
Recognized Component for Canada and US	20.1A - 30A
CSA Certified	100mA - 15A
CSA Acceptance	15.1A - 20A
PSE	5.1A - 15A (250V)

### Interrupting Rating

100mA - 30A:	10,000 amperes at 125V AC
100mA - 1A:	35 amperes at 250V AC
1.25A - 3.5A:	100 amperes at 250V AC
3.75A - 10A:	200 amperes at 250V AC
10.1A - 15A:	750 amperes at 250V AC
15.1A - 20A:	1,500 amperes at 250V AC (ADA) 400 amperes at 250V AC (APA-A)
20.1A - 30A:	1,500 amperes at 250V AC 10,000 amperes at 125V DC


### Product Characteristics

<b>Operating Temperature</b>	-55 °C to 125 °C
<b>Material</b>	Body: Ceramic / Caps: Nickel Plated Brass
<b>Leads Wire</b>	Ø0.8 mm 12A and less. Ø1.0 mm for rating above 13A to 19A. Ø1.2 mm for rating above 20A.

### Packaging

Packaging Option	Quantity
Bulk	ADA: 500 pcs / box APA-A: 250 pcs / box

### Mechanical Dimensions (mm)



### Electrical Characteristics

Ampere Rating	Opening Time			
	1 In	1.35 In	2 In	
	MIN	MAX	MIN	MAX
100mA - 30A	4 hr	1 hr	2 sec	120 sec

Catalog Number	Ampere Rating (A)	Voltage Rating (V)	Nominal Cold Resistance (Ohms)	Nominal Melting I <sup>2</sup> t (A <sup>2</sup> sec.)
ADA / APA-A .100	100mA	250V	16.570	0.0200
ADA / APA-A .125	125mA		10.705	0.0313
ADA / APA-A .150	150mA		9.5450	0.0563
ADA / APA-A .160	160mA		8.3850	0.0640
ADA / APA-A .175	175mA		7.2250	0.0766
ADA / APA-A .180	180mA		6.0650	0.0879
ADA / APA-A .200	200mA		4.9050	0.1400
ADA / APA-A .250	250mA		4.3940	0.1875
ADA / APA-A .300	300mA		3.8881	0.7477
ADA / APA-A .315	315mA		3.8821	0.7520
ADA / APA-A .350	350mA		2.8762	0.9211
ADA / APA-A .375	375mA		2.2000	1.0078
ADA / APA-A .400	400mA		1.5237	1.0944
ADA / APA-A .500	500mA		0.8705	4.5000
ADA / APA-A .600	600mA		0.5779	0.4970
ADA / APA-A .700	700mA		0.4208	0.7610
ADA / APA-A .750	750mA		0.3801	0.9455
ADA / APA-A .800	800mA		0.3425	1.3788
ADA / APA-A 001	1A		0.2394	2.4644
ADA / APA-A 1.25	1.25A		0.1667	5.3063
ADA / APA-A 1.50	1.5A		0.1234	7.5265
ADA / APA-A 1.60	1.6A		0.1126	11.748
ADA / APA-A 002	2A		0.1993	7.8624
ADA / APA-A 2.50	2.5A		0.1208	11.674
ADA / APA-A 003	3A		0.0885	16.061
ADA / APA-A 3.50	3.5A		0.0823	28.190
ADA / APA-A 004	4A		0.0592	40.320
ADA / APA-A 4.50	4.5A		0.0453	56.984
ADA / APA-A 005	5A		0.0401	73.647
ADA / APA-A 006	6A		0.0308	116.96
ADA / APA-A 6.30	6.3A	0.0293	117.30	
ADA / APA-A 007	7A	0.0156	119.50	
ADA / APA-A 008	8A	0.0132	150.00	
ADA / APA-A 010	10A	0.0098	270.00	
ADA / APA-A 012	12A	0.0080	417.32	
ADA / APA-A 013	13A	0.0076	587.91	
ADA / APA-A 015	15A	0.0054	777.44	
ADA / APA-A 020	20A	0.0043	1296.0	
ADA / APA-A 025	25A	0.0030	2715.8	
ADA / APA-A 030	30A	0.0024	4446.1	

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Cartridge Fuses](#) category:*

*Click to view products by [Conquer](#) manufacturer:*

Other Similar products are found below :

[MBO-20](#) [MDA-V-1/100](#) [12C10X38GI](#) [AGA-V-2-1/2](#) [AGC-V-3-12-R](#) [AGY-50](#) [MSL-3](#) [MSL-4](#) [MSL-5](#) [BK1/C436-2A](#) [BK1-GMA-1-6-R](#)  
[BK1-GMA-200-R](#) [BK1GMA-6-R](#) [BK1/GMC-100-R](#) [BK1/GMC-1.5-R](#) [BK1-GMC-2-5-R](#) [BK1GMD-4-R](#) [BK1S500-250-R](#) [BK1S500-32-R](#)  
[BK1-S500-4-R](#) [BK1S500-5-R](#) [BK1-S505-1-R](#) [BK1-S506-2-R](#) [BK1-S506-3-15-R](#) [BK1/S506-63-R](#) [BK/ABC-5RX](#) [BK/AGW-B-4](#) [BK/AVX-](#)  
[1/4](#) [BK/C515S-250-R](#) [BK/MBO-20](#) [BK/MBO-8](#) [BK/MDM-3/4](#) [BK-MDQ-4](#) [BK/S505-V-2.5A](#) [BK/TDC120-15](#) [BK/TDC120-20](#)  
[BK/TDC122-45](#) [BP/MDL-7](#) [1C10X38AM](#) [S505-V-500MA](#) [SEF-1697-1-002](#) [AGA-V-7-1/2](#) [AGC-15WX](#) [AGC-2-1-2-R](#) [20.0M6.3X32F](#)  
[20C8X32GI](#) [GMC-50-R](#) [361.250](#) [MBO-8](#) [TDC121-30](#)