



功得電子工業股份有限公司  
CONQUER ELECTRONICS CO.,LTD.

# 規格書

Spec. No. SFA409

## Specification For Approval

品名： CQ-111(PF) 系列保險絲夾

Type： CQ-111(PF) Series CLIP

[www.conquer.com.tw](http://www.conquer.com.tw)

五股廠：新北市五股區五權五路26號(新北產業園區)  
Wugu Factory:No.26, Wucyuan 5th Rd., Wugu Dist.,  
(New Taipei Industrial Park) New Taipei City  
24888, Taiwan  
TEL:+886-2-89902189(Rep.)  
+886-2-2CONQUER(Rep.)  
FAX:+886-2-8990-2577

北投廠：台北市北投區立德路120巷15號  
Peitou Factory:No. 15,Lite Road,Peitou,  
Taipei11259, Taiwan.  
TEL:+886-2-2895-8895(代表號)  
FAX:+886-2-2895-8880



### History of Change

REV.	Description	Date	Drawn	Designed	Checked	Approved
1	1.Issue	2016.05.03	林嘉豪	邱俊傑	蔡進義 趙宏遠	蔡其湖

Conquer Electronics Co., LTD.


No.26, Wucyuan 5th Rd., Wugu Dist.,(New Taipei Industrial Park) New Taipei City 24888, Taiwan TEL:+886-2-8990-2189 (代表號) FAX:+886-2-8990-2577

Peitou Factory : No. 15, Lane 120, Lite Road, Peitou, 11259, Taipei, Taiwan. TEL: +886-2-2895-8895 (代表號) FAX:+886-2-2895-8880

E-mail: conqfuse@ms62.hinet.net Official Website: <http://www.conquer.com.tw>

1. **適用範圍** Available Range : P.C. board mount fuse clip for blade auto fuse ATQ type ◦

2. **形狀及尺寸如下圖** Shape & Size as following illustrations ◦ 單位 Unit : mm



公差 Tolerance :  $\pm 0.2$

安裝孔  
Mounting Holes

3. **金屬材料** Metal Material :

CQ-111 (PF) 為黃銅 Brass.

CQ-111 (CQ) (PF) 為磷青銅 Phosphor Bronze.

4. **材料厚度** Material Thickness (mm) :  $0.35 \pm 0.03$

5. **電性特性** Electrical Characteristics :

CQ-111 (PF) 額定電流 Rated Current : 15A

CQ-111 (CQ) (PF) 額定電流 Rated Current : 40A

6. **表面處理** Surface treatment : 鍍亮錫 Bright Tin Plated ◦

7. **類型** Type : 擋耳類型 Ear Type ◦

8. **機械特性** Mechanical Properties :

第一次插拔的力量 The insertion and pulling forces of the first time :  $\geq 1\text{Kgf}$  ◦



9. **儲存方式及期限** Storage Methods And Duration :

9.1 儲存條件：封口須保持完整性, 建議儲存溫度 $25^{\circ}\text{C}$  ( $+5^{\circ}\text{C}$ ,  $-10^{\circ}\text{C}$ )、  
溼度 $40\%RH$  ( $+20\%RH$ ,  $-20\%RH$ )。

Storage conditions : Package need to be sealed completely, the recommended storage  
temperature  $25^{\circ}\text{C}$  ( $+5^{\circ}\text{C}$ ,  $-10^{\circ}\text{C}$ )、relative humidity  $40\%RH$  ( $+20\%RH$ ,  $-20\%RH$ ).

9.2 保存期限：未拆包為六個月，建議拆包後為一星期，產品拆包後易有氧化的風險，  
如未使用完請封口。

Expiration date : For packing products : 6 months , For unpacking products :  
recommend one week. Due to the risk of oxidation for unpacking product,  
please seal completely the package for the remainders.

10. **包裝方式** Packing : 1000 pcs/box

---

Conquer Electronics Co., LTD.

No.26, Wucyuan 5th Rd., Wugu Dist., (New Taipei Industrial Park) New Taipei City 24888, Taiwan TEL:+886-2-8990-2189 (代表號) FAX:+886-2-8990-2577

Peitou Factory : No. 15, Lane 120, Lite Road, Peitou, 11259, Taipei, Taiwan. TEL: +886-2-2895-8895 (代表號) FAX:+886-2-2895-8880

E-mail: conqfuse@ms62.hinet.net Official Website: <http://www.conquer.com.tw>

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Fuse Holder](#) category:*

*Click to view products by [Conquer](#) manufacturer:*

Other Similar products are found below :

[0031.1351.01](#) [6R30A1B](#) [6SC30A2IC](#) [F30A3S](#) [F600A3B](#) [80910030](#) [80910080](#) [9-3557-GP REV A](#) [HFH-1](#) [RF30A1S](#) [RF30A2B](#) [RF30A3SP](#)  
[15602-04-08-21](#) [HTJ-LES-FUSE](#) [RTMF-SC](#) [2602](#) [2650](#) [178.000100](#) [F60A2SQ](#) [T30A2B](#) [2660](#) [HKP-CCHH](#) [R6F30A2S](#) [341001A](#) [345621A](#)  
[348670](#) [CVRMCC](#) [4202](#) [4408](#) [4423](#) [4532](#) [4537](#) [HPC](#) [55900008011](#) [32NNL](#) [345602-010](#) [345603-010](#) [345612](#) [345903A](#) [3578](#) [3833-5](#)  
[3833-7](#) [3992](#) [4393](#) [4409](#) [4522](#) [4574](#) [02800031Z](#) [ESFH04/HTCC35M](#) [02800002Z](#)