



+105°C Long Life



### FEATURES

Small size – Extended Life – Low cost

### APPLICATIONS

Filtering – Bypass – Coupling – Blocking

Operating Temperature Range		<b>-40°C to +105°C (6.3 to 100WVDC)</b> <b>-25°C to +105°C (160 to 450WVDC)</b>														
Capacitance Tolerance		<b>+20% at 120 Hz, 20°C</b>														
Surge voltage	WVDC	6.3	10	16	25	35	50	63	100	160	200	250	400	450		
	SVDC	7.9	13	20	32	44	63	79	125	200	250	300	450	500		
Dissipation Factor	WVDC	6.3	10	16	25	35	50	63	100	160	200	250	400	450		
	$\tan \delta$	.3	.24	.2	.16	.14	.14	.18	.18	.2	.2	.2	.25	.25		
D $\geq$ 12.5		.35	.3	.34	.26	.22	.18	.14	.18	.2	.2	.2	.25	.25		
Leakage current		<b>2 Minutes</b> .01CV or 3 $\mu$ A, Whichever is greater														
Low temperature stability Impedance ratio (120 Hz)	Rated WVDC	6.3	10	16	25	35	50	63	100	160-450						
	-25°C/+20°C	4	3	2	2	2	2	2	2	4						
	-40°C/+20°C	8	8	4	4	3	3	3	3	-						
Load Life		<b>2000 hours at 105°C with rated WVDC</b>														
Capacitance change		$\leq 30\%$ of initial measured value														
Dissipation factor		$\leq 300\%$ of maximum specified value														
Leakage current		$\leq 100\%$ of maximum specified value														
Shelf Life		<b>1000 hours at 105°C with no voltage applied</b>														
Capacitance change		$\leq 30\%$ of initial measured value														
Dissipation factor		$\leq 300\%$ of maximum specified value														
Leakage current		$\leq 100\%$ of maximum specified value														
Resistance to soldering heat		Capacitors placed on a 250°C hot plate for 30 seconds with their electrode terminations facing downward will fulfill the following conditions after being cooled to room temperature														
Capacitance change		$\leq 10\%$ of initial measured value														
Dissipation factor		$\leq 100\%$ of maximum specified value														
Leakage current		$\leq 100\%$ of maximum specified value														
Ripple Current Multipliers		<b>Frequency (Hz)</b>														
		50	120	400	1k	10k	100k									
		0.7	1.0	1.17	1.38	1.5	1.5									



D	L	W $\pm$ 0.2	H $\pm$ 0.2	C $\pm$ 0.2	R	LL $\pm$ 0.2	S $\pm$ 0.2
4.0	5.4 +/-0.3	4.3	4.3	5.0	0.5~0.8	1.8	1.0
5.0	5.4 +/-0.3	5.3	5.3	6.0	0.5~0.8	2.1	1.4
6.3	5.4 +/-0.3	6.6	6.6	7.3	0.5~0.8	2.4	2.2
6.3	7.7 +/-0.3	6.6	6.6	7.3	0.5~0.8	2.4	2.2
8.0	10.5+/-0.3	8.3	8.3	9.0	0.7~1.0	2.9	3.1
10.0	10.5+/-0.3	10.3	10.3	11.0	0.7~1.0	3.2	4.5
12.5	13.5+/-0.5	13.0	13.0	15.0	0.7~1.1	4.8	4.4
12.5	16.0+/-0.5	13.0	13.0	15.0	0.7~1.1	4.8	4.4

**Americas / EU**  
Phone: 1-508-996-8561  
Email: cdena@cde.com

**CDE**  
ENERGIZING IDEAS

**CORNELL DUBILIER**

**IC**  
ILLINOIS CAPACITOR

**Asia**  
Phone: 852-2793-0931  
Email: cdeasia@cde.com

WVDC	Capacitance ( $\mu$ F)	IC PART NUMBER	Maximum ESR ( $\Omega$ ) 120 Hz, +20°C	Maximum RMS Ripple Current (mA) 120 Hz, +105°C	Dims DxL (mm)
6.3	4.7	<b>475SVH6R3MCR</b>	10.82	31	4x5.4
6.3	22	<b>226SVH6R3MCR</b>	22.61	22	4x5.4
6.3	33	<b>336SVH6R3MCR</b>	15.07	29	4x5.4
6.3	47	<b>476SVH6R3MDR</b>	10.58	36	5x5.4
6.3	150	<b>157SVH6R3MGE</b>	3.32	86	6.3x5.4
6.3	220	<b>227SVH6R3MER</b>	2.261	80	6.3x5.4
6.3	330	<b>337SVH6R3MEL</b>	1.507	140	6.3x7.7
6.3	680	<b>687SVH6R3MFE</b>	0.73	340	8x10.5
6.3	1500	<b>158SVH6R3MGE</b>	0.39	460	10x10.5
10	33	<b>336SVH010MDR</b>	12.06	35	5x5.4
10	220	<b>227SVH010MEL</b>	1.8086	120	6.3x7.7
10	1000	<b>108SVH010MGE</b>	0.4	450	10x10.5
10	2200	<b>228SVH010MTP</b>	0.23	680	12.5x13.5
16	22	<b>226SVH016MCR</b>	12.06	29	4x5.4
16	33	<b>336SVH016MDR</b>	8.04	40	5x5.4
16	47	<b>476SVH016MDR</b>	5.6438	42	5x5.4
16	100	<b>107SVH016MER</b>	3.32	60	6.3x5.4
16	220	<b>227SVH016MEL</b>	1.51	105	6.3x7.7
16	470	<b>477SVH016MFE</b>	0.71	240	8x10.5
25	10	<b>106SVH025MCR</b>	26.53	13	4x5.4
25	22	<b>226SVH025MDR</b>	12.06	23	5x5.4
25	33	<b>336SVH025MER</b>	8.04	38	6.3x5.4
25	47	<b>476SVH025MER</b>	5.64	48	6.3x5.4
25	100	<b>107SVH025MEL</b>	2.65	100	6.3x7.7
25	100	<b>107SVH025MEL</b>	2.6526	100	6.3x7.7
25	150	<b>157SVH025MEL</b>	1.77	91	6.3x7.7
25	220	<b>227SVH025MFE</b>	1.21	240	8x10.5
25	330	<b>337SVH025MFE</b>	0.8	320	8x10.5
25	470	<b>477SVH025MGE</b>	0.56	450	10x10.5
25	680	<b>687SVH025MGE</b>	0.39	490	10x10.5
25	1500	<b>158SVH025MTBW</b>	0.29	590	12.5x16
35	4.7	<b>475SVH035MCR</b>	49.38	16	4x5.4
35	6.8	<b>685SVH035MCR</b>	31.13	25	4x5.4
35	22	<b>226SVH035MER</b>	10.55	44	6.3x5.4
35	100	<b>107SVH035MEL</b>	2.65	100	6.3x7.7
35	150	<b>157SVH035MFE</b>	1.55	260	8x10.5
35	220	<b>227SVH035MFE</b>	1.5071	170	8x10.5
35	330	<b>337SVH035MGE</b>	0.7	410	10x10.5
35	470	<b>477SVH035MTP</b>	0.78	520	12.5x13.5
35	680	<b>687SVH035MTP</b>	0.54	590	12.5x13.5
50	1	<b>105SVH050MCR</b>	232.1	6.3	4x5.4
50	2.2	<b>225SVH050MCR</b>	105.5	11	4x5.4
50	3.3	<b>335SVH050MCR</b>	70.33	14	4x5.4
50	4.7	<b>475SVH050MDR</b>	49.38	19	5x5.4
50	10	<b>106SVH050MER</b>	23.21	30	6.3x5.4
50	22	<b>226SVH050MEL</b>	10.55	51	6.3x7.7
50	33	<b>336SVH050MEL</b>	7.03	60	6.3x7.7
50	47	<b>476SVH050MEL</b>	4.94	63	6.3x7.7
50	100	<b>107SVH050MFE</b>	2.82	230	8x10.5
50	150	<b>157SVH050MGE</b>	1.55	250	10x10.5
50	220	<b>227SVH050MGE</b>	1.06	375	10x10.5
50	330	<b>337SVH050MTP</b>	0.9043	490	12.5x13.5
50	330	<b>337SVH050MTP</b>	0.9043	490	12.5x13.5
50	470	<b>477SVH050MTBW</b>	0.5644	550	12.5x16
63	47	<b>476SVH063MFE</b>	6.35	170	8x10.5
63	100	<b>107SVH063MGE</b>	2.98	340	10x10.5
63	150	<b>157SVH063MGE</b>	1.99	360	10x10.5
63	220	<b>227SVH063MTP</b>	1.3564	470	12.5x13.5

**SVH****+105°C, Long Life, 2000 hours**

WVDC	Capacitance ( $\mu$ F)	IC PART NUMBER	Maximum ESR ( $\Omega$ ) 120 Hz, $+20^{\circ}\text{C}$	Maximum RMS Ripple Current (mA) 120 Hz, $+105^{\circ}\text{C}$	Dims DxL (mm)
100	22	<b>226SVH100MFE</b>	13.56	100	8x10.5
100	33	<b>336SVH100MFE</b>	9.04	120	8x10.5
100	33	<b>336SVH100MGE</b>	9.04	150	10x10.5
100	47	<b>476SVH100MFE</b>	6.35	170	8x10.5
100	47	<b>476SVH100MGE</b>	6.35	250	10x10.5
100	47	<b>476SVH100MTP</b>	6.3493	250	12.5x13.5
100	100	<b>107SVH100MTP</b>	2.98	300	12.5x13.5
160	33	<b>336SVH160MTP</b>	10.0477	95	12.5x13.5
200	10	<b>106SVH200MTP</b>	33.1573	80	12.5x13.5
200	22	<b>226SVH200MTBW</b>	15.0715	110	12.5x16
200	33	<b>336SVH200MTBW</b>	10.0477	120	12.5x16
250	22	<b>226SVH250MTP</b>	15.0715	105	12.5x13.5
400	10	<b>106SVH400MTP</b>	41.4466	50	12.5x13.5
450	3.3	<b>335SVH450MTP</b>	125.6	40	12.5x13.5
450	4.7	<b>475SVH450MTP</b>	88.1843	45	12.5x13.5
450	10	<b>106SVH450MTBW</b>	41.4466	75	12.5x16

Americas / EU  
Phone: 1-508-996-8561  
Email: [cdena@cde.com](mailto:cdena@cde.com)



Asia  
Phone: 852-2793-0931  
Email: [cdeasia@cde.com](mailto:cdeasia@cde.com)

# X-ON Electronics

Largest Supplier of Electrical and Electronic Components

***Click to view similar products for Aluminium Electrolytic Capacitors - SMD category:***

***Click to view products by Cornell Dubilier manufacturer:***

Other Similar products are found below :

[EEV-FK1E332W 22927](#) [MAL214099813E3](#) [HUB1800-S 34610](#) [RYK-50V101MG5TT-FL 107AXZ016MQ5](#) [EMF1EM101E83D00R](#)  
[EMK1AM221E83D00R](#) [EMK1EM471GB0D00R](#) [EMK1VM101E83D00R](#) [EMVY350ARA221MHA0G](#) [UV2G3R3M0810VG](#)  
[RVT2A4R7M0605](#) [MAL214097402E3](#) [MAL215375471E3](#) [MAL224699909E3](#) [MAL224699813E3](#) [MAL215099017E3](#) [MAL215099117E3](#)  
[MAL215099818E3](#) [AEH1010471M010R](#) [AEA0810101M035R](#) [AEA1010681M016R](#) [AEA1010471M025R](#) [AEA0810331M010R](#)  
[AEA1616102M050R](#) [AEH1010101M050R](#) [AEA1010102M010R](#) [AEA1010102M016R](#) [AEH0810470M050R](#) [AEA0810220M100R](#)  
[AEA0810151M035R](#) [AEA0810331M016R](#) [AEA0810331M025R](#) [AEA0810470M063R](#) [AEA1213221M063R](#) [AEA1213471M035R](#)  
[AEH0608101M016R](#) [AEH0608220M050R](#) [AEH0608330M050R](#) [AEH0608470M025R](#) [AEH0608470M035R](#) [AEH0810101M025R](#)  
[AEH1012101M063R](#) [HV100M100E077ETR](#) [RC0J226M04005VR](#) [RC0J476M05005VR](#) [RC1A227M08010VR](#) [RC1C476M6L005VR](#)