

EIA Class 2 Temperature/ Frequency Stable Ceramic Capacitors

High Voltage Highlights and Specifications



- Highly Efficient for Bypass and Coupling Applications
- Designed Around EIA Test
- Spec. RS-165ARadial Leads

Capacitance Range: 100 pF to 10,000 pF
Voltage Range: 2,000 and 3,000 WVDC
Tolerance: 10%. 20%
Operating Temperature Range: -30 °C to +85 °C
Lead Length: 1 inch minimum
Insulation Resistance: 10,000 megohms (min)
Power Factor @ 1000 Hz: 2.5% Max
Breakdown Voltage: 2.5 x rated(5 seconds Max)

Ratings

Part Number	Capacity pF	Tol	Temp Coef	Size (inches)				Size (Millimeters)				Part Number	Capacity pF	Tol	Temp Coef	Size (inches)				Size (Millimeters)			
				D	T	S	d	D	T	S	d					D	T	S	d	D	T	S	d
2000 WVDC												3000 WVDC											
HS102M	1,000	20%	Y5U**	.394	.236	.252	.032	10.0	6.0	6.4	0.8	HT471K	470	10%	Y5P	.394	.236	.374	.032	10.0	6.0	9.5	0.8
HS152M***	1,500	20%	Y5U**	.394	.236	.252	.032	10.0	6.0	6.4	0.8	HT561K***	560	10%	Y5P	.394	.236	.374	.032	10.0	6.0	9.5	0.8
HS222M***	2,200	20%	Y5U**	.433	.236	.252	.032	11.0	6.0	6.4	0.8	HT681K***	680	10%	Y5P	.433	.236	.374	.032	11.0	6.0	9.5	0.8
HS332M***	3,300	20%	Y5U**	.590	.236	.374	.032	15.0	6.0	9.5	0.8	HT821K***	820	10%	Y5P	.433	.236	.374	.032	11.0	6.0	9.5	0.8
HS472M***	4,700	20%	Y5U**	.590	.236	.374	.032	15.0	6.0	9.5	0.8	HT102M	1,000	20%	Y5U**	.394	.236	.374	.032	10.0	6.0	9.5	0.8
HS103M	10,000	20%	Y5U**	.787	.236	.374	.032	20.0	6.0	9.5	0.8	HT152M***	1,500	20%	Y5U**	.433	.236	.374	.032	11.0	6.0	9.5	0.8
3000 WVDC																							
HT271K***	270	10%	Y5P	.394	.236	.374	.032	10.0	6.0	9.5	0.8	HT182M***	1,800	20%	Y5U**	.433	.236	.374	.032	11.0	6.0	9.5	0.8
HT331K***	330	10%	Y5P	.394	.236	.374	.032	10.0	6.0	9.5	0.8	HT222M	2,200	20%	Y5U**	.590	.236	.374	.032	15.0	6.0	9.5	0.8
												HT472M*** 4,700 20% Y5U** .787 .236 .374 .032 20.0 6.0 9.5 0.8											
												HT682M*** 6,800 20% Y5U** 0.787 .236 .374 .032 20.0 6.0 9.5 0.8											

****Please note: Y5U Will no longer be available once stock is depleted. (2/23/05)**

*****Part number is obsolete**

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Cornell Dubilier](#) manufacturer:

Other Similar products are found below :

[474K400CS6](#) [107RZS016M](#) [CK06BX563K](#) [TDC226K035WSG-F](#) [CK05BX151K](#) [CK05BX472K](#) [TDC106K010NSF-F](#) [CK06BX223K](#)
[CK06BX332K](#) [106MABA02KJS](#) [CK05BX182K](#) [CK05BX181K](#) [CK05BX101K](#) [205QPC250KA3A1LL](#) [255QPC250KA3A1L](#) [CK05BX560K](#)
[CK05BX222K](#) [CK05BX270K](#) [CK05BX271K](#) [RJD2450ST1](#) [RJD3032](#) [RJD2430C1](#) [C0805C102K5RAC](#) [CK05BX822K](#) [ESRD100M06R](#)
[CK05BX104K](#) [EDLSG105V5R5C](#) [5AE-2000](#) [M39018/04-2181M](#) [M39018/06-0158M](#) [715P15456MA3](#) [EWF05047](#) [EWF1A147](#)
[MLP562M063EB0C](#) [MLS221M250EK0C](#) [MMW05W5-5.0MFD](#) [GM303M](#) [PSU4330](#) [PSU46030](#) [PVC16268](#) [PVC1628](#) [PVC2168](#) [124-](#)
[138MFD](#) [DCMX262T400BF2B](#) [AFK686M63G24T-F](#) [MR10KT](#) [150472K630AA](#) [155PHC600K](#) [160104J160C](#) [MTC52L4](#)