


# TEPS-series



## Feature

- Low-profile
- Small and compact PCB construction
- High efficiency
- Harmonic attenuator (Complies with IEC61000-3-2)
- Universal input (85-264VAC)
- Built-in inrush current, overcurrent and overvoltage protection circuits

## Safety agency approvals

- UL62368-1, C-UL (equivalent to CAN/CSA-C22.2 No.62368-1), EN62368-1
- Complies with DEN-AN

## 5-year warranty (refer to Instruction Manual)

## CE marking

- Low Voltage Directive
- RoHS Directive

## UKCA marking

- Electrical Equipment Safety Regulations
- RoHS Regulations

## EMI


- Complies with CISPR11-B, CISPR32-B, EN55011-B, EN55032-B, FCC Part 15-B, FCC Part 18-B, VCCI-B

## EMS Compliance : EN61204-3, EN61000-6-2

- EN61000-4-2
- EN61000-4-3
- EN61000-4-4
- EN61000-4-5
- EN61000-4-6
- EN61000-4-8
- EN61000-4-11

# TEPS45F

TEP S 45 F □ □ - □  
 ① ② ③ ④ ⑤ ⑥



Example recommended EMI/EMC filter  
EAM-03-000



High voltage pulse noise type : EAP series 150KHz-1MHz (To safety ground the secondary side) : EAC serie

\*A higher current rating EMI/EMC filter may be recommended in view of the other devices that could be connected in parallel with the power supply.

- ① Series name
- ② Single output
- ③ Output wattage
- ④ Universal input
- ⑤ Output voltage
- ⑥ Optional \*1

□ ClassII

This power supply is manufactured by SMD technology. The stress to PCB like twisting or bending causes the defect of the unit, so handle the unit with care.  
 \*Make sure necessary tests will be carried out on your end equipment with the power supply installed in accordance with any required EMC/EMI regulations.


MODEL	TEPS45F05	TEPS45F12	TEPS45F24
MAX OUTPUT WATTAGE[W]	40.0	45.6	45.6
DC OUTPUT	5V 8.0A	12V 3.8A	24V 1.9A

## SPECIFICATIONS

	MODEL	TEPS45F05	TEPS45F12	TEPS45F24	
INPUT	VOLTAGE [VAC]	85 - 264 1 φ (Refer to "Derating" and Instruction Manual 3.1)			
	CURRENT [A]	ACIN 100V	0.80typ	0.90typ	
		ACIN 230V	0.45typ	0.50typ	
	FREQUENCY [Hz]	50 / 60 (45 - 66)			
	EFFICIENCY [%]	ACIN 100V	90.0typ	90.5typ	91.5typ
		ACIN 230V	90.5typ	91.5typ	92.5typ
	INRUSH CURRENT [A]	ACIN 100V	30typ (I <sub>o</sub> =100%) Ta=25°C at cold start		
ACIN 230V		65typ (I <sub>o</sub> =100%) Ta=25°C at cold start			
LEAKAGE CURRENT[mA]	0.25max (ACIN 240V, 60Hz, I <sub>o</sub> =100%, According to IEC62368-1, and DEN-AN)				
OUTPUT	VOLTAGE [V]	5	12	24	
	CURRENT [A]	8.0	3.8	1.9	
	LINE REGULATION [mV]	20max	48max	96max	
	LOAD REGULATION [mV]	40max	100max	150max	
	RIPPLE[mVp-p]	240max	300max	360max	
	RIPPLE NOISE[mVp-p]	300max	380max	480max	
	TEMPERATURE REGULATION [mV]	0 to +50°C	50max	120max	240max
		-10 to +50°C	60max	150max	290max
	DRIFT [mV]	20max	48max	96max	
	START-UP TIME [ms]	200typ (ACIN 100V, I <sub>o</sub> =100%)			
	HOLD-UP TIME [ms]	10typ (ACIN 100V, I <sub>o</sub> =80%) / 60typ (ACIN 230V, I <sub>o</sub> =100%)			
	OUTPUT VOLTAGE SETTING [V]	4.90 to 5.30	11.50 to 12.50	23.00 to 25.00	
	PROTECTION CIRCUIT AND OTHERS	OVERCURRENT PROTECTION	Works over 105% of rating and recovers automatically		
OVERVOLTAGE PROTECTION [V]		5.50 to 6.50	13.20 to 15.60	26.40 to 31.20	
OPERATING INDICATION		Not provided			
REMOTE SENSING		Not provided			
ISOLATION	INPUT-OUTPUT	3,000VAC 1minute, Cutoff current = 10mA, 500VDC 50MΩ min (At Room Temperature)			
ENVIRONMENT	OPERATING TEMP., HUMID. AND ALTITUDE	-10 to +70°C, 20 - 90%RH (Non condensing), (Refer to "Derating"), 5,000m (16,500feet) max			
	STORAGE TEMP., HUMID. AND ALTITUDE	-20 to +75°C, 20 - 90%RH (Non condensing), 9,000m (30,000feet) max			
	VIBRATION	10 - 55Hz 19.6m/s <sup>2</sup> (2G), 3minutes period, 60minutes each along X, Y and Z axis			
	IMPACT	196.1m/s <sup>2</sup> (20G), 11ms, once each X, Y and Z axis			
SAFETY AND NOISE REGULATIONS	AGENCY APPROVALS	UL62368-1, C-UL(equivalent to CAN/CSA-C22.2 No.62368-1), EN62368-1, Complies with DEN-AN			
	CONDUCTED NOISE	Complies with CISPR11-B, CISPR32-B, EN55011-B, EN55032-B, FCC Part 15-B, FCC Part 18-B, VCCI-B			
	HARMONIC ATTENUATOR	Complies with EN61000-3-2 (Class A) (No built-in power factor correction)			
OTHERS	CASE SIZE/WEIGHT	25.4 X 24.0 X 58.5mm [1.00 X 0.94 X 2.30 inches] (W X H X D) / 60g max			
	COOLING METHOD	Convection/Forced air (Requires external fan)(Refer to "Derating")			

- \*1 The listed options may affect the published standard specifications. Please contact us for detailed product specifications.
- \*2 Derating is required.
- \*3 At low load conditions, the burst mode operation will start. To check load regulation, you will need to measure the characteristics at average mode with instruments.
- \*4 This is the value that measured on measuring board with capacitor of 22μF and 0.1μF at 50mm from output terminal. (Refer to Instruction Manual)
- \*5 5V, 12V output product, the maximum temperature of 40°C.
- \*6 Drift is the change in DC output for an eight hour period after a half-hour warm-up at 25°C, with the input voltage held constant at the rated input/output.
- \*7 When secondary circuit will be connected to earth, the spec will be changed. (Refer to Instruction Manual 2)
- \*8 Please contact us about another class. When two or more units are operating it may not comply with the IEC61000-3-2. Please contact us for details.
- \* To meet the specification, do not operate overload condition.
- \* Parallel operation is not possible.
- \* Sound noise may be emitted from the power supply depending on operating conditions.

## External view




- ※ Dimensions in mm, [ ]=inches
- ※ Tolerance : ±1.5 [±0.06]
- ※ Weight : 60g max
- ※ PCB Material / thickness : FR-4 / 1.1 [0.04]
- ※ Pin material : Copper
- ※ Plating treatment of pin : Lead free plating

# TEPS65F

TEP S 65 F   -

① ② ③ ④ ⑤ ⑥



Example recommended EMI/EMC filter  
EAM-03-000



High voltage pulse noise type : EAP series  
150KHz-1MHz (To safety ground the secondary  
side) : EAC serie

\*A higher current rating EMI/EMC filter  
may be recommended in view of the  
other devices that could be connected  
in parallel with the power supply.

- ① Series name
- ② Single output
- ③ Output wattage
- ④ Universal input
- ⑤ Output voltage
- ⑥ Optional \*1

ClassII

This power supply is manufactured by SMD technology. The stress to PCB like twisting or bending causes the defect of the unit, so handle the unit with care.  
\*Make sure necessary tests will be carried out on your end equipment with the power supply installed in accordance with any required EMC/EMI regulations.


MODEL	TEPS65F05	TEPS65F12	TEPS65F24
MAX OUTPUT WATTAGE [W]	*2 50.0	65.4	66.0
DC OUTPUT	*2 5V 10.0A	12V 5.45A	24V 2.75A

## SPECIFICATIONS

	MODEL	TEPS65F05	TEPS65F12	TEPS65F24	
INPUT	VOLTAGE [VAC]	*2 85 - 264 1 φ (Refer to "Derating" and Instruction Manual 3.1)			
	CURRENT [A]	ACIN 100V	1.00typ	1.25typ	
		ACIN 230V	0.55typ	0.70typ	
	FREQUENCY [Hz]	50 / 60 (45 - 66)			
	EFFICIENCY [%]	ACIN 100V	90.0typ	91.5typ	92.5typ
		ACIN 230V	91.5typ	93.0typ	93.5typ
	INRUSH CURRENT [A]	ACIN 100V	30typ (Io=100%) Ta=25°C at cold start		
ACIN 230V		65typ (Io=100%) Ta=25°C at cold start			
LEAKAGE CURRENT [mA]	0.25max (ACIN 240V, 60Hz, Io=100%, According to IEC62368-1, and DEN-AN)				
OUTPUT	VOLTAGE [V]	5	12	24	
	CURRENT [A]	*2 10.0	5.45	2.75	
	LINE REGULATION [mV]	*3 20max	48max	96max	
	LOAD REGULATION [mV]	*3 40max	100max	150max	
	RIPPLE[mVp-p]	*4 -10 to +50°C *5 240max	300max	360max	
	RIPPLE NOISE[mVp-p]	*4 -10 to +50°C *5 300max	380max	480max	
	TEMPERATURE REGULATION [mV]	0 to +50°C *5 50max	120max	240max	
		-10 to +50°C *5 60max	150max	290max	
	DRIFT [mV]	*6 20max	48max	96max	
	START-UP TIME [ms]	500typ (ACIN 100V, Io=100%)			
	HOLD-UP TIME [ms]	10typ (ACIN 100V, Io=80%) / 60typ (ACIN 230V, Io=100%)			
	OUTPUT VOLTAGE SETTING [V]	4.90 to 5.30	11.50 to 12.50	23.00 to 25.00	
	PROTECTION CIRCUIT AND OTHERS	OVERCURRENT PROTECTION	Works over 105% of rating and recovers automatically		
OVERVOLTAGE PROTECTION [V]		5.50 to 6.50	13.20 to 15.60	26.40 to 31.20	
OPERATING INDICATION		Not provided			
REMOTE SENSING		Not provided			
ISOLATION	INPUT-OUTPUT	3,000VAC 1minute, Cutoff current = 10mA, 500VDC 50MΩ min (At Room Temperature)			
ENVIRONMENT	OPERATING TEMP., HUMID. AND ALTITUDE *2	-10 to +70°C, 20 - 90%RH (Non condensing), (Refer to "Derating"), 5,000m (16,500feet) max			
	STORAGE TEMP., HUMID. AND ALTITUDE	-20 to +75°C, 20 - 90%RH (Non condensing), 9,000m (30,000feet) max			
	VIBRATION	10 - 55Hz 19.6m/s <sup>2</sup> (2G), 3minutes period, 60minutes each along X, Y and Z axis			
	IMPACT	196.1m/s <sup>2</sup> (20G), 11ms, once each X, Y and Z axis			
SAFETY AND NOISE REGULATIONS	AGENCY APPROVALS	UL62368-1, C-UL (equivalent to CAN/CSA-C22.2 No.62368-1), EN62368-1, Complies with DEN-AN			
	CONDUCTED NOISE *7	Complies with CISPR11-B, CISPR32-B, EN55011-B, EN55032-B, FCC Part 15-B, FCC Part 18-B, VCCI-B			
	HARMONIC ATTENUATOR *8	Complies with EN61000-3-2 (Class A) (No built-in power factor correction)			
OTHERS	CASE SIZE/WEIGHT	25.4 X 27.5 X 58.5mm [1.00 X 1.08 X 2.30 inches] (W X H X D) / 70g max			
	COOLING METHOD *2	Convection/Forced air (Requires external fan) (Refer to "Derating")			

- \*1 The listed options may affect the published standard specifications. Please contact us for detailed product specifications.
- \*2 Derating is required.
- \*3 At low load conditions, the burst mode operation will start. To check load regulation, you will need to measure the characteristics at average mode with instruments.
- \*4 This is the value that measured on measuring board with capacitor of 22μF and 0.1μF at 50mm from output terminal.(Refer to Instruction Manual)
- \*5 12V output product, the maximum temperature of 45°C.
- \*6 Drift is the change in DC output for an eight hour period after a half-hour warm-up at 25°C, with the input voltage held constant at the rated input/output.
- \*7 When secondary circuit will be connected to earth, the spec will be changed. (Refer to Instruction Manual 2)
- \*8 Please contact us about another class. When two or more units are operating it may not comply with the IEC61000-3-2. Please contact us for details.
- \* To meet the specification, do not operate overload condition.
- \* Parallel operation is not possible.
- \* Sound noise may be emitted from the power supply depending on operating conditions.


## External view



- ※ Dimensions in mm, [ ]=inches
- ※ Tolerance : ± 1.5 [± 0.06]
- ※ Weight : 70g max
- ※ PCB Material / thickness : FR-4 / 1.1 [0.04]
- ※ Pin material : Copper
- ※ Plating treatment of pin : Lead free plating

## Pin Configuration

### ●TEPS45F/TEPS65F




No.	Pin connection	Function
①	AC (L)	AC input
②	AC (N)	
③	+Vout	+DC output
④	-Vout	-DC output



## Implementation • Mounting Method

### Mounting method

- When two or more power supplies are used side by side, position them with proper intervals to allow enough air ventilation. The temperature around each power supply should not exceed the temperature range shown in derating curve.
- It can be mounted in the mounting position shown in the figure below.



- Avoid placing the AC input line pattern layout underneath the unit. It will increase the line conducted noise. Make sure to leave an ample distance between the line pattern layout and the unit. Also avoid placing the DC output line pattern underneath the unit because it may increase the output noise. Lay out the pattern away from the unit.
- When installing the components (inclusive chassis) or pattern which is a foreign potentials around the unit, keep the distance for more than 5mm.




- Do not touch any SMD components on the unit and soldering points.

### Soldering

- Flow soldering: 260°C for up to 15 seconds.
- Soldering iron (26W): 450°C for up to 5 seconds.


### Stress to the pins

- Applying excessive stress to the input or output pins of the power module may damage internal connections. Avoid applying stress in excess of that shown in right figure.
- Input/output pin are soldered to the PCB internally. Do not pull or bend a lead powerfully.
- If it is expected that stress is applied to the input/output pin due to vibration or impact, reduce the stress to the pin by taking such measures as fixing the unit to the PCB by silicone rubber, etc.




Derating

● Derating curve for input voltage



● TEPS45F Ambient temperature derating curve at rated input (Reference value)




Cooling method	Output voltage	Mounting method	
		A, B, C, D, E, F	
Convection	5V	①	
	12V	①	
	24V	②	
Forced air (0.5m <sup>3</sup> /min)	5V, 12V, 24V	③	

■As example, these derating curves have been decided at the below PCB condition.

- FR-4 (Double-sided)
- 203.2mm×76.2mm×1.6mm
- Copper foil thickness : 70μm

● TEPS65F Ambient temperature derating curve at rated input (Reference value)



Cooling method	Output voltage	Mounting method		
		A, B, C, E	D	F
Convection	5V	③	③	②
	12V	②	①	①
	24V	④	②	②
Forced air (0.5m <sup>3</sup> /min)	5V, 12V, 24V	⑤		

■As example, these derating curves have been decided at the below PCB condition.

- FR-4 (Double-sided)
- 203.2mm×76.2mm×1.6mm
- Copper foil thickness : 70μm

Instruction Manual

◆ Please see catalog and instructionmanual before you use.

Instruction Manual <https://www.cosel.co.jp/redirect/catalog/en/TEPS/>  
 Before using our product <https://en.cosel.co.jp/technical/caution/index.html>

TEPS



NOTICE



Basic Characteristics Data

Model	Circuit method	Switching frequency [kHz]	Input current *1 [A]	Inrush current protection	PCB/Pattern			Series/Parallel operation availability	
					Material	Single sided	Double sided	Series operation	Parallel operation
TEPS45F	Flyback converter	20 to 250	0.9	Thermistor	FR-4		Yes	Yes	No
TEPS65F	Flyback converter	20 to 800	1.25	Thermistor	FR-4		Multilayer	Yes	No

\*1 The value of input current is at ACIN 100V and rated load.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Switching Power Supplies](#) category:*

*Click to view products by [Cosel](#) manufacturer:*

Other Similar products are found below :

[70841011](#) [73-551-0005](#) [73-551-0048](#) [EVS57-5R3/A](#) [AAD600S-4-OP](#) [MS924](#) [HWS50A-5/RA](#) [KD0204](#) [LDIN100150](#) [FP80](#) [FRV7000G](#)  
[22929](#) [PS3E-F12F](#) [CQM1IA121](#) [VI-PU22-EXX](#) [LDIN5075](#) [432703037161](#) [09-160CFG](#) [LPM000-BBAR-08](#) [LPM000-BBAR-07](#) [08-30466-](#)  
[1055G](#) [DMB-EWG](#) [CQM1IPS01](#) [SP-300-5](#) [CQM1-IPS02](#) [VI-MUL-ES](#) [22829](#) [08-30466-0028G](#) [09-250CFG](#) [CA400](#) [H47251](#) [96PSR-](#)  
[A460WOTH-2](#) [VP-E2935648E](#) [G08-L](#) [G06-Q01](#) [GHA300F-12-SNF](#) [MTA040009A](#) [FSA150024A](#) [VI-RUR22-EWXX](#) [VI-PU03-EYW](#)  
[PM1-03B-48-2](#) [VI-LUF-EW](#) [VI-QCWB3-CSV](#) [HLS30ZE-NT8](#) [UT1404-7](#) [ERP-350-12](#) [S8FSG01512C](#) [S8FSG03012C](#) [VI-PU22-EYY](#)  
[XPFM201A+](#) [S8FS-G15015C](#)