

MATERIAL SAFETY DATA SHEET

Product Name 5.56 AEROSOL

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Supplier Name	CRC INDUSTRIES (AUST) PTY LIMITED
Address	9 Gladstone Road, Castle Hill, NSW, AUSTRALIA, 2154
Telephone	(02) 9634 2088
Fax	(02) 9680 4914
Emergency	(02) 9634 2088
Email	info@crcind.com.au
Web Site	http://www.crcind.com.au/
Synonym(s)	5.56 (AEROSOL) • 5005 - PRODUCT CODE • 5027 - PRODUCT CODE • 5028 - PRODUCT CODE • CRC 5-56 (AEROSOL) (FORMERLY) • CRC 5.56 AEROSOL
Use(s)	LUBRICANT • PENETRANT
SDS Date	01 Apr 2010

2. HAZARDS IDENTIFICATION

CLASSIFIED AS HAZARDOUS ACCORDING TO ASCC CRITERIA

RISK PHRASES

R11	Highly flammable.							
R65	Harmful: May cause lung	Harmful: May cause lung damage if swallowed.						
SAFETY PHRASE	S							
S16	Keep away from sources	s of ignition - No sn	noking.					
S23	Do not breathe gas/fume	es/vapour/spray (w	here applicable).					
S24	Avoid contact with skin.							
S45	In case of accident or if you feel unwell seek medical advice immediately (show the label where possible).							
S53	Avoid exposure - obtain special instructions before use.							
S62	If swallowed, do not indu	uce vomiting; seek	medical advice immediat	ely and show this con	tainer or label.			
CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE								
UN No.	1950	DG Class	2.1	Subsidiary Risk(s)	None Allocated			
Packing Group	None Allocated	Hazchem Code	2Y	EPG	2D1			

3. COMPOSITION/ INFORMATION ON INGREDIENTS

Ingredient	Formula	CAS No.	Content
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	Not Available	64742-47-8	>60%
LIQUEFIED PETROLEUM GAS (LPG)	C3H8/C3H6/C4H10	68476-85-7	10-30%
MINERAL OIL (SOLVENT REFINED)	Not Available	Not Available	10-30%
CORROSION INHIBITOR(S)	Not Available	Not Available	<10%



Page 1 of 5 RMT Reviewed: 01 Apr 2010 Printed: 13 Apr 2010

4. FIRST AID MEASURES

Еуе	If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor, or for at least 15 minutes.
Inhalation	If inhaled, remove from contaminated area. To protect rescuer, use a Type A (Organic vapour) respirator or an Air- line respirator (in poorly ventilated areas). Apply artificial respiration if not breathing.
Skin	If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor.
Ingestion	For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting. Ingestion is considered unlikely due to product form.
Advice to Doctor	Treat symptomatically

5. FIRE FIGHTING MEASURES

Flammability Highly flammable. May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition. Vapour may form explosive mixtures with air. Eliminate all ignition sources, including cigarettes, open flames, spark producing switches/tools, heaters, pilot lights, mobile phones etc. when handling. Aerosol cans may explode above 50°C.

Fire andEvacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind
and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing
Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

Extinguishing Dry agent, carbon dioxide or foam. Prevent contamination of drains or waterways.

Hazchem Code 2Y

6. ACCIDENTAL RELEASE MEASURES

Spillage If cans/containers are punctured (bulk), use personal protective equipment. Clear area of all unprotected personnel. Ventilate area where possible. Collect and allow to discharge outdoors. Contain spillage, then cover / absorb spill with non-combustible absorbant material (vermiculite, sand, or similar), collect and place in suitable containers for disposal.

7. STORAGE AND HANDLING

Storage Store in a cool (< 50°C), dry, well ventilated area, removed from oxidising agents, acids, alkalis, heat or ignition sources and foodstuffs. Ensure aerosol containers/ cans are adequately labelled, protected from physical damage and sealed when not in use. Check regularly for damaged/ leaking containers. Large storage areas should have appropriate fire protection systems.

Handling Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

Exposure Stds	Ingradiant	Poforonao	TWA		STEL	
	Ingredient	Reference	ppm	mg/m3	ppm	mg/m3
	Mineral Oil Mist	ASCC (AUS)		5		
	LIQUEFIED PETROLEUM GAS (LPG)	ASCC (AUS)	1000	1800	1000	1800
	Mineral Oil Mist	ASCC (AUS)		5		

Biological Limits No biological limit allocated.





Product Name 5.56 AEROSOL

Engineering

Controls

Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical explosion proof extraction ventilation is recommended. Flammable vapours may accumulate in poorly ventilated or confined areas. Vapours are heavier than air and may travel some distance to an ignition source and flash back. Maintain vapour levels below the recommended exposure standard.

PPE

Wear splash-proof goggles and neoprene or nitrile gloves. At high vapour levels, wear: a Type A-Class P1 (Organic gases/vapours and Particulate) respirator.



S-{

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	AMBER LIQUID (AEROSOL DISPENSED)	Solubility (Water)	INSOLUBLE
Odour	PLEASANT ODOUR	Specific Gravity	0.81
рН	NOT AVAILABLE	% Volatiles	82 %
Vapour Pressure	0.23 mm Hg	Flammability	HIGHLY FLAMMABLE
Vapour Density	> 1 (Air = 1)	Flash Point	< 0°C (Propellant)
Boiling Point	193°C (Initial)	Upper Explosion Limit	12 %
Melting Point	NOT AVAILABLE	Lower Explosion Limit	1.4 %
Evaporation Rate	NOT AVAILABLE		
Autoignition Temperature	550°C		

10. STABILITY AND REACTIVITY

Chemical Stability	Stable under recommended conditions of storage.
Conditions to Avoid	Avoid heat, sparks, open flames and other ignition sources.
Material to Avoid	Incompatible with oxidising agents (eg. hypochlorites), acids (eg. nitric acid), alkalis (eg. hydroxides), heat and ignition sources.
Decomposition	May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition.
Hazardous Reactions	Polymerization is not expected to occur.

11. TOXICOLOGICAL INFORMATION

Toxicity Data	No LD50 data available for this product.
Ingestion	Low to moderate toxicity. Ingestion may result in nausea, vomiting, abdominal pain and drowsiness with large quantities. Aspiration may result in chemical pneumonitis and pulmonary oedema. Ingestion is considered unlikely due to product form.
Skin	Irritant. Contact may result in drying and defatting of the skin, rash and dermatitis.
Inhalation	Irritant. Over exposure may result in irritation of the nose and throat, coughing and headache. High level exposure may result in nausea, dizziness and drowsiness.
Eye	Irritant. Contact may result in irritation, lacrimation, pain and redness.
Health Hazard Summary	Low to moderate toxicity - irritant. This product may only have the potential to cause adverse health effects if intentionally misused (eg. deliberately inhaling contents). Over exposure may result in central nervous system (CNS) effects. Use safe work practices to avoid eye or skin contact and vapour generation - inhalation.

12. ECOLOGICAL INFORMATION

Environment Aliphatic hydrocarbons behave differently in the environment depending on their size. WATER: Light aliphatics volatilise rapidly from water (half life - few hours). Bioconcentration should not be significant. SOIL: Light aliphatics biodegrade quickly in soil and water, heavy aliphatics biodegrade very slowly. ATMOSPHERE: Vapour-phase aliphatics will degrade by reaction with hydroxyl radicals.



Page 3 of 5 RMT Reviewed: 01 Apr 2010 Printed: 13 Apr 2010

13. DISPOSAL CONSIDERATIONS

Waste Disposal For small amounts absorb contents with sand or similar and dispose of to an approved landfill site. Do not puncture or incinerate aerosol cans. Contact the manufacturer for additional information.
 Legislation Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION



CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

Shipping Name	AEROSOLS				
UN No.	1950	DG Class	2.1	Subsidiary Risk(s)	None Allocated
Packing Group	None Allocated	Hazchem Code	2Y	EPG	2D1

15. REGULATORY INFORMATION

Poison Schedule A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP).
 AICS All chemicals listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

Additional Information AEROSOL CANS may explode at temperatures approaching 50°C.

RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

ABBREVIATIONS: ADB - Air-Dry Basis. BEI - Biological Exposure Indice(s) CAS# - Chemical Abstract Service number - used to uniquely identify chemical compounds. CNS - Central Nervous System. EINECS - European INventory of Existing Commercial chemical Substances. IARC - International Agency for Research on Cancer. M - moles per litre, a unit of concentration. mg/m3 - Milligrams per cubic metre. NOS - Not Otherwise Specified. NTP - National Toxicology Program. OSHA - Occupational Safety and Health Administration. pH - relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline). ppm - Parts Per Million. RTECS - Registry of Toxic Effects of Chemical Substances. TWA/ES - Time Weighted Average or Exposure Standard. HEALTH EFFECTS FROM EXPOSURE: It should be noted that the effects from exposure to this product will depend on several factors including: frequency

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a Chem Alert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES: The recommendation for protective equipment contained within this Chem Alert report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

Report Status This document has been compiled by RMT on behalf of the manufacturer of the product and serves as the manufacturer's Safety Data Sheet ('SDS').



Page 4 of 5 RMT Reviewed: 01 Apr 2010 Printed: 13 Apr 2010 It is based on information concerning the product which has been provided to RMT by the manufacturer or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

Prepared By Risk Management Technologies 5 Ventnor Ave, West Perth Western Australia 6005 Phone: +61 8 9322 1711 Fax: +61 8 9322 1794 Email: info@rmt.com.au Web: www.rmt.com.au

> SDS Date: 01 Apr 2010 End of Report

ChemAlert.

Page 5 of 5 RMT Reviewed: 01 Apr 2010 Printed: 13 Apr 2010

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for CRC manufacturer:

Other Similar products are found below :

 20581
 32722
 FS7110
 102553161231
 20584
 30463
 100364071242
 30589-001
 12006-002
 33164
 30344-003
 100364011242
 101513161231

 GX3045
 100364001242
 100364081242
 32168
 GX4097C
 AC6028
 10690-009
 FC6069
 100364041242
 100364051242
 100043911231

 RS5025
 GY4007
 GX4218C
 YX4314
 GY4004
 AC5019
 GX4115C
 GX4125C
 GX4128J
 GX4212C
 GX4228
 GX5051J
 GX5064C

 YX4411C
 YX5011J
 YX5075C
 GX4223C
 HA4002
 HA4037
 HS5044
 AC5030
 GY3005
 GX4100C
 YX4278J
 HS5005