

GH1213 12 volt 1.3 Ah

GH1213 is a general purpose battery with 3-5 years in standby service or more than 400 cycles at 50% depth of discharge in cycle service.


☆ SPECIFICATION

NOMINAL VOLTAGE	: 12 V	
 NOMINAL CAPACITY(20 hr) 	: 1.3 Ah	
DIMENSIONS		
TOTAL HEIGHT	: 59 mm (2.32 inches)	
CONTAINER HEIGHT	: 52 mm (2.05 inches)	
LENGTH	: 97 mm (3.82 inches)	
WIDTH	: 43 mm (1.69 inches)	
• WEIGHT	: APPROX 0.58 Kg (1.28 lbs)	
CONTAINER MATERIAL	: UL94HBABS	
	: UL94V-0 ABS	
● INTERNAL RESISTANCE(25°C , 77 °F) : ~80mΩ		
DISCHARGE CAPACITY UN	DER DIFFERENT TEMPERATURES	
40°C	:~102%	
25°C	:~100%	
0 °C	:~85%	


☆CHARACTERISTICS

• CAPACITY 25 °C / 77 °F		
20 hr @ 0.065 A	:1.3 Ah	
5 hr @ 0.208 A	: 1.04 Ah	
1 hr @ 0.78 A	:0.78 Ah	
1 C @ 1.3 A	:0.65 Ah	
CHARGING VOLTAGE (25°C , 77	′°F)	
STANDBY USE	:13.65∨±0.15∨	
CYCLE USE	: 14.7 V±0.3V	
MAX DISCHARGE CURRENT	: 20 A (5 sec)	
 MAX CHARGING CURRENT 	: 0.39 A	
 SELF-DISCHARGE RESIDUAL C 	APACITY	
AFTER 3 MONTHS	:~90%	
AFTER 6 MONTHS	:~82%	
AFTER 12 MONTHS	:~70%	


☆ Discharge Current vs Time




Discharge Characteristics @25 °C (77 °F)



☆ Dimensions



☆ Terminal



CSB Battery Technologies, Inc. 3900 Highway 377 South, Suite 101, Fort Worth, Texas 76116 Tel: (817) 244-7777 Fax (817) 244-4445 Toll Free: (800) 327-2872 Email: <u>usasls@csb-battery.com</u> or latinsls@csb-battery.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Sealed Lead Acid Battery category:

Click to view products by CSB manufacturer:

Other Similar products are found below :

035021