



CT1010-W, CT1011-W, CT1012-W, CT1013-W, CT1014-W

CT1015-W, CT1016-W, CT1017-W, CT1018-W, CT1019-W

DC Input 4-Pin Long Mini-Flat Phototransistor Optocoupler

Features

- High isolation 5000 VRMS
- CTR flexibility available see order information
- Extra low coupling capacitance
- DC input with transistor output
- Temperature range - 55 °C to 125 °C
- External creepage distance > 8 mm
- Internal creepage distance > 4.6 mm
- Distances through insulation > 0.4 mm
- Green Package
- Regulatory Approvals
 - UL - UL1577 (E364000)
 - VDE - EN60747-5-5(VDE0884-5)
 - CQC – GB4943.1, GB8898
 - IEC60065, IEC60950


Applications

- Switch mode power supplies
- Computer peripheral interface
- Microprocessor system interface


Description

The CT1010-W, CT1011-W, CT1012-W, CT1013-W, CT1014-W, CT1015-W, CT1016-W, CT1017-W, CT1018-W, CT1019-W consists of a photo transistor optically coupled to a gallium arsenide Infrared-emitting diode in a 4-lead SOP Package.

Package Outline



Schematic





CT1010-W, CT1011-W, CT1012-W, CT1013-W, CT1014-W

CT1015-W, CT1016-W, CT1017-W, CT1018-W, CT1019-W

DC Input 4-Pin Long Mini-Flat Phototransistor Optocoupler

Absolute Maximum Rating at 25°C

Symbol	Parameters	Ratings	Units	Notes
V _{ISO}	Isolation voltage	5000	V _{RMS}	
T _{OPR}	Operating temperature	-55 ~ +125	°C	
T _{STG}	Storage temperature	-55 ~ +150	°C	
T _{SOL}	Soldering temperature	260	°C	

Emitter

I _F	Forward current	50	mA	
I _{F(TRANS)}	Peak transient current (≤1μs P.W,300pps)	1	A	
V _R	Reverse voltage	6	V	
P _D	Power dissipation	85	mW	

Detector

P _C	Power dissipation	150	mW	
B _{VCEO}	Collector-Emitter Breakdown Voltage	80	V	
B _{VECO}	Emitter-Collector Breakdown Voltage	7	V	
I _c	Collector Current	50	mA	

Thermal Characteristics

Symbol	Parameters	Ratings	Units	Notes
R _{θJA}	Thermal Resistance Junction-Ambient	445	°C/W	
T _J	Junction temperature	125	°C	



CT1010-W, CT1011-W, CT1012-W, CT1013-W, CT1014-W

CT1015-W, CT1016-W, CT1017-W, CT1018-W, CT1019-W

DC Input 4-Pin Long Mini-Flat Phototransistor Optocoupler

Electrical Characteristics $T_A = 25^\circ\text{C}$ (unless otherwise specified)

Emitter Characteristics

Symbol	Parameters	Test Conditions	Min	Typ	Max	Units	Notes
V_F	Forward voltage	$I_F=10\text{mA}$		1.26	1.4	V	
		$I_F=50\text{mA}$	-	1.42	1.5	V	
I_R	Reverse Current	$V_R = 6\text{V}$	-	-	5	μA	
C_{IN}	Input Capacitance	$f= 1\text{kHz}$	-	45	-	pF	

Detector Characteristics

Symbol	Parameters	Test Conditions	Min	Typ	Max	Units	Notes
B_{VCEO}	Collector-Emitter Breakdown	$I_C = 100\mu\text{A}$	80	-	-	V	
B_{VECO}	Emitter-Collector Breakdown	$I_E = 100\mu\text{A}$	7	-	-	V	
I_{CEO}	Collector-Emitter Dark Current	$V_{CE}= 20\text{V}, I_F= 0\text{mA}$	-	-	100	nA	

Transfer Characteristics

Symbol	Parameters	Test Conditions	Min	Typ	Max	Units	Notes
CTR	Current Transfer Ratio	CT1012-W CT1013-W CT1014-W	$I_F= 1\text{mA}, V_{CE}= 5\text{V}$	22	-	-	%
				34	-	-	
				56	-	-	
		CT1011-W CT1012-W CT1013-W CT1014-W	$I_F= 10\text{mA}, V_{CE}= 5\text{V}$	60	-	300	
				63	-	125	
				100	-	200	
				160	-	320	
		CT1010-W CT1015-W CT1016-W CT1017-W CT1018-W CT1019-W	$I_F= 5\text{mA}, V_{CE}= 5\text{V}$	50	-	600	
				50	-	150	
				100	-	300	
				80	-	160	
				130	-	260	
				200	-	400	
$V_{CE(SAT)}$	Collector-Emitter Saturation Voltage	$I_F= 10\text{mA}, I_C= 1\text{mA}$	-	-	0.4	V	
R_{IO}	Isolation Resistance	$V_{IO}= 500\text{V}_{\text{DC}}$	5×10^{10}			Ω	
C_{IO}	Isolation Capacitance	$f= 1\text{MHz}$			1	pF	



CT1010-W, CT1011-W, CT1012-W, CT1013-W, CT1014-W

CT1015-W, CT1016-W, CT1017-W, CT1018-W, CT1019-W

DC Input 4-Pin Long Mini-Flat Phototransistor Optocoupler

Electrical Characteristics $T_A = 25^\circ\text{C}$, $V_{CC} = 5\text{V}$ (unless otherwise specified)

Switching Characteristics

Symbol	Parameters	Test Conditions	Min	Typ	Max	Units	Notes
T_{ON}	Turn On Time	$I_C = 5\text{mA}$, $V_{CE} = 5\text{V}$, $R_L = 100\Omega$	-	4.8	22	μs	
T_{OFF}	Turn Off Time		-	4.2	22		
t_r	Rise Time		-	2.7	18		
t_f	Fall Time		-	4	18		



CT1010-W, CT1011-W, CT1012-W, CT1013-W, CT1014-W

CT1015-W, CT1016-W, CT1017-W, CT1018-W, CT1019-W

DC Input 4-Pin Long Mini-Flat Phototransistor Optocoupler

Typical Characteristic Curves

Forward Current vs. Forward Voltage




Figure 1

Collector Dark Current vs. Ambient Temperature




Figure 4

Normalized CTR vs. Forward Current




Figure 3

Collector Current vs. Ambient Temperature




Figure 4

Normalized CTR vs. Ambient Temperature




Figure 5

Collector-Emitter Saturation Voltage vs. Collector Current




Figure 6



CT1010-W, CT1011-W, CT1012-W, CT1013-W, CT1014-W

CT1015-W, CT1016-W, CT1017-W, CT1018-W, CT1019-W

DC Input 4-Pin Long Mini-Flat Phototransistor Optocoupler




Figure 7




Figure 8




Figure 9




Figure 10




CT1010-W, CT1011-W, CT1012-W, CT1013-W, CT1014-W


CT1015-W, CT1016-W, CT1017-W, CT1018-W, CT1019-W

DC Input 4-Pin Long Mini-Flat Phototransistor Optocoupler

Package Dimension Dimensions in mm unless otherwise stated



Recommended Solder Mask Dimensions in mm unless otherwise stated





CT1010-W, CT1011-W, CT1012-W, CT1013-W, CT1014-W

CT1015-W, CT1016-W, CT1017-W, CT1018-W, CT1019-W

DC Input 4-Pin Long Mini-Flat Phototransistor Optocoupler

Marking Information



Note:

- CT : Denotes "CT Micro"
1019 : Part Number
Y : Fiscal Year
V : VDE safety mark (option)
WW : Work Week
K : Manufacturing Code

Ordering Information

CT101X(V)(Y) -W

X = Part No. (0,1,2,3,4,5,6,7,8,9)

V = VDE safety mark option (V or none)

Y = Tape and reel option (T1 or T2)

W = Outline Color (W, White)

Option	Description	Quantity
T1	Surface Mount Lead Forming – With Option 1 Taping	3000Units/Reel
T2	Surface Mount Lead Forming – With Option 2 Taping	3000Units/Reel




CT1010-W, CT1011-W, CT1012-W, CT1013-W, CT1014-W

CT1015-W, CT1016-W, CT1017-W, CT1018-W, CT1019-W


DC Input 4-Pin Long Mini-Flat Phototransistor Optocoupler

Carrier Tape Specifications Dimensions in mm unless otherwise stated

Option T1



Option T2





CT1010-W, CT1011-W, CT1012-W, CT1013-W, CT1014-W

CT1015-W, CT1016-W, CT1017-W, CT1018-W, CT1019-W

DC Input 4-Pin Long Mini-Flat Phototransistor Optocoupler

Wave soldering (JEDEC22A111 compliant)


One time soldering is recommended within the condition of temperature.

Temperature: 260+0/-5°C.

Time: 10 sec.

Preheat temperature: 25 to 140°C.

Preheat time: 30 to 80 sec.



Hand soldering by soldering iron

Allow single lead soldering in every single process.

One time soldering is recommended. Temperature: 350+0/-5°C

Time: 3 sec max.




CT1010-W, CT1011-W, CT1012-W, CT1013-W, CT1014-W

CT1015-W, CT1016-W, CT1017-W, CT1018-W, CT1019-W

DC Input 4-Pin Long Mini-Flat Phototransistor Optocoupler

Reflow Profile



Profile Feature	Pb-Free Assembly Profile
Temperature Min. (T _{smin})	150°C
Temperature Max. (T _{smax})	200°C
Time (t _s) from (T _{smin} to T _{smax})	60-120 seconds
Ramp-up Rate (t _L to t _P)	3°C/second max.
Liquidous Temperature (T _L)	217°C
Time (t _L) Maintained Above (T _L)	60 – 150 seconds
Peak Body Package Temperature	260°C +0°C / -5°C
Time (t _P) within 5°C of 260°C	30 seconds
Ramp-down Rate (T _P to T _L)	6°C/second max
Time 25°C to Peak Temperature	8 minutes max.



CT1010-W, CT1011-W, CT1012-W, CT1013-W, CT1014-W

CT1015-W, CT1016-W, CT1017-W, CT1018-W, CT1019-W

DC Input 4-Pin Long Mini-Flat Phototransistor Optocoupler

DISCLAIMER

CT MICRO RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. CT MICRO DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

CT MICRO ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT EXPRESS WRITTEN APPROVAL OF CT MICRO INTERNATIONAL CORPORATION.

1. *Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instruction for use provided in the labelling, can be reasonably expected to result in significant injury to the user.*
2. *A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.*

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [High Speed Optocouplers](#) category:

Click to view products by [CT Micro International](#) manufacturer:

Other Similar products are found below :

[6N136F](#) [HCPL-2201-300](#) [JAN4N24](#) [610737H](#) [HCPL2630M](#) [HCPL2630SM](#) [PS9817A-1-F3-AX](#) [PS9821-2-F3-AX](#) [TLP2766A\(E\)](#)
[TLP2766A\(LF4,E](#) [PS9121-F3-AX](#) [TLP5774H\(TP4,E](#) [TLP5771H\(TP,E](#) [TLP2304\(E\(O](#) [054279X](#) [HCPL2631SD](#) [HCPL-2730-500E](#)
[TLP118\(TPL,E](#) [TLP2309\(E\(T](#) [TLP2366\(TPL,E](#) [TLP521-2XGB](#) [TLP621-2XGB](#) [JANTXV4N24U](#) [8102802PC](#) [5962-8767902XA](#) [5962-](#)
[8876801XA](#) [5962-8957101PA](#) [SFH6318T](#) [6N135-300E](#) [TIL198](#) [TLP104\(TPR,E\)](#) [TLP2309\(TPL,E\)](#) [TLP2355\(TPL,E](#) [TLP2358\(E\)](#) [TLP521-](#)
[4GR](#) [TLP521-4XGB](#) [TLP621XSM](#) [5962-8876801PA](#) [IS281-4GB](#) [IS2805-4](#) [IS181GR](#) [ICPL2630](#) [ICPL2531](#) [ICPL2601](#) [ICPL2530](#) [5962-](#)
[8876801PC](#) [TLP2301](#) [TLP2301\(E\(T](#) [TLP2362\(TPR,E](#) [TLP754\(F\)](#)