CUI DEVICES

date 04/21/2020

page 1 of 3

SERIES: TBL009V-254 | **DESCRIPTION:** TERMINAL BL0CK

FEATURES

- 2~24 poles
- · vertical with board
- interlocking (side)
- push button clamp
- 2.54 mm pitch
- UL safety approval
- IEC 60947-7-4 compliant
















SPECIFICATIONS

parameter	conditions/description	min	typ	max	units
rated voltage (nor contact)	UL			150	V
rated voltage (per contact)	IEC			160	V
rated current (per contact)	UL			5	Α
	IEC			6	Α
withstanding voltage	for 1 minute		1300		Vac
surge voltage				2500	V
contact resistance				20	mΩ
insulation resistance	at 500 Vdc	500			МΩ
operating temperature		-40		105	°C
safety approvals	UL 1059 certified, IEC 60947-7-4 compliant				
flammability rating	UL94V-0				·
RoHS	yes				

SOLDERABILITY

parameter	conditions/description	min	typ	max	units
wave soldering	for maximum 5 seconds		250		°C

PART NUMBER KEY




^{*}Standard housing color is gray with gray push button. All other colors are subject to higher MOQ. Please inquire with CUI Devices sales for details.


MECHANICAL DRAWING


units: mm tolerance:


 $X \le 6.00$: ± 0.20 mm $6.00 < X \le 10.00$: ± 0.30 mm $10.00 < X \le 30.00$: ± 0.50 mm $30.00 < X \le 60.00$: ± 0.70 mm $60.00 < X \le 100.00$: ± 1.00 mm $100.00 < X \le 160.00$: ± 1.30 mm X > 160.00: ± 1.60 mm unless otherwise noted

DESCRIPTION	MATERIAL	PLATING/COLOR
housing	PA66 (UL94V-0)	
contacts	copper alloy	tin









WIRE ASSEMBLY						
UL IEC						
Wire Range	26~18 AWG	0.5~ 1.0 mm²				
Strip Length	11 mm					

P.C.B. LAYOUT

Т	This series is constructed of 1 pole modules where L is the total length, P is the pitch, and N is the number of poles.											
N	02	03	04	05	06	07	08	09	10	11	12	13
L	6.58	9.12	11.66	14.20	16.74	19.28	21.82	24.36	26.90	29.44	31.98	34.52
В	2.54	5.08	7.62	10.16	12.70	15.24	17.78	20.32	22.86	25.40	27.94	30.48
N	14	15	16	17	18	19	20	21	22	23	24	
L	37.06	39.60	42.14	44.68	47.22	49.76	52.30	54.84	57.38	59.92	62.46	
В	33.02	35.56	38.10	40.64	43.18	45.72	48.26	50.80	53.34	55.88	58.42	

Additional Resources: Product Page | 3D Model | PCB Footprint

CUI Devices | SERIES: TBL009V-254 | DESCRIPTION: TERMINAL BL0CK date 04/21/2020 | page 3 of 3

REVISION HISTORY

rev.	description	date
1.0	initial release	08/13/2019
1.01	brand update	02/06/2020
1.02	updated datasheet	04/21/2020

The revision history provided is for informational purposes only and is believed to be accurate.

CUI DEVICES

CUI Devices offers a one (1) year limited warranty. Complete warranty information is listed on our website.

CUI Devices reserves the right to make changes to the product at any time without notice. Information provided by CUI Devices is believed to be accurate and reliable. However, no responsibility is assumed by CUI Devices for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI Devices products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Fixed Terminal Blocks category:

Click to view products by CUI Devices manufacturer:

Other Similar products are found below:

MBE-1512 MBE-154 MBE-156 MBES-153 MBES-156 MH-2512 MHE-132 MHE-163 MI-254 (35) MI-272 880507 MPT-275

15602-04-08-21 ELM023100 BA311TU BA411SU MV-152 MV-252-D MV-253/NCNOC MV-254-D MV-255 MV-462 MV-493 MVE
252 MVE-253 MVE-273 MVEB-153 1700096 1705142 1712417 1713020 1713088 1745195 1760594 1776118-2 1790852 1-796689-8

1-796692-6 1800001 1800114 1995279 20020314-C121B01LF 20020316-G041B01LF CB2-12 KP03215000J0G KP04215000J0G S451

282802-2 29.007 29.116