


SERIES: PVQ100W-D | DESCRIPTION: DC-DC CONVERTER
FEATURES

- 100 W isolated output
- ultra-wide 14:1 input range, 12~160 Vdc
- -40 ~ 105 °C operating temperature with derating
- reinforced insulation
- input under-voltage; output over temperature, over current, & over voltage protection
- 4,200 Vdc isolation
- remote on/off
- industry standard 1/4 brick package
- UL/EN/IEC 62368 certified
- meets EN 55032/55035/50155/EN 45545-2 with external circuits



| MODEL | input voltage | | output voltage | output current | output power | ripple & noise ¹ | efficiency ² |
|-------------------|---------------|-------------|----------------|----------------|--------------|-----------------------------|-------------------------|
| | nom (Vdc) | range (Vdc) | (Vdc) | max (A) | max (W) | max (mVp-p) | typ (%) |
| PVQ100W-072-S5-D | 72 | 12~160 | 5 | 20 | 100 | 150 | 87.5 |
| PVQ100W-072-S12-D | 72 | 12~160 | 12 | 8.3 | 100 | 150 | 88 |
| PVQ100W-072-S15-D | 72 | 12~160 | 15 | 6.7 | 100 | 150 | 89 |
| PVQ100W-072-S24-D | 72 | 12~160 | 24 | 4.2 | 100 | 240 | 89 |
| PVQ100W-072-S28-D | 72 | 12~160 | 28 | 3.6 | 100 | 240 | 90 |
| PVQ100W-072-S54-D | 72 | 12~160 | 54 | 1.85 | 100 | 480 | 90 |

Notes: 1. 20MHz bandwidth, peak to peak, 10µF polymer tantalum and 1µF ceramic capacitors.
 2. Efficiency is measured at 72 Vdc input voltage.
 3. An external input capacitor 220µF for all models is recommended to reduce input ripple voltage.

PART NUMBER KEY


INPUT

| parameter | conditions/description | min | typ | max | units |
|-----------------------------------|---|---|-----|------|------------------|
| operating input voltage | | 12 | 72 | 160 | Vdc |
| under voltage lockout | turn-on voltage threshold | 10.7 | 11 | 11.7 | Vdc |
| | turn-off voltage threshold | 9.7 | 10 | 10.7 | Vdc |
| | lockout hysteresis voltage | | 1.0 | | Vdc |
| current | at 16 V input, full load at 12 V input, 80% load | | | 8.0 | A |
| inrush current (I ² t) | as per ETS300 132-2 | | | 0.1 | A ² s |
| filter | Pi filter | | | | |
| surge voltage | for maximum of 100ms | | | 185 | Vdc |
| CTRL | positive logic | models ON (3.5~160 Vdc or on/off pin open circuit) | | | |
| | | models OFF (on/off pin 0~1.2 Vdc) | | | |
| | negative logic | models ON (on/off pin 0~1.2 Vdc) | | | |
| | | models OFF (3.5~160 Vdc or on/off pin open circuit) | | | |
| on/off current ⁴ | I on/off at V on/off = 0V | | 0.4 | 1 | mA |
| leakage current ⁴ | logic high, V on/off = 15V | | | 30 | μA |

Notes: 4. For both remote on/off logic.

OUTPUT

| parameter | conditions/description | min | typ | max | units |
|--------------------------------|--|------|-----|--------|-------|
| maximum capacitive load | 5 Vdc output model | | | 20,000 | μF |
| | 12 Vdc output model | | | 8,300 | μF |
| | 15 Vdc output model | | | 6,700 | μF |
| | 24 Vdc output model | | | 4,200 | μF |
| | 28 Vdc output model | | | 3,600 | μF |
| | 54 Vdc output model | | | 1,000 | μF |
| voltage accuracy | at 72 V input, full load, 25°C | -1.0 | | 1.0 | % |
| line regulation | from low line to high line, full load | | | ±0.2 | % |
| load regulation | full load to no load | | | ±0.2 | % |
| temperature coefficient | -40° ~ 105°C | | | ±0.02 | %/°C |
| switching frequency | | 180 | 200 | 220 | kHz |
| transient recovery time | 75 ~ 100% of step load change, d _i /d _t = 0.1A/μs (within 1% Vout nominal) | | | 250 | μs |
| transient response deviation | 75 ~ 100% of step load change, d _i /d _t = 0.1A/μs (within 1% Vout nominal) | | | ±5 | % |
| start up time / input voltage | V on/off to 10% Vo_set, remote on | | 50 | | ms |
| start up time / on/off control | Vin_min to 10% Vo_set, power up | | 50 | | ms |
| rise time | 10% Vo_set to 90% Vo_set | | 50 | | ms |
| adjustability | Po ≤ max rated power, Io ≤ Io_max | | | | |
| | 54 Vdc output model | -20 | | 10 | % |
| | all other models | -20 | | 15 | % |
| remote sense | Po ≤ max rated power, Io ≤ Io_max % of nominal Vo | | | | |
| | 54 Vdc output model | | | 10 | % |
| | all other models | | | 15 | % |

PROTECTIONS

| parameter | conditions/description | min | typ | max | units |
|-----------------------------|---|-----|-----|-----|-------|
| over voltage protection | limited voltage, % of nominal output | | | | |
| | 54 Vdc output model | 112 | 117 | 140 | % |
| | all other models | 117 | 125 | 140 | % |
| over current protection | auto recovery, hiccup | 110 | 150 | 180 | % |
| short circuit protection | continuous, auto recovery | | | | |
| over temperature protection | temperature at the center part of case, non-latching shutdown | | 110 | | °C |
| | recovery | | 100 | | °C |

SAFETY AND COMPLIANCE

| parameter | conditions/description | min | typ | max | units |
|------------------------------|--|-----|-------|----------------|------------|
| isolation voltage | input to output, for 1 minute | | | 3,000 4,200 | Vac Vdc |
| | input to case (base plate), for 1 minute | | | 2,100 3,000 | Vac Vdc |
| | output to case (base plate), for 1 minute | | | 1,500 2,100 | Vac Vdc |
| isolation resistance | input to output | 100 | | | MΩ |
| isolation capacitance | input to output | | 1,000 | | pF |
| safety approvals | certified to 62368: UL/cUL, EN, IEC | | | | |
| conducted emissions | EN55032 and EN50155 Compliant (with external filter) | | | | |
| ESD | EN61000-4-2 Level 3: Air ±8kV, Contact ±6kV, perf. Criteria A | | | | |
| radiated immunity | EN61000-4-3 Level 3: 80~ 1000 MHz, 20V/m, perf. Criteria A | | | | |
| EFT/burst | EN61000-4-4 Level 3: on power input port, ±2kV, external input capacitor required (EN 50155), perf. Criteria A | | | | |
| surge | EN61000-4-5 Level 4: Line to Earth, ±4kV, Line to Line ±2kV (EN50155), perf. Criteria A | | | | |
| conducted immunity | EN61000-4-6 Level 3: 0.15~80MHz, 10V, perf. Criteria A | | | | |
| voltage supply interruptions | EN50155 Class S3: 20ms interruptions | | | | |
| MTBF | as per MIL-HDBK-217F, 25°C | | | | |
| | 5 Vdc output model | | 570 | | |
| | 12 Vdc output model | | 690 | | |
| | 15 Vdc output model | | 785 | | K hours |
| | 24 Vdc output model | | 840 | | |
| | 28 Vdc output model | | 800 | | |
| | 54 Vdc output model | | 850 | | |
| RoHS | yes | | | | |

ENVIRONMENTAL

| parameter | conditions/description | min | typ | max | units |
|----------------------------|--|-----|-----|-----|-------|
| operating case temperature | measured at the center of the case plate, see derating curve | -40 | | 105 | °C |
| storage temperature | | -55 | | 125 | °C |
| operating humidity | non-condensing | | | 95 | % |

MECHANICAL

| parameter | conditions/description | min | typ | max | units |
|---------------|--|-----|-----|-----|-------|
| dimensions | 57.9 × 36.8 × 12.8 [2.28 × 1.45 × 0.50 inch] | | | | mm |
| case material | plastic, DAP, UL 94V-0 | | | | |
| weight | | | 66 | | g |


MECHANICAL DRAWING

units: inch [mm]

tolerances: inches: x.xx = ±0.02, x.xxx = ±0.010


mm: x.x = ±0.5, x.xx = ±0.25

| PIN Out | |
|---------|----------|
| PIN | Function |
| 1 | +Vin |
| 2 | on/off |
| 3 | -Vin |
| 4 | -Vo |
| 5 | Sense- |
| 6 | Trim |
| 7 | Sense+ |
| 8 | +Vo |




DERATING CURVES


TEMPERATURE DERATING CURVE ($V_{in} = 72\text{ V}$)
PVQ100W-072-S5-D, PVQ100W-072-S12-D



TEMPERATURE DERATING CURVE ($V_{in} = 72\text{ V}$)
PVQ100W-072-S15-D, PVQ100W-072-S24-D,
PVQ100W-072-S28-D, PVQ100W-072-S54-D




INPUT VOLTAGE DERATING CURVE




EFFICIENCY CURVES


EFFICIENCY VS OUTPUT LOAD
25°C
PVQ100W-072-S5-D




POWER DISSIPATION VS OUTPUT POWER
25°C
PVQ100W-072-S5-D




EFFICIENCY VS OUTPUT LOAD
25°C
PVQ100W-072-S12-D




POWER DISSIPATION VS OUTPUT POWER
25°C
PVQ100W-072-S12-D



EFFICIENCY VS OUTPUT LOAD
25°C
PVQ100W-072-S15-D




POWER DISSIPATION VS OUTPUT POWER
25°C
PVQ100W-072-S15-D




EFFICIENCY CURVES (CONTINUED)


EFFICIENCY VS OUTPUT LOAD
25°C
PVQ100W-072-S24-D




POWER DISSIPATION VS OUTPUT POWER
25°C
PVQ100W-072-S24-D




EFFICIENCY VS OUTPUT LOAD
25°C
PVQ100W-072-S28-D




POWER DISSIPATION VS OUTPUT POWER
25°C
PVQ100W-072-S28-D



EFFICIENCY VS OUTPUT LOAD
25°C
PVQ100W-072-S54-D




POWER DISSIPATION VS OUTPUT POWER
25°C
PVQ100W-072-S54-D




EFFICIENCY CURVES (CONTINUED)

Efficiency measured at 100% load. At 80% load when Vin is 12 ~ 16V.


**EFFICIENCY VS INPUT VOLTAGE
(25°C, FULL LOAD)
PVQ100W-072-S5-D**




**EFFICIENCY VS INPUT VOLTAGE
(25°C, FULL LOAD)
PVQ100W-072-S12-D**




**EFFICIENCY VS INPUT VOLTAGE
(25°C, FULL LOAD)
PVQ100W-072-S15-D**




**EFFICIENCY VS INPUT VOLTAGE
(25°C, FULL LOAD)
PVQ100W-072-S24-D**



**EFFICIENCY VS INPUT VOLTAGE
(25°C, FULL LOAD)
PVQ100W-072-S28D**



**EFFICIENCY VS INPUT VOLTAGE
(25°C, FULL LOAD)
PVQ100W-072-S54-D**



REVISION HISTORY

| rev. | description | date |
|------|------------------------------------|------------|
| 1.0 | initial release | 11/22/2022 |
| 1.01 | clear mounting insert option added | 12/12/2022 |

The revision history provided is for informational purposes only and is believed to be accurate.



Headquarters
20050 SW 112th Ave.
Tualatin, OR 97062
800.275.4899

Fax 503.612.2383
cui.com
techsupport@cui.com

CUI offers a two (2) year limited warranty. Complete warranty information is listed on our website.

CUI reserves the right to make changes to the product at any time without notice. Information provided by CUI is believed to be accurate and reliable. However, no responsibility is assumed by CUI for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Isolated DC/DC Converters - Through Hole](#) category:

Click to view products by [CUI Inc](#) manufacturer:

Other Similar products are found below :

[PDME2-S5-S7-S](#) [PDME2-S5-S3-S](#) [PDME2-S5-D3-S](#) [PEME2-S5-D9-S](#) [PQC10-48-S5-O](#) [PQC10-48-S15-O](#) [PQC60-24-S5](#) [PQC60-24-S12](#)
[PQC60-24-S15-H](#) [PQC60-24-S12-H](#) [PQQ6W-Q24-D12-S](#) [PVQ100W-O72-S12-D](#) [PVQ100W-O72-S24-D](#) [PH1200A280-28/T](#) [PH1200A280-48/T](#) [PH1200A280-28](#) [PH1200A280-36](#) [PH1200A280-24/T](#) [PYD20-72WS12](#) [PYD20-72WS15](#) [PYD20-72WS05](#) [PYD20-72WD12](#) [PYD20-72WD24](#) [PYD20-72WD15](#) [PYH200-72WS48](#) [TEL 15-2411WIN](#) [TEL 15-4812WIN](#) [TEP 150-7211UIR](#) [THL 30-2410WI](#) [THL 30-2415WI](#)
[THL 30-2412WI](#) [THL 30-4812WI](#) [THL 30-2411WI](#) [TMR 12-2423WI](#) [TRV 2-1211M](#) [TRV 2-1210M](#) [TRV 2-2422M](#) [IAB0112D24](#)
[IAB0124D12](#) [IAB0105D24](#) [IAB0115D15](#) [IAB0105D05](#) [IAB0112D3V3](#) [IAB0124D05](#) [IAB0105D09](#) [IAB0115D12](#) [IAB0115D05](#)
[IAB0124D15](#) [IEB0112S12](#) [IEB0124S12](#)