



SERIES: V78-1000-SMT | **DESCRIPTION:** NON-ISOLATED SWITCHING REGULATOR

FEATURES


- 1 A current output
- high efficiency up to 93%
- no heat sink required
- SMT package
- remote on/off control
- low ripple and noise
- short circuit protection, thermal shutdown
- wide temperature (-40°C~+85°C)



MODEL	input voltage range (Vdc)	output voltage (Vdc)	output current (mA)	output power max (W)	ripple and noise ¹ max (mVp-p)	efficiency level ² typ (%)
V7801-1000-SMT*	4.75 ~ 15	1.5	1,000	1.5	35	76
V7801A-1000-SMT*	4.75 ~ 15	1.8	1,000	1.8	35	79
V7802-1000-SMT*	5 ~ 18	2.5	1,000	2.5	35	83
V7803-1000-SMT	5 ~ 18	3.3	1,000	3.3	35	84
V7805-1000-SMT	7 ~ 18	5.0	1,000	5	35	90
V7806-1000-SMT	8.5 ~ 18	6.5	1,000	6.5	35	93

Notes: 1. 20 MHz bandwidth
 2. Measured at Vin min. and 100% load
 *. Discontinued model

PART NUMBER KEY



INPUT

parameter	conditions/description	min	typ	max	units
operating input voltage	1.5, 1.8 Vdc models	4.75	12	15	Vdc
	2.5, 3.3 Vdc models	5.0	12	18	Vdc
	5.0 Vdc model	7.0	12	18	Vdc
	6.5 Vdc model	8.5	12	18	Vdc
input filter	capacitor		10		μF
remote on/off	on: open or $1.2 < V_c \leq 6 \text{ V}$ off: $V_c < 0.6 \text{ V}$				
on/off control current	on: open or $1.2 < V_c \leq 6 \text{ V}$ off: GND or $V_c < 0.4 \text{ V}$		100	200	μA
shutdown input current			120	200	μA

OUTPUT

parameter	conditions/description	min	typ	max	units
max capacitive load				1,000	μF
line regulation	measured from low line to high line at 100% load		±0.2	±0.5	%
load regulation	measured from 10% to full load at nominal input		±0.4	±1.0	%
voltage accuracy	measured from low line to high line at 100% load		±2	±3	%
adjustability ¹	1.8 Vdc model	1.5		3.6	Vdc
	2.5 Vdc model	1.5		3.9	Vdc
	3.3 Vdc model	1.8		5.5	Vdc
	5.0 Vdc model	2.5		6.5	Vdc
switching frequency	PWM type		1.4		MHz
temperature coefficient	-40 °C ~ +85 °C ambient			±0.02	%/°C

Notes: 1. Output voltage adjustment must meet $V_{in}-V_o > 2\text{V}$ requirement, see adjustment resistor values on page 4. Not available on 1.5 or 6.5 Vdc output models.

PROTECTIONS

parameter	conditions/description	min	typ	max	units
short circuit protection	hiccup, continuous, automatic recovery				
thermal shutdown	internal IC junction		150		°C
current limit			1.8		A

SAFETY AND COMPLIANCE

parameter	conditions/description	min	typ	max	units
thermal resistance				90	°C/W
conducted emissions	CISPR22/EN55022 class A (without external circuit) CISPR22/EN55022 class B (external circuit required, see Figure 1-b)				
radiated emissions	CISPR22/EN55022 class A (external circuit required, see Figure 1-b)				
ESD	IEC/EN 61000-4-2, class B, contact ±6KV/ Air ±8KV				
radiated immunity	IEC/EN 61000-4-3, class A, 10V/m				
EFT/burst	IEC/EN 61000-4-4, class B, ±2KV (external circuit required, see Figure 1-a)				
surge	IEC/EN 61000-4-5, class B, ±2KV (external circuit required, see Figure 1-a)				
conducted immunity	IEC/EN 61000-4-6, class A, 3 Vr.ms				
voltage dips & interruptions	IEC/EN 61000-4-29, class B, 0%-70%				
MTBF	as per MIL-HDBK-217F, 25 °C	1,000,000			hours
RoHS	2011/65/EU				

ENVIRONMENTAL

parameter	conditions/description	min	typ	max	units
case operating temperature				100	°C
operating temperature	see derating curve	-40		85	°C
storage temperature		-55		125	°C
storage humidity				95	%
hand soldering	for 10 seconds			260	°C
reflow soldering	refer to IPC/JEDEC J-STD-020D.1			240	°C

MECHANICAL

parameter	conditions/description	min	typ	max	units
dimensions	15.24 x 8.30 x 7.25 (0.600 x 0.327 x 0.285)				mm inches
case material	Plastic (UL94-V0)				
weight			2.3		g




MECHANICAL DRAWING

units: mm [in]



pin tolerance: ±0.10 mm [±0.004 in]

general tolerance: ±0.25 mm [±0.010 in]


PIN CONNECTIONS	
1	+Vin
7,9	GND
5	+Vout
6	Vadj
10	On/Off



Note: Grid 2.54*2.54mm




TYPICAL APPLICATION CIRCUIT



1. C1 and C2 are required for best performance and should be fitted close to the converter pins.
2. See the capacitor values for C1 and C2 in the external capacitor table below. These can be increased if required and tantalum or low ESR electrolytic capacitors will also suffice.
3. No parallel connection or plug and play.


DERATING CURVE



EXTERNAL CAPACITOR TABLE

MODEL	C1 (Ceramic)	C2 (Ceramic)
V7801-1000-SMT	10 μ F / 25 V	22 μ F / 16 V
V7801A-1000-SMT	10 μ F / 25 V	22 μ F / 16 V
V7802-1000-SMT	10 μ F / 25 V	22 μ F / 16 V
V7803-1000-SMT	10 μ F / 25 V	22 μ F / 16 V
V7805-1000-SMT	10 μ F / 25 V	22 μ F / 16 V
V7806-1000-SMT	10 μ F / 25 V	22 μ F / 16 V

APPLICATION EXAMPLE



To reduce output ripple, it is recommended to add a LC filter to the output port.

L: Recommended parameter 10 ~ 47 μ H.

ADJUSTMENT RESISTOR VALUES

MODEL	V7801A-1000		V7802-1000		V7803-1000		V7805-1000	
Vadj (V)	R1 (kΩ)	R2 (kΩ)	R1 (kΩ)	R2 (kΩ)	R1 (kΩ)	R2 (kΩ)	R1 (kΩ)	R2 (kΩ)
1.5	188.1	-	15.4	-	-	-	-	-
1.8	-	-	68.6	-	15.4	-	-	-
2.5	-	81.4	-	-	87	-	9.7	-
3.0	-	32.2	-	88.7	339	-	30.5	-
3.3	-	18.6	-	41.3	-	-	48.8	-
3.6	-	9.5	-	20.1	-	121	75	-
3.9	-	-	-	8.0	-	51.0	115	-
4.5	-	-	-	-	-	16.6	338	-
4.9	-	-	-	-	-	8.0	1,835	-
5.0	-	-	-	-	-	6.5	-	-
5.1	-	-	-	-	-	5.2	-	426
5.5	-	-	-	-	-	1.1	-	58.7
6.0	-	-	-	-	-	-	-	16.9
6.5	-	-	-	-	-	-	-	3.2

The R1, R2 in the above table are used to set the output voltage. If no need to adjust the output voltage, connect a ceramic capacitor to GND with 470pF typical value for increase immunity. Insure the output voltage is in the adjust range or else may cause permanent damage to the device. Fine-tune output voltage must appease $V_{in}-V_o > 2V$.

EMC RECOMMENDED CIRCUIT




Figure 1

Recommended External Circuit Components	
FUSE	choose according to practical input current
MOV	10D560
LDM1	82μH
TVS	SMCJ36A
C0	120μF/50V
C1	4.7μF/50V
LDM2	33μH

Table 1

REVISION HISTORY

rev.	description	date
1.0	initial release	11/23/2011
1.01	V-Infinity branding removed	09/04/2012
1.02	added TR package option	10/31/2012
1.03	housing width changed, EMC recommendations updated	01/26/2016
1.04	discontinued V7802-1000-SMT model	10/23/2018
1.05	discontinued V7801-1000-SMT, V7801A-1000-SMT models	06/24/2019

The revision history provided is for informational purposes only and is believed to be accurate.

**CUI INC**[®]

Headquarters
20050 SW 112th Ave.
Tualatin, OR 97062
800.275.4899

Fax 503.612.2383
cui.com
techsupport@cui.com

CUI offers a two (2) year limited warranty. Complete warranty information is listed on our website.

CUI reserves the right to make changes to the product at any time without notice. Information provided by CUI is believed to be accurate and reliable. However, no responsibility is assumed by CUI for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Non-Isolated DC/DC Converters](#) category:

Click to view products by [CUI Inc](#) manufacturer:

Other Similar products are found below :

[DP8160G-S1-R1](#) [BRFS50](#) [APTH003A0X-SRZ](#) [SPM1004-3V3C](#) [APXW012A0X3-SRDZ](#) [R-785.0-05](#) [BRFS30](#) [PJT020A0X43-SRZ](#) [CONN-KIT](#) [10E24-P15-10PPM](#) [1E24-P4-25PPM-SHV-5KV](#) [CA-17205-L4](#) [4D15-N1](#) [MYGTM01210BZN](#) [APXW012A0X3-SRDZ](#) [MYRGP250100W21RA](#) [MYRGP120100B21RA](#) [MYRGP180100B21RA](#) [PTV05020WAH](#) [PTV12010LAH](#) [PTV12020WAD](#) [R-625.0D](#) [R-7212D](#) [R-7212P](#) [R-745.0D](#) [R-78AA15-0.5SMD](#) [R-78AA5.0-1.0SMD](#) [30A24-N15-E](#) [10A12-P4-M](#) [10C24-N250-I5](#) [10C24-P125](#) [10C24-P250-I5](#) [6A24-P20-I10-F-M-25PPM](#) [1A24-P30-F-M-C](#) [TSR 1-24150SM](#) [1/2AA24-N30-I10](#) [1C24-N125](#) [12C24-N250](#) [IBF05012A006V-007-R](#) [IBF12012A007V-007-R](#) [V7806-1500](#) [V7806W-500](#) [1/4C24-NP250-1](#) [EC5A-05S33](#) [TPS82084SILR](#) [1A12-N4-F-C](#) [PTV12020LAH](#) [PTV05010WAH](#) [PTN04050CAZT](#) [PTN04050CAS](#)