


SERIES: VGS-75W | DESCRIPTION: INTERNAL AC-DC POWER SUPPLY
FEATURES

- wide input range (85 ~ 305 VAC)
- available with conformal coating or terminal cover options
- UL/EN/IEC 62368 certified
- designed to meet IEC/EN 61558 and IEC/EN 60335 system requirements
- short-circuit, over-current, over-voltage protections
- CISPR/EN55032 Class B radiated/conducted emissions



| MODEL | output voltage | output current | output power | ripple and noise ¹ | efficiency ² |
|------------|----------------|----------------|--------------|-------------------------------|-------------------------|
| | (Vdc) | max (A) | max (W) | typ (mVp-p) | typ (%) |
| VGS-75W-5 | 5 | 14.0 | 70 | 100 | 85 |
| VGS-75W-12 | 12 | 6.0 | 72 | 120 | 87 |
| VGS-75W-15 | 15 | 5.0 | 75 | 120 | 87 |
| VGS-75W-24 | 24 | 3.2 | 76 | 150 | 89 |
| VGS-75W-36 | 36 | 2.1 | 75 | 200 | 89 |
| VGS-75W-48 | 48 | 1.6 | 76 | 200 | 90.5 |

Notes: 1. Ripple & noise are measured at 20 MHz BW with 47 μ F aluminum electrolytic capacitor and 0.1 μ F ceramic capacitor on the output.
 2. Measured at 230 Vac

PART NUMBER KEY


INPUT

| parameter | conditions/description | min | typ | max | units |
|---------------------------|-----------------------------------|-----|-----|------|-------|
| voltage | ac input | 85 | | 305 | Vac |
| | dc input | 120 | | 430 | Vdc |
| frequency | | 47 | | 63 | Hz |
| current | at 115 Vac | | | 2 | A |
| | at 230 Vac | | | 1 | A |
| inrush current | at 115 Vac, full load, cold start | | 40 | | A |
| | at 230 Vac, full load, cold start | | 75 | | A |
| leakage current | at 277 Vac | | | 0.75 | mA |
| no load power consumption | | | | 0.5 | W |

OUTPUT

| parameter | conditions/description | min | typ | max | units |
|----------------------------|--|-----|-------|--------|-------|
| capacitive load | 5 Vdc output | | | 10,000 | μF |
| | 12 Vdc output | | | 6,000 | μF |
| | 15 Vdc output | | | 5,000 | μF |
| | 24 Vdc output | | | 1,500 | μF |
| | 36 Vdc output | | | 1,000 | μF |
| | 48 Vdc output | | | 680 | μF |
| line regulation | rated load | | ±0.5 | | % |
| load regulation | 0% ~ 100%, 5 Vdc output | | ±1 | | % |
| | 0% ~ 100%, 12, 15, 24, 36, 48 Vdc output | | ±0.5 | | % |
| hold-up time | at 115 Vac | 8 | | | ms |
| | at 230 Vac | 55 | | | ms |
| switching frequency | | | 65 | | kHz |
| temperature coefficient | at 230 Vac, 0°C to 50°C | | ±0.03 | | %/°C |
| adjustability | built in trim pot | | ±10 | | % |
| initial set point accuracy | 5 Vdc output | | ±2 | | % |
| | other outputs | | ±1 | | % |

PROTECTIONS

| parameter | conditions/description | min | typ | max | units |
|--------------------------|---------------------------------------|-----|-----|-------|-------|
| over voltage protection | 5 Vdc output, clamp, auto recovery | | | 6.3 | Vdc |
| | 12 Vdc output, hiccup, auto recovery | | | 16.2 | Vdc |
| | 15 Vdc output, hiccup, auto recovery | | | 21.75 | Vdc |
| | 24 Vdc output, hiccup, auto recovery | | | 33.6 | Vdc |
| | 36 Vdc output, clamp, auto recovery | | | 50.0 | Vdc |
| | 48 Vdc output, clamp, auto recovery | | | 60.0 | Vdc |
| over current protection | at 230 Vac, rated load, auto recovery | 110 | | 200 | % |
| short circuit protection | hiccup, continuous, auto recovery | | | | |

SAFETY & COMPLIANCE

| parameter | conditions/description | min | typ | max | units |
|-------------------|---|--------------------|-----|-----|-------|
| isolation voltage | input to ground, 1 min. <10mA | 2,000 | | | Vac |
| | input to output, 1 min. <10mA | 4,000 | | | Vac |
| | output to ground, 1 min. <10mA | 1,250 | | | Vac |
| safety approvals | certified to | 62368: IEC, EN, UL | | | |
| | designed to meet | 60335: IEC, EN | | | |
| | designed to meet | 61558: IEC, EN | | | |
| safety class | class I | | | | |
| EMI/EMC | CISPR32/EN 55032 class B, IEC 61000-3-2 Class A | | | | |
| ESD | IEC/EN 61000-4-2 Contact ±6KV/Air ±8KV perf. criteria A | | | | |
| radiated immunity | IEC/EN 61000-4-3 10 V/m perf. criteria A | | | | |

SAFETY & COMPLIANCE

| | | | |
|-------------------------------|---|---------|-------|
| EFT/burst | IEC/EN 61000-4-4 ±2KV perf. criteria A | | |
| surge | IEC/EN 61000-4-5 line to line ±2KV/line to ground ±4KV perf. criteria A | | |
| conducted immunity | IEC/EN 61000-4-6 10 Vr.m.s perf. criteria A | | |
| voltage dips and interruption | IEC/EN 61000-4-11 0%, 70% perf. criteria B | | |
| MTBF | as per MIL-HDBK-217F at 25°C | 300,000 | hours |
| RoHS | yes | | |

ENVIRONMENTAL

| parameter | conditions/description | min | typ | max | units |
|-----------------------|------------------------|-----|-----|-----|-------|
| operating temperature | | -30 | | 70 | °C |
| storage temperature | | -40 | | 85 | °C |
| operating humidity | non-condensing | 20 | | 90 | % |
| storage humidity | non-condensing | 0 | | 95 | % |

MECHANICAL


| parameter | conditions/description | min | typ | max | units |
|---------------|--------------------------|-----|-----|-----|-------|
| dimensions | 99.00 x 97.00 x 30.00 mm | | | | mm |
| weight | | | 220 | | g |
| cooling | free air convection | | | | |
| case material | metal (AL1100, SGCC) | | | | |

MECHANICAL DRAWING

units: mm
tolerance: ±1 [±0.039]


| PIN CONNECTIONS | |
|-----------------|----------|
| PIN | Function |
| 1 | AC(L) |
| 2 | AC(N) |
| 3 | ⊕ |
| 4 | -Vo |
| 5 | +Vo |

wire range: 22-12 AWG
connector tightening torque: M3.5, 0.8 N·m




DERATING CURVE

TEMPERATURE DERATING CURVE




INPUT VOLTAGE DERATING CURVE (25 °C)




EFFICIENCY CURVES

EFFICIENCY VS INPUT LOAD (full load)



EFFICIENCY VS OUTPUT LOAD (at 230 Vac)



REVISION HISTORY

| rev. | description | date |
|------|--|------------|
| 1.0 | initial release | 09/02/2020 |
| 1.01 | derating and efficiency curves updated | 06/04/2021 |

The revision history provided is for informational purposes only and is believed to be accurate.



Headquarters
20050 SW 112th Ave.
Tualatin, OR 97062
800.275.4899

Fax 503.612.2383
cui.com
techsupport@cui.com

CUI offers a two (2) year limited warranty. Complete warranty information is listed on our website.

CUI reserves the right to make changes to the product at any time without notice. Information provided by CUI is believed to be accurate and reliable. However, no responsibility is assumed by CUI for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Switching Power Supplies](#) category:

Click to view products by [CUI Inc](#) manufacturer:

Other Similar products are found below :

[70841011](#) [73-551-0005](#) [73-551-0048](#) [PS3E-B12F](#) [PS3E-E12F](#) [AAD600S-4-OP](#) [R22095](#) [KD0204](#) [9021](#) [LDIN100150](#) [LPM000-BBAR-01](#)
[LPX17S-C](#) [EVS57-10R6/R](#) [FP80](#) [FRV7000G](#) [22929](#) [PS3E-F12F](#) [CQM1IA121](#) [40370121900](#) [VI-PU22-EXX](#) [40370121910](#) [LDIN5075](#)
[LPM615-CHAS](#) [LPX140-C](#) [09-160CFG](#) [70841025](#) [VPX3000-CBL-DC](#) [VI-LUL-IU](#) [LPM000-BBAR-05](#) [LPM000-BBAR-08](#) [LPM124-](#)
[OUTA1-48](#) [LPM000-BBAR-07](#) [LPM109-OUTA1-10](#) [LPM616-CHAS](#) [08-30466-1055G](#) [08-30466-2175G](#) [08-30466-2125G](#) [DMB-EWG](#)
[TVQF-1219-18S](#) [6504-226-2101](#) [CQM1IPS01](#) [SP-300-5](#) [CQM1-IPS02](#) [VI-MUL-ES](#) [22829](#) [08-30466-0065G](#) [VI-RU031-EWWX](#) [08-30466-](#)
[0028G](#) [EP3000AC48INZ](#) [VP-C2104853](#)