

SERIES: VOF-550C | **DESCRIPTION:** AC-DC POWER SUPPLY**FEATURES**


- 90~264 Vac and 127~370 Vdc input voltage range
- 3" x 5" open-frame footprint
- 320 W under natural convection, 550 W with airflow
- -40 ~ 70 °C temperature range
- active PFC
- 5 Vsby, 12 Vfan, power good, remote sense
- certified to 62368 safety standard
- designed to meet 60335 & 61558 safety requirements



| MODEL | output voltage | | output current max (A) | output power ² max (W) | ripple and noise ³ max (mVp-p) | efficiency ⁴ typ (%) |
|-------------|----------------|--------------------------|------------------------|-----------------------------------|---|---------------------------------|
| | (Vdc) | range ¹ (Vdc) | | | | |
| VOF-550C-12 | 12 | 11.4~12.6 | 41.60 | 499.2 | 200 | 91.0 |
| VOF-550C-15 | 15 | 14.25~15.75 | 33.30 | 499.5 | 200 | 92.0 |
| VOF-550C-24 | 24 | 22.8~25.2 | 22.90 | 549.6 | 200 | 93.0 |
| VOF-550C-27 | 27 | 25.65~28.35 | 20.40 | 550.8 | 200 | 93.5 |
| VOF-550C-36 | 36 | 34.2~37.8 | 15.30 | 550.8 | 200 | 94.0 |
| VOF-550C-48 | 48 | 45.6~50.4 | 11.46 | 550.0 | 200 | 94.0 |

Notes:

1. When adjusting the output voltage care should be taken never to exceed the stated output power or output current of the unit.
2. With 25 CFM of forced air cooling.
3. At full load, nominal input, 20 MHz bandwidth oscilloscope, tip & barrel method, output terminated with 47 μ F electrolytic and 0.1 μ F ceramic capacitors.
4. At 230 Vac.

PART NUMBER KEY

INPUT

| parameter | conditions/description | min | typ | max | units |
|---------------------------|---|------|-----|-----|-------|
| voltage | ac input | 90 | | 264 | Vac |
| | dc input | 127 | | 370 | Vdc |
| frequency | | 47 | | 63 | Hz |
| current | at 90/115 Vac | | | 6.5 | A |
| | at 230 Vac | | | 3.0 | A |
| inrush current | at 115 Vac, cold start | | 50 | | A |
| | at 230 Vac, cold start | | 80 | | A |
| leakage current | at 264 Vac | | | 0.1 | mA |
| | contact leakage current earth leakage current | | | 0.5 | mA |
| power factor correction | at 115 Vac, full load | 0.98 | | | |
| | at 230 Vac, full load | 0.95 | | | |
| no load power consumption | at 230 Vac, PS-ON signal held low (output disabled) | | | 0.5 | W |

OUTPUT

| parameter | conditions/description | min | typ | max | units |
|----------------------------|--|-----|----------|-------|--------|
| output capacitance | 12, 15, 24 Vdc output models | | | 6,000 | μF |
| | 27 Vdc output model | | | 4,000 | μF |
| | 36 Vdc output model | | | 3,000 | μF |
| | 48 Vdc output model | | | 2,000 | μF |
| initial set point accuracy | full load | | | | |
| | 12,15, 24, 27 Vdc output models all other output models | | ±2 ±1 | | % % |
| line regulation | rated load | | ±0.5 | | % |
| load regulation | 0 ~ 100% load | | ±1 | | % |
| hold-up time | at 115 Vac | 10 | | | ms |
| | at 230 Vac | 10 | | | ms |
| temperature coefficient | | | ±0.03 | | %/°C |
| fan power | output power of 12 Vdc/0.5A | | | 6 | W |

PROTECTIONS

| parameter | conditions/description | min | typ | max | units |
|-----------------------------|--|-----|------|------|-------|
| over voltage protection | output shutdown, latching | | | | |
| | 12 Vdc output model | | | 15.6 | Vdc |
| | 15 Vdc output model | | | 19.5 | Vdc |
| | 24 Vdc output model | | | 31.2 | Vdc |
| | 27 Vdc output model | | | 35.1 | Vdc |
| | 36 Vdc output model | | | 46.8 | Vdc |
| 48 Vdc output model | | | 60.0 | Vdc | |
| over current protection | auto recovery, hiccup | 105 | | | % |
| short circuit protection | continuous, auto recovery, hiccup, recovery time <5s | | | | |
| over temperature protection | auto recovery | | | | |

SAFETY & COMPLIANCE


| parameter | conditions/description | min | typ | max | units |
|----------------------------------|---|---------|-----|-----|-------|
| isolation voltage | input to output, 1 min, <5mA | 4,000 | | | Vac |
| | input to ground, 1 min, <5mA | 2,000 | | | Vac |
| | output to ground, 1 min, <5mA | 1,500 | | | Vac |
| safety approvals | certified to 62368: EN/UL designed to meet 60335: EN designed to meet 61558: EN | | | | |
| safety class | Class I | | | | |
| conducted emissions ⁵ | EN55032(CISPR32) CLASS B | | | | |
| radiated emissions ⁵ | EN55032(CISPR32) CLASS B | | | | |
| harmonic current | IEC/EN61000-3-2 CLASS A and CLASS D | | | | |
| flicker | IEC/EN61000-3-3 | | | | |
| ESD | IEC/EN61000-4-2 Contact ±8KV/Air ±15KV, perf. Criteria A | | | | |
| radiated immunity | IEC/EN61000-4-3 10V/m, perf. Criteria A | | | | |
| EFT/burst | IEC/EN61000-4-4 ±2KV, perf. Criteria A | | | | |
| surge | IEC/EN61000-4-5 line to line ±2KV, line to ground ±4KV, perf. Criteria A | | | | |
| conducted immunity | IEC/EN61000-4-6 10Vr.m.s, perf. Criteria A | | | | |
| voltage dips and interruptions | IEC/EN61000-4-11 0%, 70% perf. Criteria B | | | | |
| MTBF | as per MIL-HDBK-217F at 25°C | 200,000 | | | hours |
| RoHS | yes | | | | |

Note: 5. The power supply is considered a component of the end system. All EMC performance has been tested on a metal plate with the dimensions 360 x 360 x 1 mm. The power supply must be integrated into the end system for proper electromagnetic compatibility testing.

ENVIRONMENTAL

| parameter | conditions/description | min | typ | max | units |
|-----------------------|------------------------|-----|-----|-----|-------|
| operating temperature | see derating curves | -40 | | 70 | °C |
| storage temperature | | -40 | | 85 | °C |
| operating humidity | non-condensing | 20 | | 90 | % |
| storage humidity | non-condensing | 10 | | 95 | % |



DERATING CURVES





Note: With an AC input voltage between 90 ~ 115 Vac and a DC input between 127 ~ 160 Vdc the output power must be derated as per the temperature derating curves.

EFFICIENCY CURVES



EFFICIENCY VS INPUT VOLTAGE
(full load)





EFFICIENCY VS OUTPUT LOAD
($V_{in} = 230\text{ Vac}$)





EFFICIENCY VS INPUT VOLTAGE
(full load)





EFFICIENCY VS OUTPUT LOAD
($V_{in} = 230\text{ Vac}$)



EFFICIENCY VS INPUT VOLTAGE
(full load)



EFFICIENCY VS OUTPUT LOAD
($V_{in} = 230\text{ Vac}$)



MECHANICAL

| parameter | conditions/description | min | typ | max | units |
|------------|--|-----|-----|-----|-------|
| dimensions | open frame models: 127 × 76.2 × 40.5 [5.0 × 3.0 × 1.594 inch] | | | | mm |
| | covered models: 130.0 × 86.0 × 43.0 [5.118 × 3.385 × 1.692 inch] | | | | mm |
| | with rear fan: 160.0 × 86.0 × 43.0 [6.299 × 3.385 × 1.692 inch] | | | | mm |
| weight | open frame models | | 490 | | g |
| | covered models | | 605 | | g |
| | with rear fan | | 645 | | g |
| cooling | natural convection or 25 CFM forced air | | | | |


MECHANICAL DRAWING

Open-frame

units: mm [inch]

general tolerance: ±1.00 [±0.039]

pin 7,8 connector tightening torque: M4, 1.2N·m (max)



| PIN-OUT | | |
|---------|-------------------|---|
| PIN | Function | Mating Connector |
| 1 | AC (L) | Housing: JST VHR or equivalent Contact: JST SVH-21T-P1.1 or equivalent |
| 2 | NC | |
| 3 | AC (N) | |
| 4 | GND | Contact: JST SPS-21T-250 |
| 5 | FAN+ | CN5: Fan power output port Housing: TKP 2502 or equivalent |
| 6 | FAN- | Contact: TKP 8811 or equivalent |
| 7 | +Vo | |
| 8 | -Vo | |
| 9 | ADJ (Trim POT) | |

| CN6: PS_ON signal input port (3-4) 5Vdc standby (1-2) | | |
|--|----------|--|
| PIN | Function | Mating Connector |
| 1 | +5V | Housing: JST PHD-2*2Y or equivalent |
| 2 | GND | |
| 3 | PS-ON | Contact: JST PHD-TE or equivalent |
| 4 | GND | |

| CN2: remote sensing signal input port (1-2) PG signal (3-4) | | |
|--|----------|--|
| PIN | Function | Mating Connector |
| 1 | RS- | Housing: JST PHD-2*2Y or equivalent |
| 2 | RS+ | |
| 3 | GND | Contact: JST PHD-TE or equivalent |
| 4 | PG | |

| Position | Screw Spec. | L (recommended) | Torque (max) |
|----------|-------------|--------------------|-----------------|
| ①~④ | M3 | 2.5mm | 0.4 N·m |

Note: 1. Class I system ①, ②, ④ positions must be connected to the protective earth ground (⊕).
2. It is recommended that a minimum distance of 10mm be placed between the PCB edge and all other components.







MECHANICAL DRAWING (CONTINUED)

Covered

units: mm [inch]

general tolerance: ± 1.00 [± 0.039]


pin 7,8 connector tightening torque: M4, 1.2N·m (max)



| PIN-OUT | | |
|---------|----------------|--|
| PIN | Function | Mating Connector |
| 1 | AC (L) | Housing: JST VHR or equivalent Contact: JST SVH-21T-P1.1 or equivalent |
| 2 | NC | |
| 3 | AC (N) | |
| 4 | GND | Contact: JST SPS-21T-250 |
| 5 | FAN+ | CN5: Fan power output port Housing: TKP 2502 or equivalent Contact: TKP 8811 or equivalent |
| 6 | FAN- | |
| 7 | +Vo | |
| 8 | -Vo | |
| 9 | ADJ (Trim POT) | |

| CN6: PS_ON signal input port (3-4) 5Vdc standby (1-2) | | |
|--|----------|-------------------------------------|
| PIN | Function | Mating Connector |
| 1 | +5V | Housing: JST PHD-2*2Y or equivalent |
| 2 | GND | |
| 3 | PS-ON | Contact: JST PHD-TE or equivalent |
| 4 | GND | |

| CN2: remote sensing signal input port (1-2) PG signal (3-4) | | |
|--|----------|-------------------------------------|
| PIN | Function | Mating Connector |
| 1 | RS- | Housing: JST PHD-2*2Y or equivalent |
| 2 | RS+ | |
| 3 | GND | Contact: JST PHD-TE or equivalent |
| 4 | PG | |



| Position | Screw Spec. | L (max) | Torque (max) |
|----------|-------------|---------|--------------|
| ①~② | M3 | 4mm | 0.4 N·m |
| ③~⑥ | M3 | 2mm | 0.4 N·m |

Note: Safety Class I integrations require the metal case to be securely fastened to protective earth ground (⊕).

MECHANICAL DRAWING (CONTINUED)

with rear fan:

units: mm [inch]


general tolerance: ±1.00 [±0.039]

pin 7,8 connector tightening torque: M4, 1.2N·m (max)



| Position | Screw Spec. | L (max) | Torque (max) |
|----------|-------------|---------|--------------|
| ①~④ | M3 | 2mm | 0.4 N·m |

Note: Safety Class I integrations require the metal case to be securely fastened to protective earth ground (Ⓛ).

| PIN-OUT | | |
|---------|----------------|--|
| PIN | Function | Mating Connector |
| 1 | AC (L) | Housing: JST VHR or equivalent Contact: JST SVH-21T-P1.1 or equivalent |
| 2 | NC | |
| 3 | AC (N) | |
| 4 | GND | Contact: JST SPS-21T-250 |
| 5 | FAN+ | CN5: Fan power output port Housing: TKP 2502 or equivalent Contact: TKP 8811 or equivalent |
| 6 | FAN- | |
| 7 | +Vo | |
| 8 | -Vo | |
| 9 | ADJ (Trim POT) | |




| CN6: PS_ON signal input port (3-4) 5Vdc standby (1-2) | | |
|--|----------|-------------------------------------|
| PIN | Function | Mating Connector |
| 1 | +5V | Housing: JST PHD-2*2Y or equivalent |
| 2 | GND | |
| 3 | PS-ON | Contact: JST PHD-TE or equivalent |
| 4 | GND | |



| CN2: remote sensing signal input port (1-2) PG signal (3-4) | | |
|--|----------|-------------------------------------|
| PIN | Function | Mating Connector |
| 1 | RS- | Housing: JST PHD-2*2Y or equivalent |
| 2 | RS+ | |
| 3 | GND | Contact: JST PHD-TE or equivalent |
| 4 | PG | |

REMOTE SENSE

Remote Sense signals (RS+ and RS-) can be used to compensate for voltage drops that occur within the output power cables. RS+ and RS- should always be routed as a twisted pair and never shorted together or reversed otherwise permanent damage may occur.



REVISION HISTORY

| rev. | description | date |
|------|-----------------|------------|
| 1.0 | initial release | 12/21/2021 |

The revision history provided is for informational purposes only and is believed to be accurate.



CUI INC

a bel group

Headquarters

20050 SW 112th Ave.
Tualatin, OR 97062
800.275.4899

Fax 503.612.2383

cui.com

techsupport@cui.com

CUI offers a two (2) year limited warranty. Complete warranty information is listed on our website.

CUI reserves the right to make changes to the product at any time without notice. Information provided by CUI is believed to be accurate and reliable. However, no responsibility is assumed by CUI for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Switching Power Supplies](#) category:

Click to view products by [CUI Inc](#) manufacturer:

Other Similar products are found below :

[70841011](#) [73-551-0005](#) [73-551-0048](#) [EVS57-5R3/A](#) [AAD600S-4-OP](#) [MS924](#) [HWS50A-5/RA](#) [KD0204](#) [LDIN100150](#) [FP80](#) [FRV7000G](#)
[22929](#) [PS3E-F12F](#) [CQM1IA121](#) [VI-PU22-EXX](#) [LDIN5075](#) [432703037161](#) [09-160CFG](#) [LPM000-BBAR-08](#) [LPM000-BBAR-07](#) [08-30466-](#)
[1055G](#) [DMB-EWG](#) [CQM1IPS01](#) [SP-300-5](#) [CQM1-IPS02](#) [VI-MUL-ES](#) [22829](#) [08-30466-0028G](#) [09-250CFG](#) [CA400](#) [H47251](#) [96PSR-](#)
[A460WOTH-2](#) [VP-E2935648E](#) [G08-L](#) [G06-Q01](#) [GHA300F-12-SNF](#) [MTA040009A](#) [FSA150024A](#) [VI-RUR22-EWXX](#) [VI-PU03-EYW](#)
[PM1-03B-48-2](#) [VI-LUF-EW](#) [VI-QCWB3-CSV](#) [HLS30ZE-NT8](#) [UT1404-7](#) [ERP-350-12](#) [S8FSG01512C](#) [S8FSG03012C](#) [VI-PU22-EYY](#)
[XPFM201A+](#) [S8FS-G15015C](#)