

SERIES: VX78-1000R | **DESCRIPTION:** NON-ISOLATED DC SWITCHING REGULATOR
FEATURES

- wide input
- pin-out compatible with linear regulators
- encapsulated
- UL & CSA approved
- high efficiency up to 96%
- no-load input current as low as 0.2 mA
- wide operating temp: -40°C to +85°C
- supports negative output
- short circuit protection on the output
- EN 62368-1


**MODEL**

| MODEL | input voltage ¹ | | output voltage (Vdc) | output current max (mA) | output power max (W) | ripple & noise ² max (mVp-p) | efficiency typ (%) |
|--------------|----------------------------|----------------|-------------------------|-------------------------------|----------------------------|---|--------------------------|
| | typ (Vdc) | range (Vdc) | | | | | |
| VX7803-1000R | 24 | 6~36 | 3.3 | 1000 | 3.3 | 75 | 90 |
| VX7805-1000R | 24 | 8~36 | 5 | 1000 | 5 | 75 | 93 |
| | 12 | 8~27 | -5 | -500 | 2.5 | 75 | 86 |
| VX7809-1000R | 24 | 13~36 | 9 | 1000 | 9 | 75 | 95 |
| VX7812-1000R | 24 | 16~36 | 12 | 1000 | 12 | 75 | 96 |
| | 12 | 8~20 | -12 | -300 | 3.6 | 75 | 89 |
| VX7815-1000R | 24 | 20~36 | 15 | 1000 | 15 | 75 | 96 |
| | 12 | 8~18 | -15 | -300 | 4.5 | 75 | 89 |

Note:

1. For input voltage exceeding 30 VDC, an input capacitor of 22µF/50V is required

2. 20MHz bandwidth, nominal input, 20%-100% load. With light loads at or below 20%, ripple and noise for 3/3V/5V output parts increases to 100mVp-p and for 9V/12V/15V output parts to 2%Vo max.

PART NUMBER KEY

INPUT

| parameter | conditions/description | min | typ | max | units |
|-----------------------|------------------------|-----|-----|-----|-------|
| filter | capacitor filter | | | | |
| no-load input current | positive outputs | | 0.1 | 1 | mA |

OUTPUT

| parameter | conditions/description | min | typ | max | units |
|------------------------------|--|------------|--------------------|--------------------|--------------------|
| maximum capacitive load | for positive output applications for negative output applications | | | 680 330 | μ F μ F |
| voltage accuracy | at full load, input voltage range 3.3 Vdc output model all other models | | \pm 2 \pm 2 | \pm 4 \pm 3 | % % |
| line regulation | at full load, input voltage range | | \pm 0.2 | \pm 0.4 | % |
| load regulation | at nominal input, 10~100% load | | \pm 0.4 | \pm 0.6 | % |
| switching frequency | at nominal input voltage, full load 3.3/5 Vdc output models all other models | 420 580 | 520 680 | 620 780 | kHz kHz |
| transient recovery time | at nominal input voltage, 25% load step change | | 0.1 | 1 | ms |
| transient response deviation | at nominal input voltage, 25% load step change | | 50 | 300 | mV |
| temperature coefficient | Operating ambient temperature -40°C to +85°C | | | \pm 0.03 | %/°C |

PROTECTIONS

| parameter | conditions/description | min | typ | max | units |
|--------------------------|---------------------------|-----|-----|-----|-------|
| short circuit protection | continuous, auto recovery | | | | |

SAFETY AND COMPLIANCE

| parameter | conditions/description | min | typ | max | units |
|---------------------|--|-----|-----------|-----|-------|
| safety approvals | certified to 62368-1: EN certified to 60950: UL | | | | |
| conducted emissions | CISPR22/EN55022, class B (external circuit required, see Figure 4-b) | | | | |
| radiated emissions | CISPR22/EN55022, class B (external circuit required, see Figure 4-b) | | | | |
| ESD | IEC/EN61000-4-2, contact \pm 4kV, criteria B | | | | |
| radiated immunity | IEC/EN61000-4-3, 10V/m, criteria A | | | | |
| EFT/burst | IEC/EN61000-4-4, \pm 1kV, criteria B (external circuit required, see Figure 4-a) | | | | |
| surge | IEC/EN61000-4-5, line-line \pm 1kV, criteria B (external circuit required, see Figure 4-a) | | | | |
| conducted immunity | IEC/EN61000-4-6, 3 Vr.m.s, criteria A | | | | |
| MTBF | as per MIL-HDBK-217F, 25°C | | 2,000,000 | | hours |
| RoHS | yes | | | | |

ENVIRONMENTAL

| parameter | conditions/description | min | typ | max | units |
|-----------------------|------------------------|-----|-----|-----|-------|
| operating temperature | see derating curve | -40 | | 85 | °C |
| storage temperature | | -55 | | 125 | °C |
| storage humidity | non-condensing | 5 | | 95 | % |



MECHANICAL

| parameter | conditions/description | min | typ | max | units |
|---------------|--|-----|-----|-----|-------|
| dimensions | 11.50 x 9.00 x 17.50 [0.453 x 0.354 x 0.689 inch] | | | | mm |
| case material | black flame-retardant heat-proof plastic (UL94V-0) | | | | |
| weight | | | 3.8 | | g |

MECHANICAL DRAWING


units: mm [inch]
 tolerance: $\pm 0.25[\pm 0.010]$
 pin diameter tolerance: $\pm 0.10[\pm 0.004]$

| PIN CONNECTIONS | | |
|-----------------|---------|---------|
| PIN | +OUTPUT | -OUTPUT |
| 1 | +VIN | +VIN |
| 2 | GND | -VOUT |
| 3 | +VOUT | GND |







Note : Grid 2.54*2.54mm

DERATING CURVE



EFFICIENCY CURVES



TYPICAL APPLICATION CIRCUIT

Figure 1
Positive output application circuit




Figure 3




Figure 2
Negative output application circuit




Table 1


External Capacitor Table

| Model Number | C1, C3 (ceramic capacitor) | C2, C4 (ceramic capacitor) |
|--------------|-------------------------------|-------------------------------|
| VX7803-1000R | 10 μ F/50 V | 22 μ F/10 V |
| VX7805-1000R | 10 μ F/50 V | 22 μ F/10 V |
| VX7809-1000R | 10 μ F/50 V | 22 μ F/16 V |
| VX7812-1000R | 10 μ F/50 V | 22 μ F/25 V |
| VX7815-1000R | 10 μ F/50 V | 22 μ F/25 V |

- Note:
1. C1 & C2 (C3 & C4) are required and should be connected as close to the module pins as possible.
 2. Refer to Table 1 for C1 and C2 (C3 and C4) capacitor values. For certain applications, increased values for C2 and C4 and/or tantalum or low ESR electrolytic capacitors may also be used instead;
 3. When using configurations as shown in figure 3, we recommended to add an inductor (LDM) with a value of up to 10 μ H which helps reducing mutual interference;
 4. Converter cannot be used for hot swap and with output in parallel.

EMC RECOMMENDED CIRCUIT

Figure 4



- Note:
1. Part ① in Fig. 4 shows EMS compliance filter and part ② filter for EMI compliance; depending on requirement both filters ① and ② can be used in series as shown.

Table 2

| Recommended external circuit components | |
|---|--|
| FUSE | choose according to actual input current |
| MOV | S20K30 |
| LDM1 | 82 μ H |
| C0 | 680 μ F/50 V |
| C1, C2 | see Table 1 |
| C5 | 4.7 μ F/50 V |
| LDM2 | 12 μ H |

REVISION HISTORY

| rev. | description | date |
|------|---|------------|
| 1.0 | initial release | 03/09/2020 |
| 1.01 | safeties updated | 02/03/2021 |
| 1.02 | derating curve, efficiency curves and circuit figures updated | 09/21/2021 |

The revision history provided is for informational purposes only and is believed to be accurate.



Headquarters
20050 SW 112th Ave.
Tualatin, OR 97062
800.275.4899

Fax 503.612.2383
cui.com
techsupport@cui.com

CUI offers a two (2) year limited warranty. Complete warranty information is listed on our website.

CUI reserves the right to make changes to the product at any time without notice. Information provided by CUI is believed to be accurate and reliable. However, no responsibility is assumed by CUI for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Non-Isolated DC/DC Converters](#) category:

Click to view products by [CUI Inc](#) manufacturer:

Other Similar products are found below :

[PSR152.5-7IR](#) [APTH003A0X-SRZ](#) [SPM1004-3V3C](#) [R-785.0-05](#) [10E24-P15-10PPM](#) [1E24-P4-25PPM-SHV-5KV](#) [PROPOWER-3.3V](#)
[MYGTM01210BZN](#) [40C24-N250-I5-H](#) [40A24-P30-E](#) [3V12-P0.8](#) [10C24-N250-I10-AQ-DA](#) [4AA24-P20-M-H](#) [3V12-N0.8](#) [3V24-P1](#) [3V24-](#)
[N1](#) [BMR4672010/001](#) [BMR4652010/001](#) [6AA24-P30-I5-M](#) [6AA24-N30-I5-M](#) [BM2P101X-Z](#) [35A24-P30](#) [2.5M24-P1](#) [PTV03010WAD](#)
[PTV05020WAH](#) [PTV12010LAH](#) [PTV12020WAD](#) [R-7212D](#) [R-7212P](#) [R-78AA15-0.5SMD](#) [R-78AA5.0-1.0SMD](#) [30A24-N15-E](#) [10A12-P4-](#)
[M](#) [10C24-N250-I5](#) [10C24-P125](#) [10C24-P250-I5](#) [6A24-P20-I10-F-M-25PPM](#) [1A24-P30-F-M-C](#) [TSR 1-24150SM](#) [1/2AA24-N30-I10](#) [1C24-](#)
[N125](#) [12C24-N250](#) [V7806-1500](#) [PTV12020LAH](#) [PTV05010WAH](#) [PTN04050CAZT](#) [PTH12020WAD](#) [PTH12020LAS](#) [PTH05050YAH](#)
[PTH05T210WAH](#)