




# SSF212X100-14G

*Compact Horizontal Stainless Steel Floatswitch*

*1/2" NPT External Fitting*



- **Stainless Steel**
- **External Mount (1/2" NPT)**
- **N/O or N/C switching action**
- **Operating Temp up to 120°C**
- **G1/4 thread for attaching junction box**

The SSF212 series are externally mounted float switches via 1/2NPT thread. This particular version has a G1/4 thread at the cable entry to enable attachment of a suitable junction box.

The switches can be fitted to a tank without requiring access to the inside of the tank, as they are screwed in from the outside.

The float switch can be fitted to achieve either N/O (make on rise) or N/C (make on fall) switching action by simply rotating through 180° when fitting.


Technical Specification			
Mounting style	External	Cable length - standard	100cm
Mounting thread	1/2" NPT	Cable size	17/0.10 - AWG22
Float/Stem material	316/304 grade	Cable conductor material	Tinned copper
Maximum Temperature	120 °C	Cable sheath material	XLPE
Maximum Pressure	10 bar	Cable temperature rating	125 °C
Float SG	0.7	Sealing gasket	N/A
Minimum Fluid SG	0.75	Tightening torque for fixing	2.0kg/cm

Electrical Specification		
Contact Form		N/O or N/C
Switching Power Max.	VA	50
Switching Current Max.	A	0.5
Switching Voltage Max AC	V	300
Switching Voltage Max DC	V	350

All ratings are for resistive load only.

Cynergy3 Part	Leadouts
SSF212X100-14G	100cm XLPE wires

### Mechanical Dimensions (mm)



Cynergy3 Components Ltd.  
7 Cobham Road  
Ferndown Industrial Estate  
Wimborne, Dorset BH21 7PE  
Telephone +44 (0) 1202 897969

Email:sales@cynergy3.com

ISO 9001 CERTIFIED

www.cynergy3.com

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Liquid Level Sensors](#) category:*

*Click to view products by [Cynergy3](#) manufacturer:*

Other Similar products are found below :

[F03-16PT-1M](#) [FSH-21](#) [FSH-25](#) [FSH-34](#) [FSH-35](#) [FSV-31](#) [FSV-35](#) [LRNH31S41](#) [FSH-31](#) [RSF14Y100RF](#) [F03-16PT-10M](#) [LL01-1AB01](#)  
[F03-16PS-F](#) [F03-16SF-5M](#) [F03-16PE-5M](#) [F03-16PT-5M](#) [K7L-U](#) [LBFS 1151](#) [LL8951T5](#) [SCN-1518SC](#) [LL103000](#) [LRNR31N01](#) [K7L-](#)  
[AT50DB](#) [F03-16PT-2M](#) [14102](#) [RSF107H100GV](#) [MS03-PP](#) [KSL-100-1](#) [LS01-1A66-PP-2000W](#) [LS01-1B66-PP-500W](#) [LS02-1A66-S-500W](#)  
[LS02-1B66-S-500W](#) [LS02-1B85-PP-5000W](#) [LS03-1A85-PP-500W](#) [LS03/DL-1A85-PA-500W](#) [RSF26H050TG](#) [EL-3N](#) [LL01-1AA01](#)  
[LRNH31S42](#) [MS10C](#) [SSH66XE34N100](#) [SSH66TE34N100S](#) [TSF76H100DN](#) [TSF76H050TV](#) [OLS500D3L](#) [RSF88Y100R](#) [RSF76Y100RN](#)  
[RSF54Y100RC](#) [RSF53Y100RC](#) [OLS200D3LSH](#)