
# The AMD Opteron™ Processor for High-end Embedded Designs

#### Providing a balanced approach to embedded system design

The AMD Opteron™ processor helps enable a breakthrough in high-performance, low power processing for edge-of-enterprise markets including storage and telecommunications, as well as more traditional embedded markets such as security and medical





Opteron

imaging, military systems, and single-board computing. AMD64 technology with Direct Connect Architecture helps provide a balanced foundation for embedded systems. Based on the industry-standard x86 platform, AMD64 delivers the right match of processing power, memory performance, I/O throughput, and scalability. Add the vision of 32- and 64-bit application support with native multi-core computing in a consistent thermal envelope and many embedded designers are finding their AMD Opteron™ processor-based next-generation systems deliver superior application performance.

#### What can a leading processor platform offer?

AMD Opteron processors with third generation Direct Connect Architecture can help improve overall system performance and efficiency by helping eliminate traditional bottlenecks inherent in architectures where traditional front-side buses restrict and interrupt the flow of data. With AMD Opteron processors, there are no front-side buses. Instead, the processors, memory, and I/O are directly connected to the CPU. Further, the integrated memory controller helps reduce memory latency while HyperTransport<sup>TM</sup> technology delivers a very high I/O bandwidth. Data speeds through the system without encountering the traditional front-side bus bottleneck of competing x86 platforms. In addition to the architectural benefits inherent in Direct Connect Architecture, the AMD Opteron processor offers the following unique advantages for high-end embedded systems:

- → **HyperTransport™ technology** provides up to 17.6GB/s per link in HT 3.0 generation, and is compatible with HT 1.0 generation implementation
- → On-die integrated DDR2 memory controller offers available memory bandwidth up to 12.8GB/s (with DDR2-800) per processor
- → Hardware assisted AMD Virtualization™ technology in AMD Opteron processors with DDR2 helps streamline the efficiency of multiple servers and provides virtual machine memory isolation for improved security
- → Socket F (1207) provides system upgrade option from dualcore to quad-core in the same physical foorprint with future upgrade to six-core when they become available

#### **Dual Dynamic Power Management (DDPM)**

- → Allows for independent voltage control between the CPU cores and memory controller
- → Optimizes memory bandwidth for improved system performance
- → Helps reduce system power consumption and heat generation

#### AMD CoolCore™ technology

- → Reduces processor energy consumption by turning off unused parts of the processor
- → Helps reduce power and cooling costs by lowering the energy consumption of the platform design

#### Reliable, scalable

It's a fact that reliability is key in selecting embedded system components. AMD Opteron processors are NEBS-friendly, supporting telecommunications industry requirements for reliability. AMD64 technology provides features like Error Correcting Code (ECC) and JTAG interfaces for effective debug during system development. Additionally, Direct Connect Architecture requires fewer chips on the motherboard, further enhancing a system's overall reliabilitu.

The AMD Opteron processor provides unique scalability options with glueless multi-processing from one socket (2, 4 or 6 core) to 8 socket systems. This, combined with AMD64's reliability, helps deliver an embedded design that can provide customers a long-range plan for the life cycle of their systems.

## Beyond outstanding processors: Longevity, exceptional design support, quick time to market

The AMD64 Longevity Program is designed so that the high-performance processors you select for an embedded design will be available when you need them. AMD understands the unique requirements of the embedded market and our AMD64 Longevity Program is in place to maximize the available choice of leading edge x86 processors — delivering a wide range of performance, power, thermal, and packaging features.


AMD has a strong design support program in place. From Reference Design Kits (RDKs) to extensive and readily available documentation to a suite of leading debug tools, our goal is to make your design cycle quick and efficient, and to help you get your embedded products on the market quickly. Add this to the improved time to market achieved with utilizing commercial off-the-shelf products like the industry-standard x86 AMD Opteron processor.



©2009 Advanced Micro Devices, Inc. All rights reserved. AMD, the AMD Arrow logo, AMD Opteron, AMD Virtualization, AMD PowerNowl and combinations thereof, are trademarks of Advanced Micro Devices, Inc. HyperTransport is a licensed trademark of the HyperTransport Technology Conscribum. Other names are for informational purposes only and may be trademarks of their respective owners



AMD Opteron™ Processor Model	Order Part Number (OPN) Identifier	Core Frequency	Cache	Peak Power (worst case TDP)
Quad-Core AMD Opteron™ Processors Socket F (1207)/Lidded 1207 pad LGA package				
83VS	OE83VSWHP4DGIE	2.8GHz	L2: 512KB x 4 L3: 6MB	115W
83QS HE	OE83QSMAP4DGIE	2.4GHz		71W
23VS	OE23VSWHP4DGIE	2.8GHz		115W
23QS HE	OE23QSMAP4DGIE	2.4GHz		71W
23KS EE	OE23KSFLP4DGIE	2.0GHz		50W
13QS HE	OE13QSMAP4DGIE	2.4GHz		71W
13KS EE	OE13KSFLP4DGIE	2.0GHz		50W
Dual-Core AMD Opteron™ Processors Socket F (1207)/Lidded 1207 pad LGA package				
8214 HE	OSP8214GAU6CYE	2.2GHz	L2: 1MB x 2	68W
8210 EE	OSH8210GAS6CYE	1.8GHz		45W
2214 HE	OSP2214GAU6CXE	2.2GHz		68W
2210 EE	OSH2210GAS6CXE	1.8GHz		45W
2208 HE	OSP2208GAA5CXE	1.8GHz		68W
1214 HE	OSP1214GAU6DGE	2.2GHz		68W
1210 EE	OSH1210GAS6DGE	1.8GHz		45W
Single-Core AMD Opteron™ Processor Socket F (1207)/Lidded 1207 pad LGA package				
2204 HE	OSH2204GAA4DTE	1.8GHz	L2: 512KB x 1	45W



#### What about performance-per-watt?

It's a growing concern from the data center to embedded systems – how to increase computing performance without incurring excess power draw, additional cooling requirements, or taking up more space in either real estate or form factor. AMD was first to recognize that the processor could offer part of the solution in reducing total cost of ownership.

- → Microprocessor architecture AMD64 processor design helps reduce the overall system power budget with integration of the NorthBridge, while multi-core processors are designed to offer increased performance, with higher compute density and scalability
- → **Low power processors** AMD provides a consistent roadmap with a variety of wattage options
- → Low operational costs Reduced power draw and heat dissipation means low data center energy costs. Features like AMD PowerNow!™ technology with Optimized Power Management help deliver performance on demand and helps minimize power consumption
- → AMD Opteron processors with DDR2 support offer a seamless upgrade path from dual-core to quad-core computing with minimum impact to power and thermal consideration

#### ABOUT AMD

AMD (NYSEAMD) designs innovative microprocessors and low-power processor solutions for the computer, communications, and consumer electronics industries. AMD is dedicated to delivering standards-based, customer-focused solutions for technology users, ranging from enterprises and governments to individual consumers. 42350C

#### WWW.AMD.COM

One AMD Place P.O. Box 3453 Sunnyyale, CA 94088-3453, USA Tel: 408-749-4000 or 800-538-8450 TWX: 910-339-9280 TELEX: 34-6306

#### TECHNICAL SUPPORT

USA & Canada: 800-222-9323, Opt 2 or 408-749-5703 USA & Canada PC Processors Only: 408-749-3060 USA & Canada E-mail: hw.support@amd. com

Latin America E-mail (Spanish): amdsp@vermont.com.br Latin America E-mail (Portuguese): amdbr@vermont.com.br Argentina: 0800-333-0219 Brazil: 0800-557686 Chile: 123-00-209-110 Mexico: 01-800-123-4709 Europe & UK: +44-0-1276-803299 Europe & UK Fax: +44-0-1276-803298 France: 0800-908-621 Germany: +49-89-450-53199 Italy: 800-877224 Europe E-mail: euroctech@amd.com

China Fax: 86-10-8518-1777 Hong Kong Fax: 852-2956-0588 Japan Fax: 81-3-3346-7848 Korea Fax: 82-2-3468-2601 Talwan Fax: 886-2-2655-7855

Asia E-mail: asia.support@amd.com

#### LITERATURE ORDERING

On the Web:
www.amd.com/support/literature.html
USA & Canada: 800-222-9323, Opt 1
USA & Canada E-mail:
amdilterature@comac.com
Europe E-mail: eurolt@amd.com

China Fax: 86-10-8518-1777 Hong Kong Fax: 852-2956-0588 Japan Fax: 81-3-3346-7848 Taiwan Fax: 886-2-2655-7855

### **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Microprocessors - MPU category:

Click to view products by Cypress manufacturer:

Other Similar products are found below:

MC68302EH20C MC7457RX1000LC MC7457RX1267LC A2C00010998 A A2C52004004 R5F117BCGNA#20 R5F52106BDLA#U0
R5S72690W266BG#U0 ADJ3400IAA5DOE MPC8245TVV266D MPC8245TZU300D MPC8260ACVVMHBB MPC8323ECVRAFDCA
MPC8536ECVJAVLA BOXNUC5PGYH0AJ 20-668-0024 P1010NSN5DFB P2020NXE2HHC P5020NSE7TNB P5020NSE7VNB
LS1020ASN7KQB LS1020AXN7HNB LS1020AXN7KQB A2C00010729 A A2C00039344 T1022NSE7MQB T1022NXN7PQB
T1023NSE7MQA T1024NXE7PQA T1042NSN7MQB T1042NXN7WQB T2080NSN8PTB T2080NXE8TTB T2081NXN8TTB
R5F101AFASP#V0 MC68302CEH20C TS68040MF33A MPC8260ACVVMIBB MPC8280CZUUPEA MPC8313ECVRAFFC
MPC8313ECVRAGDC MPC8313EVRADDC MPC8313EVRAFFC MPC8313VRADDC MPC8323EVRAFDCA BOXSTCK1A8LFCL
UPD78F0503AMCA-CAB-G UPD78F0513AGA-8EU-AT UPD78F0730MC-CAB-AX DF2134BFA20V