

| Model          | POS.1       | POS.2 | POS.3       |  |  |
|----------------|-------------|-------|-------------|--|--|
| No.            |             |       | Ä           |  |  |
| 2UD1           | ON          | NONE  | ON          |  |  |
| Term.<br>Comm. | 2-3,5-6     |       | 2-1,5-4     |  |  |
| SCHEMATIC      | 2 Comm. 0 3 | N/A   | 2 Comm. 0 3 |  |  |
| SCHEMATIC      | 5 Comm. 6   |       | 5 Comm.     |  |  |

SWITCH FUNCTION

**SPECIFICATIONS** 

**MECHANICAL LIFE:** 40,000 make-and-break cycles. **CONTACT RATING:** 0.4 VA max. @ 20 V AC or DC max.

**CONTACT RESISTANCE:** Below 100 m  $\Omega$  typ. initial @ 2-4 V DC, 100 mA.

(B) INSULATION RESISTANCE: 500 M $\Omega$  min.

DIELECTRIC STRENGTH: 500 Vrms min. @ sea level.

OPERATING TEMPERATURE: - 30°C to 85°C

**MATERIALS** 

HOUSING AND BASE: Glass filled nylon 6/6 or 4/6, flame retardant, heat stabilized (UL94V-0)

ACTUATOR: Glass filled nylon 6/6, flame retardant, heat stabilized(UL94V-0), with standard internal o-ring seal.

**STATIONARY CONTACTS:** Copper alloy, with silver plate over nickel plate.

**SWITCH SUPPORT:** Steel with nickel plated.

**TERMINALS:**C268, with gold plate over nickel plate.

TERMINAL SEAL: Epoxy. All terminals insert molded.

RoHS:2002/95/EC

NOTE: Specifications and materials listed above are for switches with standard options.

For information on specific and custom switches, consult Customer Service Center.



.100 2.54

| 德利威電子股份                                 | 上四八三  |
|---|-------|
| 一一一一一一一一一一一一一一一一一一一一一一一一一一一一一一一一一一一一一一一 | 石服から  |
|   | 万一八ムコ |
| BALLYWELL ELECTRON                      |       |

|   |            |         |                              |             |                     | 1                       |                         |                |            |        |
|---|------------|---------|------------------------------|-------------|---------------------|-------------------------|-------------------------|----------------|------------|--------|
|   | 符號         | 原尺寸     | 修改後尺寸                        | 變更日期        | SCALE (比例): 3:2     | TITLE                   | Sealed Ultraminiature T | oggle Switches | SIZE<br>圖紙 | A4     |
| 1 | A          |         | 圖面重新整理                       | NOV-13-2008 | TOLERANCE (公差):     | 圖名<br>DWG NO.           |                         |                | UNIT       | inch   |
| 2 | B          | 1.000ΜΩ | Insulation resistance修正500MΩ | AUG-24-2009 | 0.00 mm ± 0.25mm    | (4年):   原味   2UI)1I1A1N |                         | M2RES          |            | mm     |
| 3 | $\bigcirc$ |         |                              |             | 0.0 mm ± 0.40mm     | REV.                    | C DATE MAR -            | 23 - 2006      | SHEET      | 1 of 1 |
| 4 | (D)        |         |                              |             | ANGULAR : ± 5°      | 版本<br>CHECKED BY        | 日 期                     | DRAWN BY       | 饭 數        |        |
| 5 | Œ)         |         |                              |             | FILE NAME: 2UDP0010 | 審核                      | RICHARD                 | 製圖             | ODA        | DA     |

.100 2.54

ø.035

Ø0.89

PC MOUNTING

DAILYWELL 德利威電子股份有限公司 版本:C 表單編號:QR-0507

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Toggle Switches category:

Click to view products by Dailywell manufacturer:

Other Similar products are found below:

8928K478 8951K2998 8951K3310 8956K1283 8956K1286 8956K1287 8961K155 8A1-C-222 020017-13 0090-0001 0121-0015 CS115W CS120W CS215I CS8275 637H/25 6663 7101SPDV30BE 7103SDV30BE 7105D 7108P3YAV2BE 71YY50282 7209SY9AQE 7209SYCBE 7300K36 7301K38 7301SS24484 7303KZQE 7306K36 7310K36 7503K21 7506K4 7565K6 7595K6 7660K12 7691K14 7700K1 7704K3 8391K108 8396K108 8811K17 8812K14 8824K14 8825K5 8828K13 8835K3 8858K44 8E4011 1202W A201SCWZB04