

SWITCH FUNCTION

SCHEMATIC

م *۹*

Term. Comm.

OPEN

8AS9

OFF

MOM

<u>۔</u>

Model No.

POS.1

POS.2

MATERIALS

CASE & BUSHING - Glass filled nylon 66, flame retardand, heat stabilized (UL94V-0).

PLUNGER - Thenoplastic Polyester (UL 94V-0), with intenal O-ring seal

SWITCH SUPPORT - Brass or steel electrotin plated. **CONTACT** - Silver or gold plated Copper alloy. **ROHS** - 2002/95/EC

INSULATION RESISTANCE: 1,000M Ω min.
DIELETRIC STRENGTH: 1,000 V RMS@sea level.
OPERATING TEMPERATURE: -30°C to 85°C.

MECHANICAL LIFE: 50,000 make-and-break cycles. CONTACT RESISTANCE: 20m Ω max. initial @ 2-4VDC

100mA for both silver and gold plated contacts.

SPECIFICATIONS

RATING

R.G: 0.4 Volt-Amps(VA) max. @20V max.(AC or DC)
Q.C.S.K: 3Amps @120VAC or 28VDC.
1Amp @250VAC.

德利威電子股份有限公司 DAILYWELL ELECTRONICS CO.,LTD.

	5	4	ယ	2	_	/
DAILYWELL	Œ	Ф	0	₿	A	符號
/ELL						原尺寸
						修改後尺寸
德利威電子股份有限公司						變更日期
	SCALE (比例): 3:2 TOLERANCE (公差): 0.00 mm ± 0.25mm 0.0 mm ± 0.40mm ANGULAR:±5° FILE NAME: 8ASP0111					
版本: C	審核	CHECKED BY	REV.	圖號	DWG NO	
	RICHARD		A DATE JUN - 26 - 2007	8AS9P1A1M2RES		Sealed Sub - Miniature Pushbutton Switches
表單編號:QR-0507	火火	DRAWN BY	26 - 2007			hbutton Switches
QR-0507	FION	坂 製	SHEET 1 of 1	單位 mm	UNIT I	SIZE A4

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Pushbutton Switches category:

Click to view products by Dailywell manufacturer:

Other Similar products are found below:

LW1L-M1C10V-A LW2L-A1C20M-GD LW2L-M1C20M-A 60324L M7E-HRN2 67021K512 67081K512X 701PB580 719-5504-000

MDPSSGLFS 810KSV30B MML21KA3ABK MML23KA3AC05K-001 MML23KW3AA01W 8418K2 8646AB6X718UL 8646ABUL

FSDWH 9001KXRK 9001T8BK 9533CD4+U574+U4922 1203MRA A22EM01S A595 1202A6 12037A2ULCSA 1203A2UL ABD122N
B 1211390004 ABN111-Y ABN400-R 1211500044 1211580012 1212MRA 1232A6NF RA3CSH6A 1241.1183.7047 1241.2511

1241.3428 1223A2ULCSA 1223MRA 1232AX2119 1241.1183.8000 1241.1183.8029 1241.2506 1241.2606 12MA6 1301940184

RELBARF6X10(PLASTIC) 13435AG