



本公司智慧財產,未經同意不得複製 DAILYWELL copyright, may not be used without permission from DAILYWELL









SWITCH FUNCTION

TERMINAL PLATING

股

Q = Gold flash over silver

C = Gold over silver

R = Gold

雷

德利威	1
10.06.2015	
工程管制	1

.143 3.63	.070 1.78 .070 1.78 .040 .030 0.77 .140 3.56 .080 .040 1.02 .040 1.02 .040 1.02 .040 1.02 .030 .040 1.02 .030 .040 1.02 .030 .040 1.02 .030 .040 .030 .040 .030 .040 .030 .040 .030 .040 .030 .040 .030 .040 .030 .040 .030 .040 .030 .040 .030 .040 .035 .040 .035 .040 .035 .040 .040 .035 .040 .040 .035 .040 .040 .035 .040 .040 .035 .040 .040 .035 .040 .040 .040 .040 .040 .040 .050 .040 .050 .040 .050 .040 .050 .040 .050 .040 .040 .050 .040 .050 .040 .050 .040 .050 .040 .050 .040 .050 .040 .050 .040 .050 .050 .050 .040 .050
	1.02 P.C. MOUNTING

SPECIFICATIONS

MECHANICAL LIFE: 50,000 make-and-break cycles. CONTACT RESISTANCE: 20mΩ max. initial @ 2-4VDC 100mA for both silver and gold plated contacts. INSULATION RESISTANCE: 1,000MΩ min. DIELECTRIC STRENGTH: 1,000 Vrms min.@sea level. OPERATING TEMPERATURE: -30°C to 85°C. MATERIALS CASE & BUSHING - Glass filled nylon 6/6, flame retardant, heat stabilized (UL94V-0). PLUNGER - Thermoplastic Polyester (UL 94V-0), with intenal O-ring seal. SWITCH SUPPORT - Brass ,tin plated. CONTACT/TERMINALS - Copper alloy. RoHS & Lead Free

							CLL CLC	CIRCINICS V	U.,L	- I D.
\square	符號	原尺寸	修改後尺寸	變更日期	SCALE (比例): 3:2	TITLE	Sealed Sub - Miniature Pushbutton Switches(SMT		SIZE	
1	A		取消端子沾錫規範	MAY-31-2013		圖名			圖紕	A4
1	_		4人7月2111月7日13月7日4日	10011 01 2010	│ TOLERANCE (公差):	DWG NO.	000		UNIT	inch
2	B	依據ECN GC13081301,修訂8.8尺寸		SEP-21-2015	$-0.00 \text{ mm} \pm 0.25 \text{mm}$	圖 號	8858	BMTRES	單位	mm
3	(\mathbb{C})	nylon 4/6	nylon 6/6	OCT-06-2015	$0.0 \text{ mm} \pm 0.40 \text{mm}$	REV.		MAY - 25 - 2009	SHEET	1 of 1
4	6				_	版本	D 日 期	WAT - 25 - 2009	張數	
4	\bigcirc				ANGULAR : ± 5°	CHECKED BY		DRAWN BY		
5	Ē				FILE NAME : 8BSP0057	審核	RICHARD	製 圖	IREN	IE

DAILYWELL

德利威電子股份有限公司

版本:C

(A)

Q

С

R

CONTACT PLATING

Silver

Gold over Silver

Gold

表單編號: QR-0507

RATINGS

0.4 Volt-Amps(VA) max. @20V max. (AC or DC)

百

3 Amps @120 VAC or 28VDC

1 Amps @250 VAC

NICC

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Pushbutton Switches category:

Click to view products by Dailywell manufacturer:

Other Similar products are found below :

LW1L-M1C10V-A LW2L-A1C20M-GD LW2L-M1C20M-A 60324L M7E-HRN2 67021K512 67081K512X 701PB580 719-5504-000 MDPSSGLFS 810KSV30B MML21KA3ABK MML23KA3AC05K-001 MML23KW3AA01W 8418K2 8646AB6X718UL 8646ABUL FSDWH 9001KXRK 9001T8BK 9533CD4+U574+U4922 1203MRA A22EM01S A595 1202A6 12037A2ULCSA 1203A2UL ABD122N-B 1211390004 ABN111-Y ABN400-R 1211500044 1211580012 1212MRA 1232A6NF RA3CSH6A 1241.1183.7047 1241.2511 1241.3428 1223A2ULCSA 1223MRA 1232AX2119 1241.1183.8000 1241.1183.8029 1241.2506 1241.2606 12MA6 1301940184 RELBARF6X10(PLASTIC) 13435AG