

|                | POS.1  | POS.2 |  |  |
|----------------|--------|-------|--|--|
| Model<br>No.   | 4      | 1     |  |  |
| 8MS9           | OFF    | MOM   |  |  |
| Term.<br>Comm. | OPEN   | 1-3   |  |  |
| SCHEMATIC      | OF EIN |       |  |  |

#### SWITCH FUNCTION

|   | PART NO. | PART NAME       | Q'TY |
|---|----------|-----------------|------|
| 1 | MNU-2M01 | 10-48 INCH NUTS | 2    |
| 2 | MNU-2M03 | LOCKING WASHER  | 1    |

FILE NAME:HARDWARE-0003

### SPECIFICATIONS (A)

Without locking ring.

PANEL MOUNTING

.179 4.55

MECHANICAL LIFE: 50,000 make-and-break cycles.
CONTACT RESISTANCE: 20 mΩ max. initial @ 2-4VDC

100mA for both silver and gold plated contacts.

.060

1.53

Epoxy seal

修改後尺寸

**INSULATION RESISTANCE:** 1,000 M  $\Omega$  min.

DIELECTRIC STRENGTH: 1,000 Vrms min.@sea level.

原尺寸

Mechanical life修正60,000→50,000

按鈕棒材質說明改為Nylon 6/6,black.

OPERATING TEMPERATURE: -30°C to 85°C.

#### **MATERIALS**

.030

0.76

.060 1.52

SOLDER LUG

CASE - Diallyl phthalate(DAP)( UL94V-0 )

B PLUNGER - Nylon 6/6, black.

**BUSHING -** Brass,nickel plated

**HOUSING - Stainless Steel** 

**CONTACT -** Brass.

**TERMINAL** - Copper alloy.

**RoHS & Lead Free** 

|   | CONTACT PLATING  | TERMINAL PLATING | RATINGS                                     |
|---|------------------|------------------|---|
| Q | Silver           | Silver           | 3 Amps @120 VAC or 28VDC                    |
| С | Gold over Silver | Gold over silver | 1 Amps @250 VAC                             |
| R | Gold             | Gold             | 0.4 Volt-Amps(VA) max. @20V max. (AC or DC) |

# 德利威電子股份有限公司 DAILYWELL ELECTRONICS CO.,LTD.

| 變更日期        | SCALE (比例): 3:2     | TITLE      | Sub               | Miniatur    | o Duchhi  | itton Switches | SIZE         | Λ.4    |
|-------------|---------------------|------------|-------------------|-------------|-----------|----------------|--------------|--------|
| JUL-05-2011 | 00/ (CL/)): 0.2     | 圖 名        | Sub -             | wiii iiatui | e rusiibu | illon Switches | 加侧           | A4     |
| 002 00 2011 | TOLERANCE (公差):     | DWG NO.    | 01400040051440505 |             |           |                | UNIT         | inch   |
| APR-13-2018 | 0.00 mm ± 0.25mm    | 圖 號        | 8MS9P1B05M1QES-5  |             |           | 單位             | mm           |        |
|             | 0.0 mm ± 0.40mm     | REV.<br>版本 | С                 | DATE<br>日期  | SEP -     | 13 - 2006      | SHEET<br>張 數 | 1 of 1 |
|             | ANGULAR: ±5°        | CHECKED BY |                   |             |           | DD AVAN DV     | 張數           |        |
|             | FILE NAME: 8MSP0269 | 審核         |                   | 陳燈財         |           | DRAWN BY 制 圖   | BLUE         |        |

04.13.2018

工程管制

DAILYWELL

符號

(A)

(B)

(D)

德利威電子股份有限公司

版本: C 表單編號: QR-0507

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Pushbutton Switches category:

Click to view products by Dailywell manufacturer:

Other Similar products are found below:

LW1L-M1C10V-A LW2L-A1C20M-GD LW2L-M1C20M-A 60324L M7E-HRN2 67021K512 67081K512X 701PB580 719-5504-000

MDPSSGLFS 810KSV30B MML21KA3ABK MML23KA3AC05K-001 MML23KW3AA01W 8418K2 8646AB6X718UL 8646ABUL

FSDWH 9001KXRK 9001T8BK 9533CD4+U574+U4922 1203MRA A22EM01S A595 1202A6 12037A2ULCSA 1203A2UL ABD122N
B 1211390004 ABN111-Y ABN400-R 1211500044 1211580012 1212MRA 1232A6NF RA3CSH6A 1241.1183.7047 1241.2511

1241.3428 1223A2ULCSA 1223MRA 1232AX2119 1241.1183.8000 1241.1183.8029 1241.2506 1241.2606 12MA6 1301940184

RELBARF6X10(PLASTIC) 13435AG