| T | | SII 2.7±0.2 | BOTTOM VIEW | | | | | | | |
|-------------------------------|--------------------|----------------|-----------------------------|------------------|---------------------------|------------|-------------|------------|-------------|------------|
| | | | 84.5±0.2 | ø0.45±0.02 | | | | Term.2 | 2 | |
| Specifications | | | Notes | | Revision History | | | | | |
| Description | Value | Unit | | | Version | | Description | 1 | Date | Approved |
| Directivity | Omnidirectional | | 1) All dimensions are in mm | 1 | Released from Engineering | | | 10/21/2013 | J.S | |
| Technology | Electret Condenser | | 2) All parts meet RoHS | | | | | | | |
| Sensitivity | -42 | (dB) | 1 | | | | | | | |
| Frequency Range | 50 ~ 16,000 | (Hz) | 4 | | | | | | | |
| Rated Voltage | 2 | (V) | | | | | | | | |
| Output Impedance | 2,200 | (Ohm) | | | | | | | | |
| Connection Method | PC Pins | | | | | | | | | |
| Voltage Range | 2 ~ 10 | (V) | | | | | | _ | | |
| Max Rated Current | 0.5 | (mA) | | | Drawn by | Date | Checked by | Date | Approved by | Date |
| Minimum Signal to Noise Ratio | >60 | (dB) | | | A.B. | 10/21/2013 | C.E. | 10/21/2013 | J.S | 10/21/2013 |
| Operating Temperature | -20 ~ +60 | °C | | phone M0044202-7 | | | | | | |
| Storage Temperature | -25 ~ +70 | °C | | | | | | | | |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Microphones category:

Click to view products by DB Unlimited manufacturer:

Other Similar products are found below :

BCM40130LFC-42-JST-ZHR-2 TO38-30702-B20 FB-EI-31809-000 SPM04C-38/1186-T/R BCM40130SBC-42 LF TOW-1242P-R BCM9745-44 BCM9765 BCM9767P LD-MC-0905P LD-MC-6035 LD-MC-9765 PMOF-9745S-42UQ ROM-2235L-HD-R CMC-4015-130T CMC-6050-40T CMC-6035-130T CMC-6015-47P BCM9745P-44 BCM9767-42 254-ECM644-RO LD-MC-4011 LD-MC-6027 LD-MC-6035P LD-MC-6035W LD-MC-9765P LD-MC-9765W FG-23629-D65 PNR-23539-000 254-FP270-RO BCM9765P-44 CMC-5042PF-AC CMC-6010-42L100 CMC-9745-L100 CMC-3015-44T CMC-4015-25T CMC-6013-38T CMC-6022-37L100 CMC-6027-24T CMC-6027-32T GMI4522P-2C-30db GMI4522P-2C-50db GMI4522P-2C-52db GMI6027P-2C66DB GMA3526H10-B26 GMA4030H11-F26 GMI4015-32DB GMI4015-40DB GMI4015P-36DB GMI4015P-46DB