TOP VIEW			SIDE VIEW		ANGLED VIEW					
TERMINAL 2 (RMINAL 1 (+)		1.5T 1.5T 1.5T 1.5T 1.5T 1.5T 1.5T		6.0±0.1	"DO"	en Free PCB T [™] Marking 1.5±0.1 ↓ BLACK CLOT 5.3x0.3T	Ή	
Spec	cifications				Revision History					
Description	Value Unit		Notes		Version	Description		Date	Approved	
Directivity	Omnidirectional		1) All dimensions are in mm	1	Released from Engineering		10/21/2013	J.S		
Technology	Electret Condenser		2) All parts meet RoHS							
Sensitivity	-44	(dB)]							
Frequency Range	40 ~ 20,000	(Hz)	1							
Rated Voltage	2	(∨)								
Output Impedance	2,200	(Ohm)								
Connection Method	Solder Pads									
Voltage Range	1~10	(V)								
Max Rated Current	0.45	(mA)			Drawn by	Date	Checked by	Date	Approved by	Date
Minimum Signal to Noise Ratio	>60	(dB)			A.B.	10/21/2013	C.E.	10/21/2013	J.S	10/21/2013
Operating Temperature	-40 ~ +85	°C		Electret Condenser Micro	phone	MO064402-3				
Storage Temperature	emperature -40~+85 °C DB UNLIMITED									

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Microphones category:

Click to view products by DB Unlimited manufacturer:

Other Similar products are found below :

BCM40130LFC-42-JST-ZHR-2 TO38-30702-B20 SPM04C-38/1186-T/R BCM4013OSBC-42 LF TOW-1242P-R BCM9745-44 BCM9765 BCM9767P LD-MC-0905P LD-MC-6035 LD-MC-9765 PMOF-9745S-42UQ ROM-2235L-HD-R CMC-4015-130T CMC-6050-40T CMC-6035-130T CMC-6015-47P BCM9745P-44 BCM9767-42 254-ECM644-RO LD-MC-4011 LD-MC-6027 LD-MC-6035P LD-MC-6035W LD-MC-9765P LD-MC-9765W FG-23629-D65 PNR-23539-000 254-FP270-RO BCM9765P-44 CMC-5042PF-AC CMC-6010-42L100 CMC-9745-L100 CMC-3015-44T CMC-4015-25T CMC-6013-38T CMC-6022-37L100 CMC-6027-24T CMC-6027-32T GMI4522P-2C-30db GMI4522P-2C-50db GMI4522P-2C-52db GMI6027P-2C66DB GMA3526H10-B26 GMA4030H11-F26 GMI4015-32DB GMI4015-40DB GMI4015P-36DB GMI4015P-46DB GMI4015P-54DB