

Specifications			Notes		Revision History						
Description	Value	Unit	Notes		Version	Description			Date	Approved	
Directivity	Omnidirectional		1) All dimensions are in mm unless otherwise noted		1	Released from Engineering			10/21/2013	J.S	
Technology	Electret Condenser		2) All parts meet RoHS								
Sensitivity	-44	(dB)									
Frequency Range	40 ~ 20,000	(Hz)									
Rated Voltage	2	(V)									
Output Impedance	2,200	(Ohm)									
Connection Method	PC Pins										
Voltage Range	1~10	(V)									
Max Rated Current	0.45	(mA)			Drawn by	Date	Checked by	Date	Approved by	Date	
Minimum Signal to Noise Ratio	>60	(dB)			A.B.	10/21/2013	C.E.	10/21/2013	J.S	10/21/2013	
Operating Temperature	-40 ~ +85	°C		Floatrot Condonsor Micro	Electret Condenser Microphone		MO064402-4				
Storage Temperature	-40 ~ +85	°C	DB UNLIMITED	Liectret Condenser Microphone		1410004402-4					

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Microphones category:

Click to view products by DB Unlimited manufacturer:

Other Similar products are found below:

BCM4013OLFC-42-JST-ZHR-2 TO38-30702-B20 FB-EI-31809-000 SPM04C-38/1186-T/R BCM4013OSBC-42 LF TOW-1242P-R
BCM9745-44 BCM9765 BCM9767P LD-MC-0905P LD-MC-6035 LD-MC-9765 PMOF-9745S-42UQ ROM-2235L-HD-R CMC-4015130T CMC-6050-40T CMC-6035-130T CMC-6015-47P BCM9745P-44 BCM9767-42 254-ECM644-RO LD-MC-4011 LD-MC-6027 LD-MC-6035P LD-MC-9765P LD-MC-9765W FG-23629-D65 PNR-23539-000 254-FP270-RO BCM9765P-44 CMC-5042PFAC CMC-6010-42L100 CMC-9745-L100 CMC-3015-44T CMC-4015-25T CMC-6013-38T CMC-6022-37L100 CMC-6027-24T CMC-6027-32T GMI4522P-2C-30db GMI4522P-2C-50db GMI4522P-2C-52db GMI6027P-2C66DB GMA3526H10-B26 GMA4030H11-F26
GMI4015-32DB GMI4015-40DB GMI4015P-36DB GMI4015P-46DB