TOP VIEW			SIDE VIEW		BOTTOM VIEW					
			2.7±0	.2						
Specifications			Notes			Revision History				
Description	Value	Unit			Version	Description			Date	Approved
Directivity	Unidirectional		1) All dimensions are in mm unless otherwise noted		1	Released from Engineering		neering	2/9/2014	J.S.
Technology	Electret Condenser		2) All parts meet RoHS							
Sensitivity	-46	(dB)								
Frequency Range	100 ~ 10,000	(Hz)	4							
Rated Voltage	2	(V)	ļ							
Output Impedance	2,200	(Ohm)								
Connection Method	Solder Pads									
Voltage Range	1.0 ~ 10.0	(V)								
Max Rated Current	0.5	(mA)			Drawn by	Date	Checked by	Date	Approved by	Date
Min. Signal to Noise Ratio	>55	(dB)			G.W.	10/31/2013	C.E.	1/16/2014		
perating Temperature -10 ~ +50 °C Electret Condenser Microp				ophone	Dhone MU064602-1					
orage Temperature -20 ~ +60 °C DB UNLIVITED Electret condenser interopriorie										

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Microphones category:

Click to view products by DB Unlimited manufacturer:

Other Similar products are found below :

BCM40130LFC-42-JST-ZHR-2 TO38-30702-B20 FB-EI-31809-000 SPM04C-38/1186-T/R BCM40130SBC-42 LF TOW-1242P-R BCM9745-44 BCM9765 BCM9767P LD-MC-0905P LD-MC-6035 LD-MC-9765 PMOF-9745S-42UQ ROM-2235L-HD-R CMC-4015-130T CMC-6050-40T CMC-6035-130T CMC-6015-47P BCM9745P-44 BCM9767-42 254-ECM644-RO LD-MC-4011 LD-MC-6027 LD-MC-6035P LD-MC-6035W LD-MC-9765P LD-MC-9765W FG-23629-D65 PNR-23539-000 254-FP270-RO BCM9765P-44 CMC-5042PF-AC CMC-6010-42L100 CMC-9745-L100 CMC-3015-44T CMC-4015-25T CMC-6013-38T CMC-6022-37L100 CMC-6027-24T CMC-6027-32T GMI4522P-2C-30db GMI4522P-2C-50db GMI4522P-2C-52db GMI6027P-2C66DB GMA3526H10-B26 GMA4030H11-F26 GMI4015-32DB GMI4015-40DB GMI4015P-36DB GMI4015P-46DB