		TOP	VIEW	SIDE V	/IEW					
	Q8.9 _{20,3}	10.0±0	.1 100001		03±0.01).1±0.02					
Specifications				Revision History						
Description	Value	Unit		Version	Description			Date	Approved	
Resonant Frequency	4,500	(Hz)	1) All dimensions are in mm u	1	Released from Engineering			10/21/2013	J.S	
Resonant Impedance (Max)	800	(Ohm)	2) All parts meet RoHS							
Max Input Voltage	30	(V)								
Capacitance	15,000	(pF)								
Plate Material	Alloy									
Operating Temperature	-20 ~ +80	°C								
Storage Temperature	-20 ~ +80	°C								
							1			
					Drawn by A.B.	Date 10/21/2013	Checked by C.E.	Date 10/21/2013	Approved by J.S	Date 10/21/2013
				, i.b.	P10045-1					

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Speakers & Transducers category:

Click to view products by DB Unlimited manufacturer:

Other Similar products are found below :

 FC-30814-P127
 AS02832MR-2-R
 PB-1220PE
 PB-2015PQ
 900-00001
 AB2025B-LW50-R
 SWFK-31736-000
 PT-2065FW
 PT-4175W
 AT

 2830-TW-LW35-R
 ED-30761-000
 CI-30120-A42
 SMT-0440-T-2-R
 PB-0927PQ
 BF-7083-000
 SMS2020-08H4.5 LF
 BDT1717

 08H6.5W56MLF
 GSPK1003PN-8R0.2W-L100
 GSPK151103TN-8R0.2W
 GSPK2014035PN-8R0.5W-L100
 AS03608MR-LW100-R
 24520

 SMT-0540-S-2-R
 1450069
 9091653
 9091661
 IPS-G6000-5
 9090231
 FS50MS0820-H9.7
 FS4014-4-2W
 PBM4-13.B29R.A115.0663
 PBM4

 13.B31R.A115.0663
 PBM4-13.B33R.A115.0663
 PBM4-13.B35R.A115.0663
 A-10-6-BG360-HD1Z-GA-M4Z-ZW
 A-10-6-BG410-HD1Z

 AA-AGZ-ZW
 A-10-6-BG410-HD1Z-AA-M4Z-ZW
 A-10-6-BG310-HD1Z-GA-M4Z-ZW
 A-10-6 BG310-HD1Z-AA-AGZ-ZW
 A-10-6

 BG310-HD1Z-AA-AGZ-ZW
 A-10-6-BG325-HD1Z-AA-M4Z-ZW
 A-10-6-BG340-HD1Z-AA-AGZ-ZW
 A-10-6-BG340-HD1Z-AA-AGZ-ZW
 A-10-6-BG340-HD1Z-AA-AGZ-ZW
 A-10-6-BG340-HD1Z-AA-AGZ-ZW

 A-10-6-BG340-HD1Z-GA-M4Z-ZW
 A-10-6-BG340-HD1Z-AA-AGZ-ZW
 A-10-6-BG340-HD1Z-AA-AGZ-ZW
 A-10-6-BG340-HD1Z-AA-AGZ-ZW
 A-10-6-BG340-HD1Z-AA-AGZ-ZW