		TOP	VIEW	SIDE VI	EW						
			Ø9±0.4 Ø12±0.1		. <u>12±0.03</u> . <u>06±0.01</u>						
S	pecifications					Revision History					
Description	Value	Unit		Notes		Description		Date	Approved		
Resonant Frequency	6,500	(Hz)	1) All dimensions are in mm unless otherwise noted		1	Released from Engineering		10/21/2013	J.S		
Resonant Impedance (Max)	700	(Ohm)	2) All parts meet RoHS					-			
Max Input Voltage	30	(V)									
Capacitance	13,000	(pF)									
Plate Material	Alloy										
Operating Temperature	-20 ~ +60	°C									
Storage Temperature	-20 ~ +70	°C									
					Drawn by A.B.	Date 10/21/2013	Checked by C.E.	Date 10/21/2013	Approved by J.S	Date	
						P12065-1				10/21/2013	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Speakers & Transducers category:

Click to view products by DB Unlimited manufacturer:

Other Similar products are found below :

FC-30814-P127
AS02832MR-2-R
PB-1220PE
PB-2015PQ
900-00001
AB2025B-LW50-R
SWFK-31736-000
PT-2065FW
PT-4175W
AT

2830-TW-LW35-R
ED-30761-000
CI-30120-A42
SMT-0440-T-2-R
PB-0927PQ
BF-7083-000
SMS2020-08H4.5 LF
BDT1717

08H6.5W56MLF
GSPK1003PN-8R0.2W-L100
GSPK151103TN-8R0.2W
GSPK2014035PN-8R0.5W-L100
FS5353DS0830-H19.3

TE082703-8
XMLP040BD21F
AS03608MR-LW100-R
24520
SMT-0540-S-2-R
1450069
9091653
9091661
IPS-G6000-5
9090231

FS4014-4-2W
PBM4-13.B29R.A115.0663
PBM4-13.B31R.A115.0663
PBM4-13.B33R.A115.0663
PBM4-13.B35R.A115.0663
A-10-6

BG360-HD1Z-GA-M4Z-ZW
A-10-6-BG410-HD1Z-AA-AGZ-ZW
A-10-6-BG310-HD1Z-AA-M4Z-ZW
A-10-6-BG310-HD1Z-FC-AGZ-ZW

A-10-6-BG316-HD1Z-GA-M4Z-ZW
A-10-6-BG310-HD1Z-AA-AGZ-ZW
A-10-6-BG310-HD1Z-AA-AGZ-ZW
A-10-6-BG325-HD1Z-AA-AGZ-ZW
A-10-6-BG325-HD1Z-AA-AGZ-ZW
A-10-6-BG325-HD1Z-AA-AGZ-ZW
A-10-6-BG325-HD1Z-AA-AGZ-ZW
A-10-6-BG325-HD1Z-AA-AGZ-ZW
A-10-6-BG325-HD1Z-AA-AGZ-ZW
A-10-6-BG325-HD1Z-AA-AGZ-ZW
A-10-6-BG340-HD1Z-AA-AGZ-ZW
A-10-6-BG340-HD1Z-AA-AGZ-ZW
A-10-6-BG340-HD1Z-AA-AGZ-ZW
A-10-6-BG340-HD1Z-AA-AGZ-ZW
A-10-6-BG340-