		TOP	VIEW	SIDE V	IEW					
			Ø27±0.1	-	20±0.05 .43±0.1					
Sp	ecifications		Netze			Revision History				
Description	Value	Unit		Notes	Version		Description		Date	Approved
Resonant Frequency	3,500	(Hz)	1) All dimensions are in mm	unless otherwise noted	1	Releas	ed from Engi	neering	10/21/2013	J.S
Resonant Impedance (Max)	2,500	(Ohm)	2) All parts meet RoHS							
Max Input Voltage	20	(V)								
Capacitance	12,000	(pF)								
Plate Material	Stainless Steel			-						
Operating Temperature	-20 ~ +60	°C]						
Storage Temperature	-20 ~ +70	°C								
					Drawn by	Date	Checked by	Date	Approved by	Date
					A.B.	10/21/2013	C.E.	10/21/2013	J.S	10/21/2013
						P27035-1				

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Speakers & Transducers category:

Click to view products by DB Unlimited manufacturer:

Other Similar products are found below :

 FC-30814-P127
 AS02832MR-2-R
 PB-1220PE
 PB-2015PQ
 900-00001
 AB2025B-LW50-R
 SWFK-31736-000
 PT-2065FW
 PT-4175W
 AT

 2830-TW-LW35-R
 ED-30761-000
 CI-30120-A42
 SMT-0440-T-2-R
 PB-0927PQ
 BF-7083-000
 SMS2020-08H4.5 LF
 BDT1717

 08H6.5W56MLF
 GSPK1003PN-8R0.2W-L100
 GSPK151103TN-8R0.2W
 GSPK2014035PN-8R0.5W-L100
 FS5353DS0830-H19.3

 XMLP040BD21F
 AS03608MR-LW100-R
 24520
 SMT-0540-S-2-R
 1450069
 9091661
 IPS-G6000-5
 9090231
 FS4014-4-2W

 PBM4-13.B29R.A115.0663
 PBM4-13.B31R.A115.0663
 PBM4-13.B33R.A115.0663
 PBM4-13.B35R.A115.0663
 A-10-6-BG360-HD1Z-GA

 M4Z-ZW
 A-10-6-BG410-HD1Z-AA-AGZ-ZW
 A-10-6-BG310-HD1Z-AA-M4Z-ZW
 A-10-6-BG310-HD1Z-GA

 HD1Z-GA-M4Z-ZW
 A-10-6-BG310-HD1Z-AA-AGZ-ZW
 A-10-6-BG310-HD1Z-AA-M4Z-ZW
 A-10-6-BG340-HD1Z-GA

 6-BG316-HD1Z-AA-M4Z-ZW
 A-10-6-BG325-HD1Z-AA-AGZ-ZW
 A-10-6-BG325-HD1Z-AA-AGZ-ZW
 A-10-6-BG340-HD1Z-AA-M4Z-ZW
 A-10-6-BG340-HD1Z-AA-AGZ

 ZW
 A-10-6-BG340-HD1Z-AA-M4Z-ZW
 A-10-6-BG340-HD1Z-AA-M4Z-ZW
 A-10-6-BG360-GT1Z-AA-M4Z-ZW
 A-10-6-BG340-HD1Z-AA-M4Z-ZW

</tabr/>