


## **TOP VIEW**



## SIDE VIEW



## **BOTTOM VIEW**



Specifications			Notes		Revision History					
Description	Value	Unit	1) All dimensions are in mm unless otherwise noted		Version	Description			Date	Approved
Shape	Round				1	Released from Engineering			2/5/2014	J.S.
Resonant Frequency	880	(Hz)	2) All parts meet RoHS							
Frequency Range	880 ~ 20,000	(Hz)								
SPL @ 10cm	85	(dBA)								
Impedance	16	(Ohm)								
Cone Material	Polyethylene Naphthalate									
Nominal Power	0.3	(W)								
Max Power	0.6	(W)								
Mount Type	Flush Mount				Drawn by	Date	Checked by	Date	Approved by	Date
Operating Temperature	-30 ~ +80	°C			G.W.	1/27/2014	C.E.	2/4/2014	J.S.	2/5/2014
Storage Temperature	-30 ~ +80	°C		High Temp Dynamic Speaker		SM160816-1				
Weight	1	(g)	DB UNLIMITED							

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Speakers & Transducers category:

Click to view products by DB Unlimited manufacturer:

Other Similar products are found below:

FC-30814-P127 AS02832MR-2-R PB-1220PE PB-2015PQ 900-00001 AB2025B-LW50-R SWFK-31736-000 PT-2065FW PT-4175W AT-2830-TW-LW35-R ED-30761-000 CI-30120-A42 SMT-0440-T-2-R PB-0927PQ BF-7083-000 CTX323B220 SMS2020-08H4.5 LF

BDT1717-08H6.5W56MLF GSPK1003PN-8R0.2W-L100 GSPK151103TN-8R0.2W GSPK2014035PN-8R0.5W-L100 AS03608MR-LW100-R 24520 SMT-0540-S-2-R 1450069 9091653 9091661 IPS-G6000-5 9090231 FS50MS0820-H9.7 FS4014-4-2W PBM4-13.B29R.A115.0663 PBM4-13.B31R.A115.0663 PBM4-13.B33R.A115.0663 PBM4-13.B35R.A115.0663 A-10-6-BG360-HD1Z-GA-M4Z-ZW A-10-6-BG410-HD1Z-AA-AGZ-ZW A-10-6-BG410-HD1Z-AA-M4Z-ZW A-10-6-BG310-HD1Z-AA-AGZ-ZW A-10-6-BG310-HD1Z-AA-M4Z-ZW A-10-6-BG310-HD1Z-GA-M4Z-ZW A-10-6-BG340-HD1Z-AA-M4Z-ZW A-10-6-BG340-HD1Z-AA-AGZ-ZW A-10-6-BG340-HD1Z-AA-M4Z-ZW A-10-6-BG340-HD1Z-AA-M4