
SIDE VIEW 5.1±Ø0.3 2.1 2.07

BOTTOM VIEW



S	Specifications		Notes V			Revision History					
Description	Value	Unit			Version		Description	1	Date	Approved	
Shape	Round		1) All dimensions are in mm	1	Released from Engineering			10/21/2013	J.S		
Resonant Frequency	280	(Hz)	2) All parts meet RoHS								
Frequency Range	280 ~ 20,000	(Hz)									
SPL @ 10cm	94	(dBA)									
Impedance	8	(Ohm)									
Cone Material	Mylar										
Nominal Power	0.5	(W)									
Max Power	0.8	(W)									
Mount Type	Flush Mount				Drawn by	Date	Checked by	Date	Approved by	Date	
Operating Temperature	-40 ~ +66	°C			A.B.	10/21/2013	C.E.	10/21/2013	J.S	10/21/2013	
Storage Temperature	-40 ~ +66	°C		Dynamic Speaker	=	SM320208-1					
Weight	8.3	(g)		Dynamic Speaker		3IVI3ZUZU8-1					

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Speakers & Transducers category:

Click to view products by DB Unlimited manufacturer:

Other Similar products are found below:

FC-30814-P127 AS02832MR-2-R PB-1220PE PB-2015PQ 900-00001 AB2025B-LW50-R SWFK-31736-000 PT-2065FW PT-4175W AT-2830-TW-LW35-R ED-30761-000 CI-30120-A42 SMT-0440-T-2-R PB-0927PQ BF-7083-000 CTX323B220 SMS2020-08H4.5 LF

BDT1717-08H6.5W56MLF GSPK1003PN-8R0.2W-L100 GSPK151103TN-8R0.2W GSPK2014035PN-8R0.5W-L100 AS03608MR-LW100-R 24520 SMT-0540-S-2-R 1450069 9091653 9091661 IPS-G6000-5 9090231 FS50MS0820-H9.7 FS4014-4-2W PBM4-13.B29R.A115.0663 PBM4-13.B31R.A115.0663 PBM4-13.B33R.A115.0663 PBM4-13.B35R.A115.0663 A-10-6-BG360-HD1Z-GA-M4Z-ZW A-10-6-BG410-HD1Z-AA-AGZ-ZW A-10-6-BG410-HD1Z-FC-AGZ-ZW A-10-6-BG410-HD1Z-GA-M4Z-ZW A-10-6-BG310-HD1Z-AA-AGZ-ZW A-10-6-BG310-HD1Z-AA-M4Z-ZW A-10-6-BG310-HD1Z-GA-M4Z-ZW A-10-6-BG340-HD1Z-AA-M4Z-ZW A-10-6-BG340-HD1Z-AA-AGZ-ZW A-10-6-BG340-HD1Z-AA-M4Z-ZW A-10-6-BG340-HD1Z-AA-AGZ-ZW A-10-6-BG340-HD1Z-AA-M4Z-ZW A-10-6-BG340-HD1Z-AA-M4