	076 5+0 5			BOTTON	A VIEV	N				
			<u>3.6±0.3</u> 37.6±0.5							
	ecifications		Notes			Revision History				
Description	Value	Unit			Version		Description		Date	Approved
Shape	Round		1) All dimensions are in mm	1	Released from Engineering			10/21/2013	J.S	
Resonant Frequency	300	(Hz)	2) All parts meet RoHS							
Frequency Range	300 ~ 12,000	(Hz)	4			ļ				
SPL @ 10cm	106	(dBA)	4							
Impedance	4	(Ohm)								
Cone Material	Mylar					ļ				
Nominal Power	10	(W)								
Max Power	15	(W)					-			
Mount Type	Flush				Drawn by	Date	Checked by	Date	Approved by	Date
Operating Temperature	-20 ~ +55	°C			A.B.	10/21/2013	C.E.	10/21/2013	J.S	10/21/2013
Storage Temperature	-20 ~ +55	°C		Dynamic Speaker			SM760304-1			
Weight	240	(g)		_ ;		51		07 I		

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Speakers & Transducers category:

Click to view products by DB Unlimited manufacturer:

Other Similar products are found below :

 FC-30814-P127
 AS02832MR-2-R
 PB-1220PE
 PB-2015PQ
 900-00001
 AB2025B-LW50-R
 SWFK-31736-000
 PT-2065FW
 PT-4175W
 AT 

 2830-TW-LW35-R
 ED-30761-000
 CI-30120-A42
 SMT-0440-T-2-R
 PB-0927PQ
 BF-7083-000
 SMS2020-08H4.5 LF
 BDT1717 

 08H6.5W56MLF
 GSPK1003PN-8R0.2W-L100
 GSPK151103TN-8R0.2W
 GSPK2014035PN-8R0.5W-L100
 AS03608MR-LW100-R
 24520

 SMT-0540-S-2-R
 1450069
 9091653
 9091661
 IPS-G6000-5
 9090231
 FS50MS0820-H9.7
 FS4014-4-2W
 PBM4-13.B29R.A115.0663
 PBM4 

 13.B31R.A115.0663
 PBM4-13.B33R.A115.0663
 PBM4-13.B35R.A115.0663
 A-10-6-BG360-HD1Z-GA-M4Z-ZW
 A-10-6-BG410-HD1Z 

 AA-AGZ-ZW
 A-10-6-BG410-HD1Z-AA-M4Z-ZW
 A-10-6-BG310-HD1Z-GA-M4Z-ZW
 A-10-6 BG310-HD1Z-AA-AGZ-ZW
 A-10-6-BG310-HD1Z-AA-M4Z-ZW
 A-10-6-BG340-HD1Z-AA-M4Z-ZW
 A-10-6-BG340-HD1Z-AA-AGZ-ZW
 A-10-6-BG340-HD1Z-AA-AGZ-ZW
 A-10-6-BG340-HD1Z-AA-AGZ-ZW
 A-10-6-BG340-HD1Z-AA-AGZ-ZW
 A-10-6-BG340-HD1Z-AA-AGZ-ZW
 A-10-6-BG340-HD1Z-AA-AGZ-ZW
 A-10-6-BG340-HD1Z-AA-AGZ-ZW